



ENERGY STAR® Certified
In all 50 States



Milliken Millwork, Inc. 
WHOLESALE DISTRIBUTORS
Your Doorway to a Beautiful Home

Exterior Doors
Majestic Steel Door
JEL-M-1 Clear

ENERGY PERFORMANCE RATINGS

| Product Description* Default Frame** Wood | U-Factor ¹ /Solar Heat Gain Coefficient (SHGC) | | | |
|---|---|-------------------|--------------------|---------------------|
| | Individual Option Number | | | |
| | 1/4 Lite ≤410† | 1/2 Lite ≤900† | 3/4 Lite ≤1100† | Full Lite >1100† |
| Dual/Clear/Air/.75 | 0.30 | 0.35 | 0.38 | 0.42 |
| | 0.11 | 0.20 | 0.26 | 0.34 |
| | 02277-00001 | 02278-00001 | 02279-00001 | 02280-00001 |
| Dual/Clear/Air/.75 With Grids | 0.30 | 0.35 | 0.38 | 0.42 |
| | 0.10 | 0.17 | 0.23 | 0.30 |
| | 02289-00001 | 02290-00001 | 02291-00001 | 02292-00001 |
| Dual/Clear/Air/.29 | 0.31 | 0.36 | 0.39 | 0.44 |
| | 0.11 | 0.20 | 0.26 | 0.34 |
| | 02253-00001 | 02254-00001 | 02255-00001 | 02256-00001 |
| Dual/Clear/Air/.29 With Grids | 0.31 | 0.36 | 0.39 | 0.44 |
| | 0.10 | 0.17 | 0.23 | 0.30 |
| | 02265-00001 | 02266-00001 | 02267-00001 | 02268-00001 |
| Dual/Clear/Air/.625 | - | - | 0.38 | - |
| | - | - | 0.26 | - |
| | - | - | 02360-00001 | - |
| Dual/Clear/Air/.50 SDL | - | - | 0.38 | 0.42 |
| | - | - | 0.20 | 0.27 |
| | - | - | 02381-00001 | 02382-00001 |
| Triple/Clear/Air/.31/.31 Deco | 0.29 | 0.32 | 0.34 | 0.38 |
| | 0.09 | 0.16 | 0.21 | 0.28 |
| | 02390-00001 | 02391-00001 | 02392-00001 | 02396-00001 |
| Triple/Clear/Air/.24/.24 Deco | - | - | 0.35 | - |
| | - | - | 0.21 | - |
| | - | - | 02400-00001 | - |
| Dual/Clear/Air/.81 With Blinds | - | 0.35 | 0.39 | 0.43 |
| | - | 0.17 | 0.23 | 0.31 |
| | - | 02452-00001 | 02453-00001 | 02454-00001 |
| Triple/Clear/Air/.50/.81 With Blinds/Grids | - | 0.32 | - | 0.36 |
| | - | 0.14 | - | 0.27 |
| | - | 03033-00001 | - | 03034-00001 |
| Flush F02211-00001 | U-Factor ¹ | 0.24 | SHGC | 0.01 |
| Embossed E02212-00001 | U-Factor ¹ | 0.24 | SHGC | 0.01 |
| Air Leakage - ≤0.30 cfm/ft² | | | | |

Manufacturer stipulates that these ratings conform to applicable NFRCC procedures for determining whole product performance. NFRCC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRCC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for other product performance information.

* #glazing layers / spacer type / low-e emissivity (surface) / gap fill / gap width (na=not applicable)

** per NFRCC 100 †square inches †btu/hr'ft²F

*** Numbers below the performance ratings are referenced in the NFRCC Certified Products Directory (e.g., ABC-X-1-00001-00001 or 123-X-1-00001-00001)

www.nfrc.org