



DYC7300

PAVER SEALER WB 7300 Data Sheet

CHARACTERISTICS

DYCO® PAVER SEALER WB™ is a non-yellowing water-proofing sealer designed to seal and protect bare/unsealed cement pavers and surfaces, as well as wood and metal surfaces. As a water-based acrylic engineered with Ambient Cure Cross Linking Technology, PAVER SEALER WB performs like an epoxy coating without all the messy mixing. This durable coating resists hot tire pick-up, cracking and peeling, and provides a mildew resistant barrier. PAVER SEALER WB enhances the true colors of the paver and delivers an attractive “wet-look” finish. PAVER SEALER WB is easy to apply, safe to use over water ways and is environmentally safe.

RECOMMENDED USES

- Concrete Surfaces
- Pavers
- Wood Surfaces
- Galvanized Metal
- Concrete and Tile Roofs

FEATURES/BENEFITS

- Resists Hot Tire Pick-Up
- Resists Mildew
- Resists Cracking & Peeling
- Easy To Apply

FOR ADDITIONAL INFORMATION

See MSDS or call toll-free 1-800-282-7901.

TECHNICAL DATA

Vehicle Type Waterbased Acrylic
 Finish/Sheen Gloss
 Solids by Weight 22.50%
 Solids by Volume 19.50%
 Viscosity #2 Zahn- 19 Sec.
 VOC (less exempt solvents) Less than 100 g/L.
 Weight per Gallon 8.51 LBS

COVERAGE

250 S.F./Gal.
(Actual coverage may vary depending on type of substrate, and application method.)

KEY ATTRIBUTES

Application Temperatures: 50 - 110 °F (10 - 43.33 °C)
 Application Tools: Brush, Roller, or Spray
 Dry Times: Touch - 1 Hour, Foot Traffic – 2 Hour, Vehicle Traffic 48 Hours
 (Dry Time Based on 77 °F (25 °C), 50% Relative Humidity)
 Thinner: Do not thin.
 Clean Up: Soap and Water.

PHYSICAL PROPERTIES

Mildew Resistance .. Excellent
Flash Point..... None





DYC7300

PAVER SEALER WB

7300 Precautions & Application Guide

FOR USE ON: Concrete/cement pavers and surfaces usually found on driveways, walkways, patios and pool decks. PAVER SEALER WB can also be used on galvanized metal, wood decks, and concrete and shingle roofs.

PRECAUTION: Do not freeze. Wear protective clothing and eyewear during application of this product. Do not transport on passenger seats or inside passenger compartment of any vehicle. Store product in cargo area of vehicle, and secure with protective cloths to prevent accidental spill damage. Do not store at temperature above 100°F (37°C). Do not use in drinking water or food systems.

SLIPPERY WHEN WET: Dyco recommends mixing SKID GARD #45 at 0.2lb. (3.2oz.) per gallon to the final coat if surface to be coated is a ramp, steps, or inclined plane; or is exposed to water from rain, sprinklers, pools or other means. If SKID GARD #45 is not available see your paint specialist for a recommendation of a suitable aggregate to be used. NOTE: Adding SKID GARD to non-opaque coatings may alter final appearance. Test coating on a hidden area before applying to the entire surface.

READ AND FOLLOW ALL DIRECTIONS: Surfaces must be clean, dry and sound. Contaminants such as dirt, dust, grease, wax, oil, soap film, rust, mold, mildew, bond breakers and curing compounds must be removed before application. Loose, chipping and peeling of previous coating must be removed before application. Clean surfaces with bleach solution (one (1) part bleach to four (4) parts water) and a stiff bristle brush. If mildew is present, treat with a mildew remover. Rinse with clean water and let dry one (1) to two (2) days before application. Do not apply to damp surfaces or when surface temperature is below 50 °F (10 °C) or above 100 °F (37 °C). Do not apply if rain is prevalent or expected.

PREPARING SURFACES: For new pavers, follow manufacturer's cleaning directions. For existing coated or uncoated surfaces, clean with a degreaser and/or pressure wash.

TINTING: Tinting is not recommended.

APPLICATION: MAKE SURE THE CONCRETE SURFACE IS 100% DRY. Do not thin. Mix thoroughly before use. Apply one (1) coat evenly with a medium nap roller, brush or airless sprayer. If two (2) coats are desired or necessary and to achieve a "wet-look" appearance, apply second coat in the opposite direction of the prior coat. Do not leave puddles or roller marks. Coverage is 400 sq. ft./gal. depending on surface porosity and application method. Dip roller cover into PAVER SEALER WB and roll forward allowing wet sealer in front of the roller to

penetrate the deeper crevices around the paver. Do not dry roll. Keep plenty of sealer on roller cover.

DRY TIME: Dries to touch in one (1) hour @ 77 °F (25 °C) and 50% relative humidity. Ready for foot traffic and 2nd coat, if desired in 12-24 hours and vehicle traffic in 2 days. Low temperatures, high humidity, thick films or poor ventilation will increase these dry times.

TOOLS & APPLICATORS / CLEANING: Medium nap roller, brush or airless sprayer. Cleans with soap and water.

VOC: Contains less than 100 g/l as supplied.

VOC calculations based on manufactured tint base. Contact manufacturer for actual VOC levels which may or may not be substantially less than stated.

FIRST AID: INGESTION: Contact a physician immediately.

SKIN CONTACT: Wash thoroughly with soap and water.

EYE CONTACT: Flush thoroughly with clean, room temperature water and contact a physician immediately.

CAUTION!

HARMFUL IF SWALLOWED. MAY CAUSE EYE, SKIN AND RESPIRATORY IRRITATION. USE WITH ADEQUATE VENTILATION. DO NOT TAKE INTERNALLY. KEEP CLOSED WHEN NOT IN USE. KEEP OUT OF REACH OF CHILDREN.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

CALIF. PROP. 65: This product does not contain chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

Technical data is true and accurate at date of issuance, but subject to change without notice. Our products conform to our quality standards, but no other warranty or guarantee is expressed or implied. Liability, if any, is limited to replacement of product or purchase price. Labor, cost of labor, or consequential damages is hereby excluded.



Sun Paints & Coatings / Dyco Paints • 5850 Ulmerton Road • Clearwater, FL 33760
Phone: 1.800.282.7901 • Facsimile: 727.536.0561 • www.SunPaintsAndCoatings.com

I-15
R-1