



# WOOD STAIN & FINISH STRIPPER

NO. 64



## PRODUCT INFORMATION

BEHR PREMIUM® Wood Stain & Finish Stripper is designed to remove oil, latex-based, and 100% acrylic finishes such as semi-transparent stains, solid color stains and clear sealers. It also removes loose wood fibers to help ensure a sound surface prior to staining or painting. Created especially for use on wood deck and siding surfaces.

## RECOMMENDED USES:

Intended for use on exterior latex and oil-based coatings over wood.

## PRODUCT SPECIFICATIONS:

**Active Type:** Sodium Hydroxide

**Weight per Gallon:** 9.0 lb

**% Solids by Weight:** 13%

**VOC:** 4.0 wt %

**Flash Point:** N/A

**Viscosity:** N/A

**Coverage:** 50-150 sq ft/gal, depending on application method and substrate porosity.

## APPLICATION:

**Brush:** Nylon/polyester

**Roller:** 3/8"-1/2" nap roller cover

**Airless Sprayer:** DO NOT use pump, paint or other sprayers

**Dry Time:** @ 77° & 50% RH

**To Recoat:** 24 hours

Dry times are temperature, humidity, and film thickness dependent.

- Conduct a small test patch in an inconspicuous area to ensure product performance.
- Pour BEHR PREMIUM Wood Stain & Finish Stripper No. 64 directly onto surface and apply liberally using a nylon/polyester brush or roller. Natural bristle brushes or lambswool applicators are not recommended.
- Due to product thickness, DO NOT use pump, paint or other sprayers. Product will clog tip, resulting in leaking and dripping.
- Always keep surface wet by misting with water and re-apply No. 64 if drying occurs.
- Finish will begin to lift from the surface.
- Repeat process as needed to keep the surface wet during the removal period.

- Most deteriorated finishes will start to lift after about 5-45 minutes. The coating should easily rinse off when ready. When the finish starts to lift, scrub the surface using a stiff bristle broom or brush.
- Rinse thoroughly with a garden hose or pressure washer. When rinsing with a pressure washer, use the broadest spray pattern while keeping the nozzle at least 24" away from the surface

## SURFACE PREPARATION:

Be sure to have a source for water, hose with nozzle and stiff bristle broom or brush and a product such as BEHR PREMIUM® All-In-One Wood Cleaner No. 63. DO NOT THIN PRODUCT. Dampen nearby foliage with water and cover with plastic drop cloths. Wear protective clothing, goggles, chemical-resistant gloves, and NIOSH approved respirator.

**WARNING!** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

## CLEAN-UP/DISPOSAL:

Clean all tools and equipment with warm, soapy water. Do not dispose of this product down a drain. If spilled, contain material and remove with an inert absorbent. Dispose of contaminated absorbent, container and unused product in accordance with all current federal, state and local regulations. For recycling or disposal of empty containers, unused product and soiled rags, contact your household refuse collection service.

COMPLIES WITH THE BELOW AS OF 2/1/2020			
SCAQMD	YES	OTC	YES
CARB SCM 2007	YES	LADCO	YES
CARB	YES	AIM	YES
OTC Phase II	YES		

## CAUTIONS/LIMITATIONS:

- Protect from freezing.
- Do not mix with any other product.
- For best results, apply when air, material and surface temperatures are between 40°F and 90°F. Avoid applying in direct sunlight or to hot surfaces.
- Surfaces must be thoroughly dry before applying any type of new finish, except those finishes that can be applied to dampened wood.
- Allow the wood to dry for a minimum of 24 hours in warm, dry weather.
- Prevent all rinse solution from entering storm drains.
- Shelf life under normal conditions is two years unopened.

## GENERAL INFORMATION:

**DANGER CORROSIVE** WILL CAUSE EYE BURNS AND PERMANENT TISSUE DAMAGE. HARMFUL IF SWALLOWED. CONTAINS: SODIUM HYDROXIDE (LESS THAN 10%) AND DIETHYLENE GLYCOL MONOBUTYL ETHER. MAY CAUSE PERMANENT SKIN DAMAGE AND SEVERE RESPIRATORY SYSTEM IRRITATION. USE ONLY WITH ADEQUATE VENTILATION. NOTICE: Do not mix BEHR PREMIUM NO.64 Wood Stain & Finish Stripper with chlorine bleach or with any other household or industrial cleaning product or detergent. Mix only in plastic containers. Only use this product outdoors. Avoid contact with eyes and skin. Wear protective clothing, chemical-resistant gloves and eye goggles. Avoid breathing vapor or mist. If properly used, a respirator may offer additional protection

**FIRST AID:** Eye and skin contact: in case of eye or skin contact, flush immediately with water for 20 minutes. Get medical attention if irritation or symptoms of overexposure persist. If inhaled, move to fresh air. If swallowed, DO NOT induce vomiting. Get medical attention immediately. Give water to dilute material in stomach. Never give anything by mouth to an unconscious person.

**CAUTION: KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY.**

