



GORILLA® PRODUCT GUIDE

GLUE

| Product | GORILLA GLUE® | | CLEAR GORILLA GLUE® | WOOD GLUE | SUPER GLUE | EPOXY | GORILLAWELD™ | CONSTRUCTION ADHESIVE | CLEAR GRIP™ | HOT GLUE STICKS | SPRAY ADHESIVE |
|---|--|------------------------|---|---|---|--|---|---|---|---|--|
| Best for | Tough repairs on dissimilar surfaces, both indoors and outdoors. | | Tough repairs requiring a durable bond. | Building, carpentry or hobby projects using any type of wood. | <p>LIQUID Instant repairs on small indoor projects.</p> <p>GEL No run, control formula great for use on vertical surfaces.</p> <p>BRUSH & NOZZLE Repairs requiring time brushed brush or precision tip nozzle.</p> | Tough repairs requiring a durable, gap-filling bond. | Heavy duty repairs that need maximum bonding power and gap filling. | Multi-surface and multi-purpose applications that require a tough, versatile, all-weather hold. | Craft projects or repairs requiring a flexible, quick and permanent bond. | Craft projects or repairs requiring a gap filling bond. | Lightweight objects, craft projects or repairs. Works great on applications where flexibility is required. |
| Open Working Time | ORIGINAL 10-15 Minutes | WHITE 5-10 Minutes | 5 Minutes | 5-10 Minutes | Not Repositionable | 5 Minutes | 3 Minutes | 10 Minutes | 2 Minutes | 45 Seconds | 1-3 Minutes |
| Clamp Time | ORIGINAL 1-2 Hours | WHITE 30-60 Minutes | 2 Hours | 20-30 Minutes | 10-45 Seconds | 30 Minutes | 30 Minutes | Clamp or Support Heavier Objects | N/A | N/A | N/A |
| Drying Time <small>100% in 24 hours</small> | ORIGINAL 80% in 1-2 Hours | WHITE 80% in 1 Hour | 24 Hours | 80% in 1-2 Hours | Light Handling After 1-5 Minutes | 24 Hours | 24 Hours | 24 Hours | 24 Hours | N/A | 24 Hours |
| Dry Color | ORIGINAL Light Tan | WHITE Soft White | Clear | Natural Wood Color | Clear | Clear | Dark Grey | White | Clear | Clear/Opaque | Clear |
| Outdoor Use | Waterproof, Passes ANSI/HPVA Type I | | Water Resistant | Water Resistant, Passes ANSI/HPVA Type II | Not Recommended | Water Resistant | Waterproof | Waterproof | Waterproof | Water Resistant | Water Resistant |
| Finishing | Sandable, Paintable & Stainable | | Sandable, Stainable & Paintable | Sandable & Paintable | Sandable | Sandable, Stainable & Paintable | Shapeable, Paintable, Sandable, Tappable & Drillable | Sandable & Paintable | Sandable, Paintable & Stainable | Sandable, Paintable & Stainable | Sandable, Paintable & Stainable |
| USE ON: | | | | | | | | | | | |
| Wood | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Metal | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Stone | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Ceramic | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Glass | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Plastic** | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| PVC Sheet | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Brick | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Concrete | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Foam | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Paper | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Rubber | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |
| Fabric | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ | ✓ |



GORILLA® PRODUCT GUIDE

SEALANT

| Product | 100% SILICONE SEALANT | PAINTABLE SILICONE |
|---------------------------------|--|--|
| Best for | All purpose applications including windows, doors, kitchens, baths, auto, marine and more. | All purpose applications where paintability is desired including windows, doors, kitchens, baths and more. |
| Open Working Time | Tool Immediately | Tool Immediately |
| Ready for Water Exposure | 30 Minutes | 15 Minutes |
| Drying Time | 24 Hours | 24 Hours |
| Dry Color | Clear and White | White |
| Outdoor Use | 100% Waterproof | 100% Waterproof |
| Finishing | Not Paintable | Paintable |
| USE ON: | | |
| Tub/Tile | ✓ | ✓ |
| Countertop | ✓ | ✓ |
| Ceramic | ✓ | ✓ |
| Shower | ✓ | ✓ |
| Granite | ✓ | ✓ |
| Trim/Siding | ✓ | ✓ |
| Wood | ✓ | ✓ |
| Vinyl | ✓ | ✓ |
| Drywall | ✓ | ✓ |
| Stainless Steel | ✓ | ✓ |
| Stone | ✓ | ✓ |
| Aluminum | ✓ | ✓ |
| Glass | ✓ | ✓ |
| Brick | ✓ | ✓ |

TAPE

| Product | GORILLA TAPE | CRYSTAL CLEAR GORILLA TAPE | CAMO GORILLA TAPE | HEAVY DUTY MOUNTING TAPE | TOUGH & CLEAR MOUNTING TAPE | PACKAGING TAPE |
|--------------------|---|--|--|---|--|--|
| Best for | Indoor or outdoor use and made to stick to rough and uneven surfaces like wood, stone, stucco, plaster, brick and more. | Providing a weatherproof, airtight bond. Fix, patch and seal almost any surface. | Ideal for applications in the field including duck blinds, tree stands, tent repairs and more. | Mounting items that need a long-lasting, weatherproof bond. Holds up to 30 lbs. | Mounting items that need a long-lasting, weatherproof bond. Holds up to 15 lbs. (roll) and 7 lbs. (squares). | Gorilla Packaging Tape is perfect for shipping, moving and storage. |
| Color | Black White Silver Blaze Orange | Crystal Clear | Mossy Oak® Break-Up Country | Black | Clear | Clear |
| Size | 1 in. (Black only) 1.88 in. 2.88 in. (Black and Silver only) | 1.5 in. x 5 yd. 1.88 in. x 9 yd. 1.88 in. x 18 yd. | 1.88 in. | 1 in. | 1 in. 1 in. Squares | 1.88 in. 2.83 in. |
| Outdoor Use | Weather and UV Resistant | UV and Temperature Resistant, Waterproof Backing | UV and Weather Resistant Shell | Weatherproof | Weatherproof | Weather and Temperature Resistant for Shipping and Long-Term Storage |