

### SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: 2-Part Epoxy Tan - Combined Epoxy Base & Activator No.955

955 Product Code: MSDS Manufacturer 955

Number:

Manufacturer Name: BEHR Process Corporation 3400 W. Segerstrom Avenue Santa Ana, CA 92704 Address:

General Phone Number: (714) 545-7101 General Fax Number: (714) 241-1002 (800) 854-0133 ext. 2 Customer Service Phone

CHEMTREC: For emergencies in the US, call CHEMTREC: 800-424-

Canutec: In Canada, call CANUTEC: (613) 996-6666 (call collect)

May 10, 2007

MSDS Creation Date: MSDS Revision Date: March 14, 2012

MSDS Format: According to ANSI Z400.1-2004



HMIS	
Health Hazard	1
Fire Hazard	1
Reactivity	1
Personal Protection	

## SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS#	Ingredient Percent
Water	7732-18-5	30 - 60 by weight
Polyamine Polymer		1 - 5 by weight
Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bis-,homopolymer	25085-99-8	10 - 30 by weight
Dipropylene glycol butoxy ether	29911-28-2	1 - 5 by weight
Proprietary	No Data	5 - 10 by weight
Titanium dioxide	13463-67-7	10 - 30 by weight

# SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview: CAUTION! Irritant. Skin Sensitizer.

Potential Health Effects:

Eye: Causes eye irritation

Skin: May cause skin irritation. Contact with skin can cause allergic reaction

(sensitization) in some individuals.

Inhalation: Prolonged or excessive inhalation may cause respiratory tract irritation.

Inaestion: May be harmful if swallowed. May cause vomiting. Chronic Health Effects: Prolonged or repeated contact may cause skin irritation. Signs/Symptoms: Overexposure may cause headaches and dizziness.

Target Organs: Eyes. Skin. Respiratory system. Digestive system.

Aggravation of Pre-Existing Individuals with pre-existing skin disorders, asthma, allergies or known Conditions: sensitization may be more susceptible to the effects of this product.

## SECTION 4 - FIRST AID MEASURES

Eye Contact: Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.

Skin Contact: Immediately wash skin with soap and plenty of water.

Get medical attention if irritation develops or persists.

If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate Inhalation:

medical attention.

If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious  $\,$ Ingestion:

person.

Other First Aid: Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the

stomach. If vomiting occurs naturally, have the person lean forward to

### SECTION 5 - FIRE FIGHTING MEASURES

Flash Point:

Lower Flammable/Explosive Not applicable.

Upper Flammable/Explosive Not applicable.

Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog

or spray when fighting fires involving this material.

As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) and full protective gear. Protective Equipment:

#### NFPA Ratings:

NEPA Health: 1 NFPA Flammability: 1 NFPA Reactivity: 1 NFPA Other: NA

### SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personnel Precautions: Use proper personal protective equipment as listed in section 8.

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways

Spill Cleanup Measures: Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Provide ventilation. Clean up spills  $\,$ 

immediately observing precautions in the protective equipment section.

## SECTION 7 - HANDLING and STORAGE

Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing. Handling:

Storage: Store in a cool, dry, well ventilated area away from sources of heat,

combustible materials, and incompatible substances. Keep container tightly closed when not in use.

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid

inhaling vapor or mist.

# SECTION 8 - EXPOSURE CONTROLS, PERSONAL PROTECTION - EXPOSURE GUIDELINES

**Engineering Controls:** Use appropriate engineering control such as process enclosures, local

use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the Eve/Face Protection:

European standard EN 166.

Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with Skin Protection Description:

eyes, skin or clothing.

A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances Respiratory Protection:

where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate

Other Protective:

### EXPOSURE GUIDELINES

Titanium dioxide:

Guideline ACGIH: TLV-TWA: 10 mg/m3 Guideline OSHA: OSHA-TWA: 15 mg/m3

### SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

Physical State Appearance: Liquid. **Boiling Point:** No Data Melting Point: No Data

12 - 14 Lbs./gal. Density:

Molecular Formula: Molecular Weight: Mixture Flash Point: No Data

Material VOC: 2 gm/l (Includes Water) Coating VOC.: 4 gm/l (Excludes Water) VOC Content:

The addition of colorant may add VOCs.

### SECTION 10 - STABILITY and REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.

Hazardous Polymerization: Not reported.

Heat, flames, incompatible materials, and freezing or temperatures below 32 deg.  $\ensuremath{\text{F.}}$ Conditions to Avoid:

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

### SECTION 11 - TOXICOLOGICAL INFORMATION

#### Dipropylene glycol butoxy ether:

RTECS Number: UA8200000

Eye: Eye - Rabbit Standard Draize test.: 100 mg (RTECS)

Administration onto the skin - Rabbit LD50: 5860 uL/kg [Behavioral - Somnolence (general depressed activity) Gastrointestinal -Skin:

Hypermotility, diarrhea Lungs, Thorax, or Respiration - Other changes] (RTECS)

Ingestion:

Oral - Rat LD50: 1620 uL/kg [Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Skin and Appendages - Hair]

(RTECS)

<u>Titanium dioxide</u>:

RTECS Number: XR2275000

Administration onto the skin - Human Standard Draize test.: 300 ug/3D (Intermittent) (RTECS) Skin:

IARC: Group 2B: Possibly carcinogenic to humans. Carcinogenicity:

# SECTION 12 - ECOLOGICAL INFORMATION

Ecotoxicity: No ecotoxicity data was found for the product.

Environmental Fate: No environmental information found for this product.

## SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal:

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

## SECTION 14 - TRANSPORT INFORMATION

DOT UN Number: No Data DOT Hazard Class: No Data

# SECTION 15 - REGULATORY INFORMATION

## $\underline{\texttt{Oxirane, 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]}}\ bis-, homopolymer:$

TSCA Inventory Status: Listed Canada DSL:

#### Dipropylene glycol butoxy ether:

TSCA Inventory Status: Listed Canada DSL: Listed

Titanium dioxide:

TSCA Inventory Status: Listed

State Regulations:

Listed in the New Jersey State Right to Know List. Listed in the Pennsylvania State Hazardous Substances List.

Listed Canada DSL:

## SECTION 16 - ADDITIONAL INFORMATION

HMIS Health Hazard: HMIS Fire Hazard: 1 HMIS Reactivity: 1 HMIS Other:

May 10, 2007 MSDS Creation Date: March 14, 2012 MSDS Revision Date: MSDS Revision Notes: Formula update MSDS Author: Actio Corporation

Disclaimer:

This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, that any revision of this Data Sheet is sent to all customers to whom we have directly supplied this substance, but must point out that it is the responsibility of any intermediate supplier to ensure that such revision is passed to of any intermediate supplier to ensure that such revision is passed to the ultimate user. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through the sales office whose address is at the top of this data sheet.

The trademarks, service marks, graphics and logos used on this MSDS are registered or unregistered trademarks of BEHR Process Corporation. All Rights Reserved. Trademark:

Copyright© 1996-2011 Actio Corporation. All Rights Reserved.