

CUSTOM COMPLETE

Product Catalog



Flooring Preparation & Installation Products



CUSTOM[®]

TILE INSTALLATION SYSTEMS

Set Materials

SET

Whether you're selling it, specifying it or spreading it, CUSTOM offers installation solutions to meet the most demanding requirements. We offer an extensive range of high-performance mortars for setting glass tile, large format tile, heavy stone and more. We have the right setting material for every job.

Polymer-Modified Dry-Set Mortars for Large and Heavy Tile

As tile continues to get larger, installations call for medium bed mortars. CUSTOM's expanded array of large format tile mortars support the weight of tiles with dimensions greater than 15" on any side, as well as natural stone and thin tile panels.



CUSTOM® Mortars Earn a Lifetime Warranty

CUSTOM is proud to back our premium mortars with a Lifetime Warranty System* when installed with qualifying prep and grout products. We are confident this is the best system, so we have the most comprehensive warranty in the industry, covering not only tile and materials – but also replacement labor. Look for the Lifetime Warranty logo on qualified products.



*See the warranty section on our website for complete program details.



Emerald System™

The Emerald System addresses critical green building issues such as agency compliance, system warranties and greenhouse gas emissions. All products comply with the standards for leading green building agencies. When a project using Emerald System products is registered for a warranty, CUSTOM will purchase Carbon Credits to offset the amount of CO₂ created from the cement used in its products.

Polymer Modified Thin-Set Mortars

FlexBond® Fortified Thin-Set Mortar

A premium quality, polymer-modified mortar with exceptional flexibility and bond strength for tiling difficult surfaces, such as plywood, vinyl and laminates, and for hard-to-bond, nonporous tile, such as porcelain and glass.



ITEM CODE	SIZE	COLOR
FBG25	25 lb (11.34 kg) Bag	Gray
FBW25	25 lb (11.34 kg) Bag	White
FB50	50 lb (22.68 kg) Bag	Gray
FBW50	50 lb (22.68 kg) Bag	White

Glass Tile Premium Thin-Set Mortar

Offers the ultimate in bond strength for the most demanding installation requirements for larger format glass tile, mosaics and other difficult-to-bond tile and stone. Specifically formulated to provide a consistent bright white backdrop for clear, iridescent and translucent glass tile to accentuate its brilliance and beauty.



ITEM CODE	SIZE	COLOR
GTMW7-4	7 lb (3.2 kg) Bag	White

MultiSet Modified Thin-Set Mortar

MultiSet offers good bond strength for tile installations over most surfaces. Apply over concrete, cement backerboards and existing ceramic tile. Meets ANSI A118.4 without the need for additives. Meets ANSI A118.11 when Mortar Admix is added at the required mixing ratio.

ITEM CODE	SIZE	COLOR
MSMG50	50 lb (22.68 kg) Bag	Gray
MSMW50	50 lb (22.68 kg) Bag	White

Porcelain Tile Fortified Thin-Set Mortar

Designed specifically for superior bonding of porcelain tile to concrete surfaces, backerboards and self-leveling underlayments. Also great for glass and large modular tile installations.

ITEM CODE	SIZE	COLOR
PMG50	50 lb (22.68 kg) Bag	Gray
PMW50	50 lb (22.68 kg) Bag	White

VersaBond® Fortified Thin-Set Mortar

Polymer-modified VersaBond offers economy with good bond strengths for floor and wall tile installations. Cures fast, even in cold weather climates.

ITEM CODE	SIZE	COLOR
MTSG25	25 lb (11.34 kg) Bag	Gray
MTSG50	50 lb (22.68 kg) Bag	Gray
MTSW50	50 lb (22.68 kg) Bag	White

VersaBond Flex® Fortified Thin-Set Mortar

This high performance formula provides outstanding working characteristics while the high flexibility and bond strength deliver excellent performance over a wide variety of floor and wall installations. Excellent for setting porcelain and glass tile, with exceptional adhesion to plywood subfloors.

ITEM CODE	SIZE	COLOR
VBFG25	25 lb (11.34 kg) Bag	Gray
VBFW25	25 lb (11.34 kg) Bag	White
VBFG50	50 lb (22.68 kg) Bag	Gray
VBFW50	50 lb (22.68 kg) Bag	White

VersaSet® Fortified Thin-Set Mortar

VersaSet is a high performance modified thin-set mortar that delivers good bond strengths for basic tile and natural stone installations over most common types of surfaces. Meets ANSI A118.4 and A118.11 mixed with water. No need for additives.

ITEM CODE	SIZE	COLOR
VSG50	50 lb (22.68 kg) Bag	Gray
VSW50	50 lb (22.68 kg) Bag	White

Rapid Setting Mortars

Complete Contact™-LFT Rapid Setting Large Format Tile & Stone Mortar

A polymer-modified, full contact medium bed mortar, specifically designed for floors, that has a rapid curing formula that allows grouting in as little as 2 hours and light foot traffic in 4 - 6 hours and commercial traffic in 24 hours. Excellent for large format tile and stone, Complete Contact-LFT Rapid Setting Mortar is suited for thin and medium bed applications up to 3/4" (19 mm).

ITEM CODE	SIZE	COLOR
CCLFTRSG50	50 lb (22.68 kg) Bag	Gray
CCLFTRSW50	50 lb (22.68 kg) Bag	White

Complete Contact™ RS (Rapid Setting) Fortified Mortar

Rapid setting, polymer-modified, full contact mortar can be used in thin-bed and medium-bed applications. Cures fast, developing high early strength for quick installations.

ITEM CODE	SIZE	COLOR
CCRSG50*	50 lb (22.68 kg) Bag	Gray
CCRSW50*	50 lb (22.68 kg) Bag	White

MegaLite® Rapid Setting Crack Prevention Mortar

Formulated with CustomLite® Technology

A premium one-part formula, MegaLite Rapid Setting offers the ultimate in high, fast bond strength and flexibility for time-critical commercial and residential installations under the most demanding requirements. Allows grouting in under three hours and traffic in four hours. Has the flexibility to withstand horizontal substrate movement up to 1/8" (3 mm) without transmitting cracks through the tile installation. Special order only.



ITEM CODE	SIZE	COLOR
MLRSG30*	30 lb (13.6 kg) Bag	Gray
MLRSW30*	30 lb (13.6 kg) Bag	White

*Indicates a special order item.

Set Materials continued

ProLite® Rapid Setting Large Format Tile & Stone Mortar

Formulated with CustomLite® Technology Industry-leading ProLite Rapid Setting Tile & Stone Mortar is a lightweight, medium bed, rapid-setting mortar. Offers high performance and flexibility designed to obtain fast tenacious bond strength needed for fast track commercial or residential installations. Apply up to 3/4" (19 mm) thick on horizontal surfaces (after beat-in). Adjustments allowed, yet it will set quickly – allowing the grouting process to begin in under three hours with light traffic in four hours.

ITEM CODE	SIZE	COLOR
PLRSG30	30 lb (13.6 kg) Bag	Gray
PLRSW30	30 lb (13.6 kg) Bag	White

SpeedSet™ Fortified Thin-Set Mortar

Polymer-modified mortar for time-critical installations such as restaurants, malls and hotel lobbies. Excellent for cold temperature installations. Grout in two hours, allows traffic in six hours.

ITEM CODE	SIZE	COLOR
SDS25	25 lb (11.34 kg) Bag	Gray
SDSW25	25 lb (11.34 kg) Bag	White

Complete Contact™ –LFT Rapid Setting Large Format Tile & Stone Mortar

See description under Large Format Tile Mortars and Medium Bed Mortars.

Chemical Resistant Mortar

EBM-Lite™ Epoxy Bonding Mortar – 100% Solids

Formulated with CustomLite® Technology Three-component, water-washable mortar system for installations where exceptionally high chemical- and impact-resistance is required. EBM-Lite's unique formula produces a mortar with greater bond and compressive strengths and improved chemical and stain resistance. It is 30% lighter and contains recycled content, contributing to LEED certification.



ITEM CODE	SIZE	COLOR
EBML	Setting Unit Contains: Part A (2 gallon yield) – 68 fl oz (2 L) Bottle Part B – 32 fl oz (.9 L) Bottle, Part C – 14.4 lb (6.5 kg) Bag	White

Polymer-Modified Dry-Set Mortars for Large and Heavy Tile

Complete Contact™ –LFT Rapid Setting Large Format Tile & Stone Mortar

See description under Rapid Setting Mortars.

FlexBond® –LFT Crack Prevention Medium Bed Mortar

A premium quality, medium bed polymer-modified mortar for use with large format tiles that has exceptional flexibility and bond strength for tiling difficult surfaces, such as plywood, vinyl and laminates, and for hard-to-bond, nonporous tile, such as porcelain and glass. FlexBond LFT offers protection and isolation against cracks in the substrate up to 1/16" (1.6 mm). The mortar's high polymer content makes it ideal for above-ground floor installations.



ITEM CODE	SIZE	COLOR
CFBLFTMW50	50 lb (22.68 kg) Bag	White

MegaLite® Crack Prevention Mortar

Formulated with CustomLite® Technology Offers the ultimate in bond strength for the most demanding installation requirements and the flexibility to withstand horizontal substrate movement up to 1/8" (3 mm). It's 40% lighter than other mortars, providing non-sag/non-slip installation on walls. A 30 lb (18.9 kg) bag covers the same area as a 50 lb (22.68 kg) bag of traditional mortar. Excellent for large format tile.



ITEM CODE	SIZE	COLOR
MLMG30	30 lb (13.6 kg) Bag	Gray
MLMW30	30 lb (13.6 kg) Bag	White

MegaLite® Rapid Setting Crack Prevention Mortar

See description under Rapid Setting Mortars.

Natural Stone & Large Tile Premium Large Format Tile Mortar

Premium, polymer-modified mortar formulated for installing natural stone and large tile. Non-slumping formula eliminates lippage. Excellent sag and slip resistance, wall tiles are held in place immediately. Apply up to 3/4" (19 mm) thick on horizontal applications or use in thin-bed applications as thin as 1/8" (6 mm).



ITEM CODE	SIZE	COLOR
MGMMY50	50 lb (22.68 kg) Bag	Gray
MGMM50	50 lb (22.68 kg) Bag	White

ProLite® Large Format Tile & Stone Mortar

Formulated with CustomLite® Technology Offers high flexibility and bond strength in a lightweight formula with excellent handling characteristics. Excellent for setting large format tile or stone, ProLite will not sag or slip on walls and offers non-slump performance for floor installations.

ITEM CODE	SIZE	COLOR
PLMG30	30 lb (13.6 kg) Bag	Gray
PLMW30	30 lb (13.6 kg) Bag	White

ProLite® Rapid Setting Large Format Tile & Stone Mortar

See description under Rapid Setting Mortars.

VersaBond®-LFT Professional Large Format Tile Mortar

NEW

VersaBond-LFT Fortified Large Format Tile Mortar is a general purpose, economical, polymer-modified medium bed mortar for use with large format porcelain, ceramic and natural stone tile. With a non-slumping formula to eliminate lippage, VersaBond-LFT can be applied up to 3/4" (19 mm) thick on horizontal applications. It bonds well to concrete, backerboard and plywood for interior and exterior applications.

ITEM CODE	SIZE	COLOR
VBLFTMG50	50 lb (22.68 kg) Bag	Gray
VBLFTMW50	50 lb (22.68 kg) Bag	White

Thick Bed Mortar

Thick Bed Bedding Mortar

Pre-blended underlayment specifically designed to float a mortar bed for ceramic tile. It is easy to mix and use, eliminating the need for site mixing of sand and cement. Thick Bed Bedding Mortar's 3:1 mix ratio provides a high-strength surface ideal for tiling commercial and industrial installations.

ITEM CODE	SIZE	COLOR
CTBBM50	50 lb (22.68 kg) Bag	Gray

Non-Modified Dry-Set Mortars and Additives

CustomBlend® Standard Thin-Set Mortar

Offers economy with good bond strength and is suitable for floor installations. Good for setting Saltillo and other clay pavers.

ITEM CODE	SIZE	COLOR
CBTSG50	50 lb (22.68 kg) Bag	Gray
CBTSW50	50 lb (22.68 kg) Bag	White

Uncoupling Mat Mortar

Uncoupling Mat Mortar is an unmodified, all-purpose thin-set for uncoupling systems. Adheres to most surfaces and types of tile.

ITEM CODE	SIZE	COLOR
UMMG50	50 lb (22.68 kg) Bag	Gray
UMMW50	50 lb (22.68 kg) Bag	White

Mortar Admix

A liquid polymer to be used in place of water to increase performance of Uncoupling Mat Mortar and CustomBlend non-polymer modified grouts or Portland cement mortar mixes. It adds water resistance and improves shock absorption.

ITEM CODE	SIZE
AMA2	2.5 gal (9.46 L) Bottle

SimpleSet®

Pre-Mixed Thin-Set Mortar

This no-mix, no-mess alternative to traditional thin-set mortars spreads quickly and easily. Bonds ceramic tile up to 18" x 18" (45 x 45 cm).

ITEM CODE	SIZE	COLOR
CTTSGQT	1 quart (.946 L) Pail	Gray
CTTSG1-2	1 gallon (3.78 L) Pail	Gray
CTTSG3	3.5 gallon (13.25 L) Pail	Gray
STTSW1-2	1 gallon (3.78 L) Pail	White
STTSW3	3.5 gallon (13.25 L) Pail	White

Ceramic Tile Adhesives

AcrylPro® Ceramic Tile Adhesive

AcrylPro spreads quickly and easily, and offers extended open times for adjusting tile. It also provides higher bond strength required for 12" x 12" (30 x 30 cm) ceramic floor tile installations and exceptional durability in wet areas.

ITEM CODE	SIZE	COLOR
ARL4000QT	1 quart (.946 L) Pail	White
ARL40001	1 gallon (3.78 L) Pail	White
ARL40003	3.5 gallon (13.25 L) Pail	White

OmniGrip® Maximum Strength Adhesive Formulated with CustomLite® Technology

Formulated with more solids and less water, OmniGrip shrinks up to 33% less than traditional tile adhesives to ensure maximum coverage and superior bonds. This high polymer formula remains flexible, so it works in a wide variety of installations. It weighs 25% less than traditional adhesives making it easier to spread and carry.

ITEM CODE	SIZE	COLOR
OGA1-2	1 gallon (3.78 L) Pail	White
OGA3	3.5 gallon (13.25 L) Pail	White

ReliaBond® Ceramic Tile Adhesive

All-purpose professional adhesive formulated for wall, floor and countertop installations of ceramic and stone tile. Spreads easily and resists slipping on vertical applications.

ITEM CODE	SIZE	COLOR
RBM3	3.5 gallon (13.25 L) Pail	White

T1-60™ Wall & Floor Tile Adhesive

Commercial-grade adhesive forms durable bonds on ceramic wall, floor and countertop installations. High tack, quick grab.

ITEM CODE	SIZE	COLOR
T1603	3.5 gallon (13.25 L) Pail	White

*Indicates a special order item.

Set Materials Guide

■ Highest Performance ▲ Highly Recommended ○ Recommended

SUBSTRATE	APPLICATION	TILE TYPE	POLYMER-MODIFIED MORTARS					RAPID SETTING MORTARS			CHEMICAL RESISTANT MORTAR	POLYMER-MODIFIED DRY-SET MORTARS FOR LARGE AND HEAVY TILE							
			FlexBond	Glass Tile Premium	MultiSet	Porcelain Tile	VersaBond	VersaBond Flex	Complete Contact-LFT RS	MegaLite Rapid Setting	ProLite Rapid Setting	SpeedSet	EBM-Lite Epoxy Bonding Mortar	FlexBond-LFT	MegaLite	Natural Stone & Large Tile	ProLite	VersaBond-LFT	
FLOORS AND COUNTERTOPS	Residential to commercial: WonderBoard Lite Backerboard Concrete Mortar Bed	Interior/Exterior Wet and Dry Areas (Not exposed to freeze/thaw conditions)	1 Non-Vitreous, Semi-Vitreous & Vitreous Including Quarry	■	○	▲	○	▲	▲	■	▲	▲	■	▲	■	▲	▲	○	
			2 Impervious Porcelain	■	○	■	○	▲	■	■	▲	▲	■	▲	■	▲	▲	▲	○
			3 Glass	▲	■					■	▲				■	■			
			4 Marble, Natural Stone	■	○	▲	○	▲	■	■	■	○		▲	■	▲	■	■	○
			5 Large Format Tile						■	■	■		▲	▲	■	■	■	■	○
			6 Green & Black Marble & Granite, Cement Tile										■						
	Masonry Cutback Adhesive Over Concrete	Exterior Wet and Dry Areas (Including freeze/thaw conditions)	Non-Vitreous, Semi-Vitreous & Vitreous Including Quarry	■	○	▲	○	▲	▲	■	▲	▲	▲	■	▲	▲	▲	○	
			Impervious Porcelain	■	○	■	○	▲	■	■	▲	▲	▲	▲	■	▲	▲	○	
			Glass		■					■	■					■			
			Marble, Natural Stone	■	○	▲	○	▲	■	■	■	○	▲	▲	■	■	■	○	
			Large Modular Tile						■	■	■		▲	▲	■	■	■	○	
	Residential to light commercial: Exterior Grade Plywood Non-Cushioned Sheet Vinyl Existing Ceramic Tile Laminated Countertops	Interior Wet and Dry Areas	Non-Vitreous, Semi-Vitreous & Vitreous Including Quarry	■	○	○	○	▲	▲	■	▲	○	■	▲	■	○	▲	○	
			Impervious Porcelain	■	○	▲	○	▲	■	■	▲	○	■	▲	■	○	▲	○	
			Glass	▲	■			▲		■	▲		■		■		▲		
			Marble, Natural Stone	■	○	○	○	▲	■	■	▲	○	■	▲	■	■	■	○	
			Large Format Tile						■	■	▲		▲	▲	■	■	■	○	
Green & Black Marble & Granite, Cement Tile												■							
WALLS	Gypsum Wallboard Greenboard Cement Plaster	Interior Dry to Intermittent Water Exposure	Non-Vitreous, Semi-Vitreous & Vitreous Including Quarry	■	○	▲	○	▲		■	▲	○	■	▲	■	■	▲		
			Impervious Porcelain	■	○	■	○	▲		■	▲	▲	▲	▲	■	▲	▲		
			Glass	▲	■					■	▲		■		■		▲		
			Marble, Natural Stone	■	○	▲		▲		■	■	○	▲	▲	■	■	■		
			Large Format Tile							■	■		▲	▲	■	■	■		
	Residential to Commercial: WonderBoard Lite Backerboard Concrete Mortar Bed Masonry	Interior/Exterior Wet and Dry Areas (Not exposed to freeze/thaw conditions)	Non-Vitreous, Semi-Vitreous & Vitreous Including Quarry	■	○	▲	○	▲	■	▲	▲	▲	▲	▲	■	▲	▲		
			Impervious Porcelain	■	○	■	○	▲	■	▲	▲	▲	▲	▲	■	▲	▲		
			Glass	▲	■					■	▲		■		■		▲		
			Marble, Natural Stone	■	○	▲		▲		■	■	○	▲	▲	■	■	■		
			Large Format Tile							■	■		▲	▲	■	■	■		
		Green & Black Marble & Granite, Cement Tile	Exterior Wet and Dry Areas (Including freeze/thaw conditions)	Non-Vitreous, Semi-Vitreous & Vitreous Including Quarry	■	○	▲	○	▲	■	▲	▲	▲	▲	■	▲	▲	▲	
				Impervious Porcelain	■	○	■	○	▲		■	▲	▲	▲	▲	■	▲	▲	
				Glass	▲	■					■	▲		■		■		▲	
				Marble, Natural Stone	■	○	▲		▲		■	■	○	▲	▲	■	■	■	
				Large Format Tile							■	■		▲	▲	■	■	■	
	Existing Ceramic Tile	Interior Wet and Dry Areas	Tile Type 1, 2, 4	▲	○	▲	○	▲		■	▲	○	▲	▲	■	▲	■		
Green & Black Marble & Granite, Cement Tile												■							

1 Mix with Mortar Admix when used over plywood.

POLYMER MODIFIED THIN-SET MORTARS			
PHYSICAL PROPERTIES	FLEXBOND	GLASS TILE PREMIUM	MULTISET
Applicable ANSI Standards	A118.15/118.11	A118.4/118.11	A118.4/118.11
Systems Warranty	Up to Lifetime	Up to Lifetime	
Shear Bond Strength @ 28 days:			
Bisque Tile	600-700 psi	500-600 psi	275-325 psi
Porcelain Tile	400-500 psi	400-500 psi	200-275 psi
Quarry Tile to Plywood	300-350 psi	200-300 psi	N/A
Pot Life	4 hours	4 hours	2 hours
Open Time	65-70 minutes	30 minutes	50-55 minutes
Adjustment Time	45-50 minutes	50-70 minutes	30-35 minutes
Approximate Coverage Range 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) square-notch trowel	90-100 sq ft/50 lb bag (8.4-9.3 M/22.68 kg)	50-55 sq ft/25 lb bag (4.6-5.1 M/11.34 kg)	85-90 sq ft/50 lb bag (7.9-8.4 M/22.68 kg)
Color(s)	White & Gray	White	White & Gray

POLYMER MODIFIED THIN-SET MORTARS				
PHYSICAL PROPERTIES	PORCELAIN TILE	VERSABOND	VERSABOND FLEX	VERSASET
Applicable ANSI Standards	A118.4/118.11	A118.4/118.11	A118.4/118.11	A118.4/118.11
Systems Warranty	Up to 15 Year	Up to 10 Year	Up to 15 Year	
Shear Bond Strength @ 28 days:				
Bisque Tile	500-600 psi	450-550 psi	500-600 psi	400-500 psi
Porcelain Tile	400-500 psi	300-400 psi	350-450 psi	225-350 psi
Quarry Tile to Plywood	200-300 psi	150-250 psi	200-300 psi	150-175 psi
Pot Life	2 hours	4 hours	4 hours	3 hours
Open Time	50 minutes	50-55 minutes	55-60 minutes	> 45 minutes
Adjustment Time	30-35 minutes	30-35 minutes	35-40 minutes	> 20 minutes
Approximate Coverage Range 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) square-notch trowel	90-100 sq ft/50 lb bag (8.4-9.3 M/22.68 kg)	90-100 sq ft/50 lb bag (8.4-9.3 M/22.68 kg)	90-100 sq ft/50 lb bag (8.4-9.3 M/22.68 kg)	85-90 sq ft/50 lb bag (7.9-8.4 M/22.68 kg)
Color(s)	White & Gray	White & Gray	White & Gray	White & Gray

RAPID SETTING MORTARS				
PHYSICAL PROPERTIES	COMPLETE CONTACT RS	MEGALITE RAPID SETTING	PROLITE RAPID SETTING	SPEEDSET
Applicable ANSI Standards	A118.15F/118.11	A118.15F/118.11	A118.15F/118.11	A118.4F/118.11
Systems Warranty	Up to 15 Year	Up to Lifetime	Up to 15 Year	Up to 15 Year
Shear Bond Strength @ 28 days:				
Bisque Tile	450-500 psi	725-850 psi	550-650 psi	425-500 psi
Porcelain Tile	400-475 psi	650-725 psi	400-475 psi	300-400 psi
Quarry Tile to Plywood	225-300 psi	350-425 psi	225-300 psi	150-250 psi
Pot Life	40-60 minutes	40-60 minutes	40-60 minutes	30 minutes
Open Time	15-20 minutes	> 20 minutes	> 40 minutes	20 minutes
Adjustment Time	30 minutes	> 20 minutes	> 20 minutes	20 minutes
Approximate Coverage Range 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) square-notch trowel	80-90 sq ft/50 lb bag (7.4-8.4 M/22.68 kg)	100-110 sq ft/30 lb bag (9.3-10.2 M/13.6 kg)	90-100 sq ft/30 lb bag (8.4-9.3 M/13.6 kg)	45-50 sq ft/25 lb bag (4.2-4.6 M/11.34 kg)
Color(s)	White & Gray	White & Gray	White & Gray	White & Gray

CHEMICAL RESISTANT MORTAR	
PHYSICAL PROPERTIES	EBM-LITE BONDING MORTAR
Applicable ANSI Standards	A118.3
Systems Warranty	Up to Lifetime
Shear Bond Strength @ 28 days:	
Bisque Tile	N/A
Porcelain Tile	1000 psi
Quarry Tile to Plywood	1200 psi
Pot Life	1 hour
Open Time	45 minutes
Initial Set	3 hours
Final Set	9 hours
Approximate Coverage Range 1/2" x 1/2" x 1/4" (13 x 13 x 6 mm) square-notch trowel	50-55 sq ft/1-3/4 gallon unit (4.6-5.1 M/6.6 L)
Color(s)	White

POLYMER-MODIFIED DRY-SET MORTARS FOR LARGE AND HEAVY TILE				
PHYSICAL PROPERTIES	COMPLETE CONTACT-LFT RS	FLEXBOND-LFT	MEGALITE	MEGALITE RAPID SETTING
Applicable ANSI Standards	A118.15F/118.11	A118.15T/118.11	A118.15TE/118.11	A118.15F/118.11
Systems Warranty	Up to 15 Year	Up to Lifetime	Up to Lifetime	Up to Lifetime
Shear Bond Strength @ 28 days:				
Bisque Tile	450-500 psi	> 550 psi	725-850 psi	725-850 psi
Porcelain Tile	400-475 psi	> 450 psi	650-725 psi	650-725 psi
Quarry Tile to Plywood	225-300 psi	> 250 psi	350-425 psi	350-425 psi
Pot Life	40-60 minutes	4 hours	4 hours	40-60 minutes
Open Time	15-20 minutes	65-70 minutes	100-120 minutes	> 20 minutes
Adjustment Time	30 minutes	45-50 minutes	50-70 minutes	> 20 minutes
Approximate Coverage Range 1/2" x 1/2" x 1/4" (13 x 13 x 6 mm) square-notch trowel	45-50 sq ft/50 lb bag (4.2-4.6 M/22.68 kg)	45-50 sq ft/50 lb bag (3.7-4.6 M/22.68 kg)	100-110 sq ft/30 lb bag (9.3-10.2 M/13.6 kg)	100-110 sq ft/30 lb bag (9.3-10.2 M/13.6 kg)
Color(s)	White	White & Gray	White & Gray	White & Gray

POLYMER-MODIFIED DRY-SET MORTARS FOR LARGE AND HEAVY TILE				
PHYSICAL PROPERTIES	NATURAL STONE & LARGE TILE	PROLITE	PROLITE RAPID SETTING	VERSABOND-LFT
Applicable ANSI Standards	A118.4/118.11	A118.15T/118.11	A118.15F/118.11	A118.4/118.11
Systems Warranty	Up to Lifetime	Up to 15 Year	Up to 15 Year	Up to 10 Year
Shear Bond Strength @ 28 days:				
Bisque Tile	400-500 psi	550-650 psi	550-650 psi	450-550 psi
Porcelain Tile	300-400 psi	400-500 psi	400-475 psi	350-450 psi
Quarry Tile to Plywood	150-200 psi	225-300 psi	225-300 psi	150-250 psi
Pot Life	4 hours	2 hours	40-60 minutes	4 hours
Open Time	65-70 minutes	60 minutes	> 40 minutes	50-55 minutes
Adjustment Time	50-55 minutes	40 minutes	> 20 minutes	30-35 minutes
Approximate Coverage Range 1/2" x 1/2" x 1/4" (13 x 13 x 6 mm) square-notch trowel	45-50 sq ft/50 lb bag (3.7-4.6 M/22.68 kg)	43-48 sq ft/50 lb bag (4.0-4.5 M/22.68 kg)	90-100 sq ft/30 lb bag (8.4-9.3 M/13.6 kg)	42-47 sq ft/50 lb bag (3.9-4.4 M/22.68 kg)
Color(s)	White	White & Gray	White & Gray	White & Gray

DRY SET MORTARS			
PHYSICAL PROPERTIES	CUSTOMBLEND	PHYSICAL PROPERTIES	UNCOUPLING MAT MORTAR
Applicable ANSI Standards	A118.4/118.11	Applicable ANSI Standards	A118.4
Shear Bond Strength @ 28 days Mixed With Water:		Shear Bond Strength @ 28 days Mixed With Water:	
Bisque Tile	225-300 psi	Bisque Tile	250-325 psi
Porcelain Tile	150-225 psi	Porcelain Tile	200-250 psi
Quarry Tile to Plywood	N/A	Quarry Tile to Plywood	N/A
Shear Bond Strength @ 28 days Mixed With Mortar Admix:		Shear Bond Strength @ 28 days Mixed With Mortar Admix:	
Bisque Tile	300-400 psi	Bisque Tile	300-400 psi
Porcelain Tile	200-300 psi	Porcelain Tile	250-350 psi
Quarry Tile to Plywood	150-200 psi	Quarry Tile to Plywood	150-200 psi
Pot Life		Pot Life	90 minutes
Open Time	55 minutes	Open Time	60-65 minutes
Adjustment Time	40-45 minutes	Adjustment Time	50-60 minutes
Approximate Coverage Range 1/4" x 1/4" x 1/4" (6 x 6 x 6 mm) square-notch trowel	85-90 sq ft/50 lb bag (7.9-8.4 M/22.68 kg)	Approximate Coverage Range Mat to Subsurface 1/4" x 3/16" (6 x 5 mm) V-notch trowel	150-200 sq ft/50 lb bag (18-19 M/22.68 kg)
		Approximate Coverage Range over Schluter-Ditra Uncoupling Membrane to Install Tile 1/4" x 3/8" x 1/4" (6 x 9.5 x 6 mm) square-notch trowel	40-50 sq ft/50 lb bag (3.7-4.6 M/22.68 kg)
Color(s)	White & Gray	Color(s)	White & Gray

Adhesives Guide

		ULTIMATE	PRO FORMULA		COMMERCIAL GRADE
		OMNIGRIP	ACRYLPRO	RELIABOND RELIABOND ES	T1-60

SUBSTRATES	Exterior Use	Walls - covered areas	■			
	Floors	Concrete	■	▲	▲	○
		Backerboards	■	▲	▲	○
		Plywood	■	▲	▲	○
		Resilient flooring	■	○	○	
		Existing ceramic tile	■	○	○	
	Walls	Concrete	■	▲	▲	○
		Backerboards	■	▲	▲	○
		Drywall, Greenboard	■	▲	▲	▲
		Plaster	■	▲	▲	▲
		Masonry	■	▲	▲	○
		Existing ceramic tile	■	○	○	○
	Countertops	Backerboards	■	▲	▲	○
		Plywood	■	▲	▲	○
		Existing ceramic tile	■	○	○	○
		Plastic laminate	■	○	○	○

TILE TYPES	Tile	Floors	UP TO 16" x 16" (40 x 40 cm)	UP TO 12" x 12" (30 x 30 cm)	UP TO 8" x 8" (20 x 20 cm)	UP TO 8" x 8" (20 x 20 cm)
		Ceramic mosaics	■	▲	▲	▲
		Wall tile	■	▲	▲	▲
		Flat back ceramic	■	▲	▲	▲
		Quarry	■	○	○	○
		Pavers	■	○	○	○
		Gauged slate	■	▲	▲	○
		Vitreous tile	■	▲	▲	○
		Lugged or button backs ¹	■	○	○	○
		Porcelain, Glass mosaics ²	■	▲	▲	○
	Marble Tile ³	Walls	■	▲	▲	
		Floors	UP TO 12" x 12" (30 x 30 cm)			

¹ Wall applications only.

² Do not set transparent glass tile.

³ Do not set moisture sensitive stone, resin backed, light colored or translucent marble.

■ Highest Performance ▲ Highly Recommended ○ Recommended

CERAMIC TILE ADHESIVES				
	ULTIMATE	PRO FORMULA	COMMERCIAL	
PHYSICAL PROPERTIES	OMNIGRIP	ACRYLPRO	RELIABOND	T1-60
Applicable ANSI Standards	A136.1 Type I	A136.1 Type I	A136.1 Type I	A136.1 Type I
Systems Warranty	15 Year	1 Year	1 Year	1 Year
Adjustment Time	>60 min	45 min	45 min	40 min
Open Time	>60 min	75 min	60 min	50 min
Shear Bond Strength: Type 1 Water Immersion	Exceeds	Passes	Passes	Passes
Freeze/Thaw	Stable	Stable	Stable	Stable
Stain Test	Passes	Passes	Passes	Passes
Impact Test	Passes	Passes	Passes	Passes
Heat Resistance	Passes	Passes	Passes	Passes
3.5 gal (13.2 L) Pail Weight	31 lbs (14.1 kg)	53 lbs (24 kg)	45 lbs (20.4 kg)	45 lbs (20.4 kg)
Approximate Coverage Range per Gallon (3.78 L) 3/16" x 5/32" (5 x 4 mm) V-notch Trowel	40-60 sq ft (3.7 - 5.6 M ²)	40-60 sq ft (3.7 - 5.6 M ²)	40-60 sq ft (3.7 - 5.6 M ²)	40-60 sq ft (3.7 - 5.6 M ²)



CUSTOM[®] Technical University

Custom Building Products developed Custom Technical University or "CTU" as its exclusive, interactive educational forum. CTU combines impactful curriculum, all the latest tools and a state-of-the-art facility designed to engage sales representatives, distributor personnel, contractors, installers, architects, designers and specifiers.

A variety of programs acquaint professionals with the latest installation methods, best practices, time-saving tips, codes, standards, products and system assemblies for the tile, stone and flooring industries.

CTU also offers AIA and CES programs plus specialized care and maintenance certification opportunities.

CustomBuildingProducts.com

For the most updated product information and specifications, visit our website. Our videos, technical data sheets and technical bulletins will help you select the right product for your job.



©2015 Custom Building Products. All rights reserved. The CUSTOM logo, and product logos are registered trademarks of Custom Building Products. All other trademarks are the property of their respective owners. CUSTOM may make product modifications at any time without notice. Product specifications are subject to change. Visit custombuildingproducts.com for updated technical data sheets and MSDS information.

Customer Support:

800-272-8786

Technical Support:

800-282-8786

Custom Building Products
800-272-8786
custombuildingproducts.com

Printed in the U.S.A. CCB1 3/15R



CUSTOM[®]

TILE INSTALLATION SYSTEMS