

Cabinet Rescue®

TECHNICAL DATA SHEET

PRODUCT MODEL NUMBER

DT-43 QT.

PRODUCT DESCRIPTION

Waterborne enamel that cures to a very hard mar-resistant laminate-like-finish.

It is self priming over plastic laminate, melamine, aluminum and many original factory applied finishes.

TYPE

Waterborne Acrylic

RECOMMENDED USE

The outstanding adhesion and mar-resistance of this enamel make it ideal for refinishing facings of laminated kitchen & bath cabinetry.

COLOR

White. Can be tinted with glycol or water based colorants to a maximum load of 1.2 fluid ounces per quart.

GLOSS LEVEL

Low Luster. 15% to 30% on 60 degree gloss meter.

SOLIDS BY WEIGHT

50% ± 1.0%

SOLIDS BY VOLUME

36% ± 1.0%

VISCOSITY

78-84KU @ 25°C

VOLATILE ORGANIC COMPOUNDS

380 grams per liter Maximum.

ENVIRONMENTAL STATEMENT

This coating's formulation does not contain any ingredients containing lead.

SURFACE PREPARATION

Thoroughly clean surface to remove any contamination (grime, grease etc.). Avoid using cleaners that leave residual waxes or polishes. Sand laminates and factory finishes with #220 to #320 wet/dry paper (use dry). Dull and smooth painted surfaces with fine sandpaper. Remove sanding residue and dry surface.

WARNING! If you scrape, sand, or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a NIOSH approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1- 800-424-LEAD or log on to www.epa.gov/lead.

USE OF PRIMERS

Plastic laminate, Formica® and Aluminum: self priming.

Ferrous metal: Apply rust inhibitive primer.

Bare wood: Shellac knots and sap streaks. Follow with even and full coat of stain blocking primer.

Lacquer, Shellac and Varnished surfaces:

Apply an appropriate pigmented primer (note: this product is NOT compatible with any shellac or shellac based primer).

Other: Test for adhesion and dried film integrity. If paint "crawls" or "cracks", use an appropriate primer.

APPLICATION:

Stir paint thoroughly. Use as supplied. Apply by brush, high density foam roller or spray. Apply thin coats on vertical surfaces.

THINNING:

Use as supplied. If necessary for spray application thin with clean water to a maximum of 1.0 fluid ounce per full quart.

DRY TIME:

At 77°F and 50% humidity: To touch: 30 minutes to one hour.

Recoat: 2 hours (max. 48 hours without lightly sanding).

Resistance to scuffing: 72 hours. Normal use and resistance to blocking: 7 days. Final cure: 20 days.

RECOMMENDED WET/DRY FILM/COAT

3.0 to 4.0 mils. wet. / 1.0 to 1.5 mils dry.

RECOMMENDED SPREAD RATE

100 to 120 sq.ft. per quart. A minimum of 2 coats is recommended.

CLEAN UP

Clean application tools promptly with warm soapy water.

LIMITATIONS

Do not use at temperatures below 50°F.

Not recommended for countertops, desk tops or table tops.

Not recommended for use on floors.

Not for immersion service or on surfaces subjected to frequent dampness (i.e. Sink back splashes, tub and shower surrounds)

WASHABILITY

After 30 days cure time, use non-abrasive solvent free cleaners. A small amount of dishwashing soap on a damp sponge followed by clean damp sponge wipe to remove soap residue is recommended.

PACKAGING

Quart size cans filled to 31 fluid ounces.

WEIGHT PER LITER

2.88 ± lbs. Approx. 2.8 lbs./qt.

FLASH POINT

None detected. Water based material. ASTM D3278, Seta Flash.

PRECAUTIONS

DO NOT TAKE INTERNALLY. USE ONLY WITH ADEQUATE VENTILATION. AVOID CONTACT WITH EYES AND SKIN.

Open windows and doors to allow entry of fresh air during application and drying. Avoid breathing vapors, spray mist or dust created from sanding. Wash exposed skin after using. Close container after each use. Do not transfer contents to other containers for storage.

FIRST AID: If breathing difficulty or dizziness develop get to fresh air. If breathing difficulty or dizziness continues get medical assistance immediately. In case of eye contact, flush eyes with abundant water for 15 minutes and get medical attention. If swallowed, do not induce vomiting – get medical attention immediately.

WARNING:

This product contains a chemical known to the state of California to cause cancer.

A PRODUCT OF:

Decotime, Inc. Ft. Myers FL.

(800) 453 1558

www.decotime.com

Decotime, Inc. believes to the best of our knowledge that information provided herein is accurate, however no warranties, either expressed or implied, of merchantability are made. Use and application of this product are beyond the control of manufacturer, distributor and dealer. Liability if any, is limited to replacement only of product proven to be defective in manufacture. It is the user's responsibility to determine suitability of use for any particular application.