Material Safety Data Sheet



Revision Number: 004.1 Issue date: 03/15/2010

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Loctite Plastic Epoxy-Resin

Product type: Epoxy resin Item number: 1360788

Region: United States

Company address:Contact information:Henkel CorporationTelephone: 800.624.7767

One Henkel Way Emergency telephone: 800.424.9300

Rocky Hill, CT 06067

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state:LiquidHEALTH:2Color:Translucent, ClearFLAMMABILITY:1Odor:NonePHYSICAL HAZARD:0

Personal Protection: See MSDS Section 8

WARNING: MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects

Inhalation: Mild respiratory tract irritation.

Skin contact: Allergic skin reaction. Moderate skin irritation. Itching. Redness.

Eye contact: Moderate eye irritation. Redness.

Ingestion: Not expected under normal conditions of use.

Existing conditions aggravated by

exposure:

Skin disorders. Skin allergies.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS			
Hazardous components	CAS NUMBER	%	
Epichlorohydrin-4,4'-isopropylidene diphenol resin	25068-38-6	60 - 100	

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms develop and persist, get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. If symptoms develop and persist, get

medical attention.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

Ingestion: Keep individual calm. DO NOT induce vomiting unless directed to do so by

medical personnel. If symptoms develop and persist, get medical attention.

IDH number: 1360788 Product name: Loctite Plastic Epoxy-Resin

5. FIRE FIGHTING MEASURES

Flash point: > 249 °C (> 480.2 °F) Pensky Martens closed cup

Autoignition temperature:

Flammable/Explosive limits - lower:

Not available

Flammable/Explosive limits - upper:

Not available

Extinguishing media: Foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: In case of fire, keep containers cool with water spray. Closed containers may

rupture (due to build up of pressure) when exposed to extreme heat.

Hazardous combustion products: Oxides of carbon. Irritating organic fragments.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Immediately contact emergency personnel.

Scrape up as much material as possible. Clean residue with soap and water.

Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling: Do not breathe gas/fumes/vapor/spray. Avoid contact with eyes, skin and

clothing. Wash thoroughly after handling. Keep container closed.

Storage: Store in original container until ready to use. Keep in a cool, well ventilated

area away from heat, sparks and open flame. Keep container tightly closed

until ready for use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Epichlorohydrin-4,4'-isopropylidene diphenol resin	None	None	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use a NIOSH approved air-purifying respirator if the potential to exceed

established exposure limits exists.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Chemical resistant, impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color: Translucent, Clear

IDH number: 1360788 Product name: Loctite Plastic Epoxy-Resin

Odor: None

Odor threshold:

pH:

Not available

Not applicable

Vapor pressure:

0.03 mm Hg

Boiling point/range: $> 260.2 \,^{\circ}\text{C} \,(> 500.4 \,^{\circ}\text{F})$

Melting point/ range: Not available

Specific gravity: 1.1

Vapor density: Not available

Flash point: > 249 °C (> 480.2 °F) Pensky Martens closed cup

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

Not available

Not available

Not available

VOC content: 0.1 % (value for resin and hardener together)

10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition products: None

Incompatible materials: Strong oxidizing agents. Strong bases. Strong acids. Amines.

Conditions to avoid: Excessive heat. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Epichlorohydrin-4,4'-isopropylidene diphenol resin	No	No	No

Hazardous components	Health Effects/Target Organs
Epichlorohydrin-4,4'-isopropylidene diphenol resin	Allergen, Irritant

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

IDH number: 1360788 Product name: Loctite Plastic Epoxy-Resin

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-A

Epichlorhydrine resin)

Hazard class or division: 9

Identification number: UN 3082
Packing group: III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: None above reporting de minimus

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA 313: None above reporting de minimus

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

IDH number: 1360788

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

WHMIS hazard class: D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format

Prepared by: Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

Material Safety Data Sheet



Revision Number: 001.1 Issue date: 03/15/2010

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: Loctite Plastic Epoxy- Hardener

Product type: Epoxy Hardener Item number: 1360788

Region: United States

Company address:Contact information:Henkel CorporationTelephone: 800.624.7767

One henkel Way Emergency telephone: 800.424.9300 Rocky Hill, CT 06067

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

HMIS:

Physical state:LiquidHEALTH:*3Color:Amber, TranslucentFLAMMABILITY:1Odor:Amine, MercaptanPHYSICAL HAZARD:0

Personal Protection: See MSDS Section 8

DANGER: CAUSES EYE, SKIN AND RESPIRATORY TRACT BURNS.

MAY CAUSE ALLERGIC SKIN REACTION.

HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN.

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects

Inhalation: Respiratory tract burns. May cause respiratory tract irritation. May cause irritation to nose and

throat. Lung damage.

Skin contact: May cause skin burns. May cause allergic skin reaction. May be harmful if absorbed through

skin. Rash. Redness. Tissue damage.

Eye contact: Burns. Severe eye irritation. Redness. Tissue damage.

Ingestion: May be harmful if swallowed. May cause burns of mouth and throat if swallowed.

Existing conditions aggravated by

exposure:

Eye, skin, and respiratory disorders. Skin allergies. Asthma.

This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR

1910.1200).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous components	CAS NUMBER	%
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptop	72244-98-5	60 - 100
m-Phenylenebis(methylamine)	1477-55-0	10 - 30
2,4,6-Tris(dimethylaminomethyl)phenol	90-72-2	5 - 10
Phenol	108-95-2	1 - 5

4. FIRST AID MEASURES

Inhalation:Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

IDH number: 1360788 Product name: Loctite Plastic Epoxy- Hardener

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Wash clothing before reuse. Thoroughly clean shoes before reuse. If symptoms develop and persist, get medical

attention.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person. Keep individual

calm. Get medical attention.

5. FIRE FIGHTING MEASURES

Flash point: > 93 °C (> 199.4 °F) Tagliabue closed cup

Autoignition temperature: Not available

Flammable/Explosive limits - lower: Not available

Flammable/Explosive limits - upper: Not available

IDH number: 1360788

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: In case of fire, keep containers cool with water spray.

Hazardous combustion products: Oxides of carbon. Oxides of nitrogen. Ammonia. Amines. Nitric acid.

Nitrosamines Irritating organic fragments.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow product to enter sewer or waterways.

Clean-up methods: Remove all sources of ignition. Immediately contact emergency personnel.

Scrape up as much material as possible. Clean residue with soap and water.

Store in a closed container until ready for disposal.

7. HANDLING AND STORAGE

Handling: Keep away from heat, spark and flame. Do not breathe

gas/fumes/vapor/spray. Keep container closed. Avoid contact with eyes, skin

and clothing. Wash thoroughly after handling.

Storage: Store in original container until ready to use. Keep in a cool, well ventilated

area away from heat, sparks and open flame. Keep container tightly closed

until ready for use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous components	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w- hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3- propanediol (4:1), 2-hydroxy-3-mercaptop	None	None	None	None
m-Phenylenebis(methylamine)	0.1 mg/m3 Ceiling (SKIN)	None	None	None
2,4,6-Tris(dimethylaminomethyl)phenol	None	None	None	None
Phenol	5 ppm TWA (SKIN)	5 ppm (19 mg/m3) TWA (SKIN)	None	None

Engineering controls: Use local exhaust ventilation if the potential for airborne exposure exists.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Chemical resistant, impermeable gloves.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid

Color: Amber, Translucent
Odor: Amine, Mercaptan
Odor threshold: Not available
pH: Not available
Vapor pressure: Not available
Boiling point/range: Not available
Melting point/ range: Not available

Specific gravity: 1.04
Vapor density: Not available

Flash point: > 93 °C (> 199.4 °F) Tagliabue closed cup

Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Evaporation rate:
Solubility in water:
Partition coefficient (n-octanol/water):
Not available
Insoluble
Not available

VOC content: 3.77 %; 0.38 g/l EPA Method 24

10. STABILITY AND REACTIVITY

Stability: Stable

IDH number: 1360788

Hazardous reactions: Will not occur.

Hazardous decomposition products: Oxides of carbon. Oxides of nitrogen. Ammonia. Amines. Nitric acid.

Nitrosamines. Irritating organic fragments.

Incompatible materials: Strong acids. Strong oxidizing agents. Halogenated compounds. Strong

mineral acids. Reactive metals. Calcium hypochlorite. Sodium hypochlorite.

Nitrous acid and other nitrosating agents.

Conditions to avoid: Excessive heat. Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptop	No	No	No
m-Phenylenebis(methylamine)	No	No	No
2,4,6-Tris(dimethylaminomethyl)phenol	No	No	No
Phenol	No	No	No

Hazardous components	Health Effects/Target Organs
Poly[oxy(methyl-1,2-ethanediyl)], a-hydro-w-hydroxy-, ether with 2,2-bis(hydroxymethyl)-1,3-propanediol (4:1), 2-hydroxy-3-mercaptop	No Data
m-Phenylenebis(methylamine)	Irritant, Liver, Kidney, Corrosive
2,4,6-Tris(dimethylaminomethyl)phenol	Irritant, Allergen
Phenol	Blood, Cardiac, Corrosive, Developmental, Eyes, Irritant, Kidney, Liver, Mutagen, Nervous System, Skin, Vascular

12. ECOLOGICAL INFORMATION

Ecological information: Not available

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

Hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The shipping classifications in this sections are for non-bulk packaging only (unless otherwise specified). Shipping classification may be different for bulk packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (aliphatic Amine)

Hazard class or division: 8
Identification number: UN 2735
Packing group: II

International Air Transportation (ICAO/IATA)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (aliphatic Amine)

Hazard class or division: 8
Identification number: UN 2735
Packing group: II

Water Transportation (IMO/IMDG)

Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (aliphatic Amine)

Hazard class or division: 8
Identification number: UN 2735
Packing group: II

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

IDH number: 1360788 Product name: Loctite Plastic Epoxy- Hardener

TSCA 12(b) Export Notification: None above reporting de minimus

CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: Phenol (CAS# 108-95-2). Immediate Health, Delayed Health

CERCLA/SARA 313:

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Phenol (CAS# 108-95-2).

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

IDH number: 1360788

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

WHMIS hazard class: D.2.A, D.2.B, E

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: First issue.

Prepared by: Regulatory Affairs

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.