D Dieline Metal Half Pint 9.437 x 2.687

000000

El Wood Stain de Varathane es un producto a base de aceite formulado con pigmentos de primera calidad que resultan en color más profundo, rico y natural para sus proyectos de madera. Los Tintes Varathane de Primera con Base de Aceite dan color a su madera, y descubren su belleza. Son ideales para muebles, gabinetes, puertas, adornos, pisos y paneles, en el interior.

PREPARACIÓN: Remueva los acabados previos con papel lija o raspador. Prepare la madera para el tinte lijando hacia el grano, usando lija #120 y progrese con #150, #180 y #220. Antes de aplicar el tinte, remueva los residuos del lijado, polvo, suciedad,grasa o cualquier adhesivo con una aspiradora o un trapo limpiomojado con espíritus de mineral. Con maderas suaves (pino, abeto,arce) use acondicionador de madera. Use el Acondicionador Varathane® antes de aplicar el tinte.

¡ADVERTENCIA! Si usteddrasca, lija o remueve la pintura vieja, usted puede sufrir polvo deplomo. EL PLOMO ES TÓXICO. UNA EXPOSICIÓN CON EL PLOMO PUEDECAUSAR UNA ENFERMEDAD SERIA COMO DAÑOS AL CEREBRO,ESPECIALMENTE EN LOS NIÑOS Y MUJERES ESPERANDO FAMILIA. Úseun respirador aprobado por NIOSH para controlar la exposición conel plomo. Limpie con una aspiradora de aire con filtro HEPA vestropaño humedo. Antes de empezar, averigue como protegerse ya su familia llamando a 1-800-424-LEAD (5323) o visite al sitiowww.epa.gov/lead.PRUEBA DE COLOR: Verifique el color deseado definite en una area fuera de la vista. APLICACIÓN DEL TINTE: Mezcle y combinejo bienantes de usar. Aplicar generosamente con un cepillo o un pairo limpio libre de pelusas. Aplique tinte a través del grano hasta saturar la superficie. Limpie frotándo el exceso del tinte siguiendo el grano de la madera. No deje que el tinte seque antes de eliminar el exceso. Aplique una segunda capa después de 2 horas. No lije entre la aplicación de cualquier capa. Para obtener mejores resultados, utilicelo a temperaturas entre 60 ° F y 90 ° F.

PROTECCIÓN DE SU MADERA: Para completarsu proyecto escoja uno de los muchos otros Varathane® Acabadoede Primera para Madera. Permita que el tinte seque por 8 horas siestá usando un acabado con base de aceite o espere 24 horas para un acabado con base de agua.

COBERTURA: Aproximadamente 150 pies²/cuarto.

LIMPIEZA: Use espíritus de mineral o diluyente para pintura.

¡PELIGRO! CONTIENE: ÉTERES DE GLICOL. Aguarrás. Vapor dañino. Puede afectar el cerebro o el sistema nervioso causando mareos, dolor de cabeza o náuseas. Provoca irritación en los ojos, la piel, la nariz y la garganta.

AVISO: Hay reportes que han asociado la sobreexposición ocupacional repetida y prolongada a solventes con daños permanentes al cerebro y sistema nervioso. El mal uso intencional de concentrando e inhalando el contenido puede ser dañino o fatal. Mantenga alejado del calor, chispas y llamas. Evite la acumulación de vapores abriendo todas las ventanas y puertas para lograr una ventilación cruzada. No respire vapores o niebla del rociado. **Use solamente con ventilación adecuada.** Asegúrese de que entre aire fresco durante la aplicación y el secado. Si le lloran los ojos, tiene dolores de cabeza o mareos, o el control del aire demuestra que los niveles de vapor o rocío son superiores a los límites aplicables, use un respirador apropiado que se ajuste adecuadamente (aprobado por NIOSH, Instituto Nacional para la Seguridad y Salud Ocupacional) durante y después de la aplicación. Siga las instrucciones de uso del respirador proporcionadas por el fabricante. Cierre el contenedor después de cada uso. Evite contacto con ojos, piel o ropa. Lave sus manos completamente después de agarrar. **MANTENGA FUERA DEL ALCANCE DE LOS NIÑOS. PRIMEROS AUXILIOS:** Si usted sufre de lagrimeo de los ojos, dolores de cabeza o mareo, aumente la cantidad de aire fresco o salga del área. Si continua teniendo dificultades, obtenga atención médica inmediatamente. En caso de contacto con los ojos, enjuague inmediatamente con bastante agua por 15 minutos y busque atención médica inmediatamente; para la piel, lávese bien con jabón y agua. En caso de ingestión (tragar), no induzca el vómito. Llame a un médico inmediatamente. En caso de un derrame, contenga el material derramado y remueva con un absorbente inerte. PELIGRO: Los trapos, virutilla o cualquier otro material saturado con este producto puede causar un incendio espontáneo si se desecha en una forma inapropiada. Inmediatamente después del uso, ponga los trapos, virutilla y todos los desechos en un contenedor de metal lleno de agua y cierre bien. Disponga de acuerdo a las regulaciones locales sobre los materiales incendiarios.

⚠ **ADVERTENCIA:** Cáncer y daños reproductivos – www.P65Warnings.ca.gov.

SATISFACCIÓN GARANTIZADA: Si no está satisfecho con este producto, comuníquese con el Soporte Técnico de Rust-Oleum al 800-901-0411 para obtener un reembolso del total del precio de compra. Consulte el número de producto y el código de lote.

Max VOC ≤ 550 g/L

Varathane®

SINCE 1958

CLASSIC

PENETRATING

WOOD STAIN

FPO

ENGLISH CHESTNUT

DANGER! COMBUSTIBLE LIQUID AND VAPOR. VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. Read carefully other cautions on back panel.

8 FL OZ 237ml

PELIGRO! VAPORES Y LIQUIDO COMBUSTIBLES. Lea atentamente otras precauciones al dorso.

Varathane® Classic Oil-Based Penetrating Wood Stains are formulated with a unique base for deep penetration and premium pigments for clear color. This results in a deeper, richer and more natural color for your wood projects. From floors to furniture, Varathane Classic Wood Stains are formulated not just to stain wood, but to reveal its true beauty. This product is ideal for use on all interior projects including: furniture, cabinets, doors and trim, floors and paneling.

PREPARATION: Remove any existing finishes with sandpaper or stripper. Prepare bare wood for staining by sanding in the direction of the grain. Begin with #120 grit sandpaper and progress through #150, #180 and #220 grits. Before staining, remove all sanding dust, dirt, grease or glue with a vacuum, or clean rag dampened with mineral spirits. Soft woods such as pine, fir and maple require a wood conditioner. Use Varathane® Wood Conditioner before staining.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN, PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

TESTING COLOR: Be sure to test your stain to verify the desired color. To test, apply the stain in an inconspicuous area. When using more than one can, pour all contents together in a separate container and mix well to ensure color uniformity. Stir occasionally throughout application.

PROTECTING YOUR WOOD: To complete your project choose one of the many Varathane® Wood Finishes. Allow Varathane Wood Stains to dry for 8 hours when applying an oil-based finish or 24 hours when applying a water-based finish.

STAIN APPLICATION: Stir the contents thoroughly before use. Apply liberally with a brush or clean, lint-free cloth. Apply the stain across the grain until the wood is saturated on top. Wipe the excess stain off in the direction of the wood grain. Do not let the stain dry before wiping excess. A second coat can be applied after 2 hours. Do not sand between stain coats.

COVERAGE: Approximately 150 sq. feet/quart. Coverage may vary depending on the applicator and wood species used.

CLEAN UP: Use mineral spirits or paint thinner.

CONTAINS PETROLEUM DISTILLATES AND AROMATIC HYDROCARBONS. Vapor Harmful. May affect the brain or nervous system causing dizziness, headache or nausea. Causes eye, skin, nose and throat irritation. May cause liver and kidney damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Keep away from heat, sparks and flame. **Vapors may cause flash fire.** Do not smoke. Extinguish all flame and pilot lights, and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. **Use only with adequate ventilation.** Do not breathe dust, vapors or spray mist. Ensure fresh air entry during application and drying. If you experience eye watering, headache or dizziness or if you are concerned about exposure levels, see doctor immediately. Wear an appropriate, properly fitted respirator NIOSH approved during and after application. Follow respirator manufacturer's directions for use. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. **KEEP OUT OF REACH OF CHILDREN. FIRST AID:** In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention immediately. For skin, wash thoroughly with soap and water. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. If swallowed, do not induce vomiting. Get medical attention immediately. **For emergency, call your physician, local poison control center or local emergency room. For product health information, call: (800)-553-3126.** Wipe up spills, clean rags or other waste soaked with this product may spontaneously ignite in a improperly discarded, unventilated trash can, place rags, clean wipes or waste in a sealed, water-filled, metal container. Dispose of in accordance with local fire regulations.

⚠ **WARNING:** Cancer and Reproductive Harm – www.P65Warnings.ca.gov.

SATISFACTION GUARANTEED: If you are dissatisfied with this product, contact Rust-Oleum Product Support at 800-901-0411 for product replacement or a full refund of the purchase price. Refer to product number and batch code.

For Interior Wood Substrates Only

Max VOC ≤ 550 g/L

RUST-OLEUM
CORPORATION
11 Hawthorn Pkwy., Vernon Hills, IL 60061
800-901-0411 rustoleum.com/varathane
Made in USA | Hecho en E.U.A.
©2018 Rust-Oleum Corporation L339737R-P 0418

339737 ENGLISH CHESTNUT

0 20066 42816 7

Overlap to 21/32"

Copy Margins all 4 sides

Bleed 1/8" Top, Bottom, Right

Background should extend to 7/16" glue lap

03/14/18	SA	Woodcare	
WDC_0035_0318_VAR_8oz_THD_VarathaneClassic_HP			
Principal Display Panel: **9.72"**		Signal Word: **.094"**	Statement of Hazard: **.0625"**
Other Cautionary Material: **.0625"**	Other Cautionary Material (Back label): **.0625"**		
Other Cautionary Material (Address): **.0625"**	Net Wt: **.125"**		

All dimensions are based on the measurements within the label at 100% actual size.