SCh simply moder

Undermount Stainless Steel Sink Installation Instructions

FOR MODELS: SC604016, SC4060RV16, SC604018, SC4060RV18, SC505016, SC505018, SC703016, SC3070RV16, SC703018, SC3070RV18, SCSB301816, SCSB301818, SCSDB18, SCSBL18, SCSBR18, SCSBSB18, SCSBSB18, SCRASB321916, SCRA604016, SCRA505016, SCRASB231916, SCRASB152016, SCSLB18, SCLD505018, SCSBE18



Before You Start


- Schön recommends that all undermount sinks be installed by an experienced, professional installer.
- IMPORTANT: The enclosed cutout template will create a countertop opening with a minimal (1/8" or less) reveal. It is recommended that you discuss this with your installer and agree that this finished appearance is the desired effect. Schön is not responsible for improper sink or countertop installations.
- IMPORTANT: The cabinet must be installed, secured, plumb, and level. Failure of this step can lead to product damage.
- Schön undermount sinks should only be fastened to a solid surface countertop (i.e. granite, Corian[®] or Silestone[®]).
- Schön is not responsible for sink or countertop if damaged during installation. Be sure to inspect the sink for damage prior to beginning installation.
- Metal edges may be sharp use caution when handling.
- Follow all local plumbing and building codes.

Recommended Tools & Materials (Not Included)


Tape Measure	Shims or Cabinet Fillers
□ Safety Glasses	Denatured Alcohol
Painter's Tape	Clamps
Level	Construction Adhesive
Framing Square	□ Silicone Sealant
Pencil (not permanent marker)	□ Screws (recommended by countertop manufacturer)

Schön^w simply modern

Undermount Stainless Steel Sink Installation Instructions



- 1. Position the template (provided with your sink) front to rear so the sink will not interfere with the cabinet; secure with tape.
- 2. Trace the template and remove. Dry fit the sink to verify the measurements.
- 4. Following the countertop manufacturer's instructions, carefully cut the countertop on the inside of the traced line.
- 5. Locate and drill the mounting holes, following the countertop manufacturer's instructions. Holes should allow even spacing of mounting brackets around the sink.
- 6. With the countertop inverted (upside down), fasten the mounting brackets to the countertop loosely.
- IMPORTANT: The cabinet must be installed, secured, plumb, and level BEFORE installing the sink.
- IMPORTANT: Schön undermount sinks should only be fastened to a solid surface countertop (i.e. granite, Corian® or Silestone®).



VERIFY SINK IS CENTERED WITHIN THE COUNTERTOP OPENING BEFORE TIGHTENING FASTENERS.

2: INSTALL COUNTERTOF

3: FINAL STEPS



- 1. Clean the bottom of the countertop and the top flange (or lip) of the sink with denatured alcohol.
- 2. Apply a narrow bead of silicone adhesive sealant evenly all around the top of the sink flanges.
- 3. Position and align the sink over the countertop opening. Press silicone onto countertop.
- 4. Tighten fasteners until mounting brackets are snug against sink. Check alignment of sink to the countertop opening.
- 5. Tighten down fasteners evenly. Be careful not to over-tighten.
- 6. Immediately remove excess sealant.
- ▲ IMPORTANT: The enclosed cutout template will create a countertop opening with a minimal (1/8" or less) reveal. It is recommended that you discuss this with your installer and agree that this finished appearance is the desired effect. Schön is not responsible for improper sink or countertop installations.
- IMPORTANT: Schön is not responsible for sink or countertop if damaged during installation. Be sure to inspect the sink for damage prior to beginning installation.
- 1. Following all local plumbing and building codes, install the faucet according to the manufacturer's instructions.
- 2. Connect the drain and piping.
- 3. Run water into the sink and check all connections for leaks.
- IMPORTANT: For additional information or warranty issues visit www.schonsimplymodern.com or contact Schön directly at: Schön Warranty Dept, World Imports Decorative Plumbing 3074 Chastain Meadows Parkway Marietta, GA 30066 (800) 880-8164