

ARTISAN PAVER CLEANER

Use **ARTISAN® Paver Cleaner** to restore and maintain concrete pavers, stamped concrete, brick, exposed aggregate and other similar surfaces. Use **ARTISAN®** to remove stains, efflorescence and surface discolorations that accumulate throughout the winter and during in-season use. This product is non-fuming, V.O.C. compliant, phosphate free and is specifically designed for use on concrete pavers. **ARTISAN®** contains a rust inhibitor that eliminates iron staining and an environmentally friendly surfactant that provides superior detergency properties. **ARTISAN®** does not contain any hydrofluoric, nitric, phosphoric, bleach, caustic or petroleum distillates and can be safely used on a regular basis.

DILUTION

Always pour cleaner into water. Never pour water into cleaner. Only use this product with plastic containers, sprayer and applicators. Do not use or apply this product with metal containers, sprayer or applicators. For heavy duty cleaning use undiluted. For light duty cleaning dilute cleaner with equal parts water (1:1). For wet cast pavers dilute 1 part cleaner with 2 parts water.

HOW TO USE

NOTE: Keep this product away from plants and vegetation. To minimize damage to grass and plants, thoroughly saturate surrounding areas with water before and during application and after rinsing. Do not allow this product to come in contact with any metal surfaces. This product will stain metal. Keep away from polished and honed natural stone. **WET CAST PAVERS:** When using on wet cast pavers, dilute one part cleaner with 2 parts water and test accordingly. Adjust dilution and/or dwell time based on results. Allow surface to dry before determining proper dilution, dwell time and desired results. Protect all surfaces this product is not intended with plastic sheeting. Work on manageable areas of approximately 200-250 square feet at a time.

1. Apply using a stiff, nylon brush or a plastic garden sprayer. Do not apply this product with metal containers or tools. Pour cleaner into a clean, plastic bucket or garden sprayer. 2. Evenly and thoroughly apply onto the surface and allow to dwell for approximately 5 minutes. The dwell time should match the dwell time from your test patch. Do not allow product to dry on the surface. If necessary, lightly mist with water to prevent product from drying or apply more cleaner. Do not apply product onto a hot surface. If surface is hot, evenly pre-wet with clean water without saturating, then apply cleaner. 3. After allowing proper dwell time, lightly scrub surface using a bristle brush and rinse with clean water or power wash. It is imperative that all chemical residue is completely rinsed from the surface. 4. If after drying, there are any remaining discolorations or stains, repeat process. For deep seated stains use **ARTISAN® Grease & Oil Remover**. When surface is thoroughly clean and dry, apply **ARTISAN® Water Repellent** or **ARTISAN® Color Enhancer**, following the directions on the label.

TEST AREA

Since it is impossible to know all of the conditions of the surface before cleaning, it is imperative that a small test be done on an inconspicuous area, and allowed to dry to determine dilution, compatibility and desired results.

COVERAGE

RATE: 200-400 square feet per gallon. Coverage rates vary depending upon the method of application and porosity.

STORAGE & SHELF LIFE

Store in a cool, dry place and away from incompatible materials. Close container after each use.

SAFETY

Wear neoprene, nitrile, 4H or other impervious gloves. Wear impervious apron, boots and other protective clothing. Wear chemical resistant safety goggles and/or face shields unless a full face piece respirator is used. Do not wear contact lenses. For spray applications and other jobs where the recommended exposure limit may be exceeded, an approved full face piece particulate respirator may be required. Select in accordance with OSHA 1910.134 and good industrial hygiene practices.

DANGER

KEEP OUT OF REACH OF CHILDREN

CORROSIVE LIQUID. CONTACT WITH EYES WILL CAUSE BURNS WITH POSSIBLE EYE DAMAGE. SKIN CONTACT MAY CAUSE MILD IRRITATION (Non-corrosive to skin, as per OSHA Standards, DOT Regulations and Canada's WHMIS regulations). Prolonged skin contact may cause drying, defatting or dermatitis. HARMFUL OR FATAL IF SWALLOWED. CAN BE IRRITATING TO RESPIRATORY TRACT. FIRST AID: **EYES:** Immediately flush eyes with water for 15 minutes, while lifting the upper and lower lids. Seek immediate medical attention. **SKIN:** Immediately flush with soap and water until no trace of chemical remains. Seek medical attention if irritation develops and persists. Remove contaminated clothing and launder before reuse. **INHALATION:** Move victim to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, have qualified personnel administer oxygen. Get medical attention. **INGESTION:** Get immediate medical attention. If conscious rinse mouth with water and give 1-2 glasses of water to dilute. Do not induce vomiting. Never give anything by mouth to an unconscious or convulsing person. Contains organic salt and surfactant.

V.O.C: Contains less than 25 g/L.

PAVER CARE MADE EASY™

ARTISAN® PAVER CLEANER

- RESTORES APPEARANCE OF PAVERS
- FAST ACTING
- WATER BASED FORMULA
- MURIATIC FREE



FOR PAVERS, BRICK AND MASONRY

1 GALLON
(3.785 liters)

DANGER: CORROSIVE LIQUID. CONTACT WITH EYES WILL CAUSE SEVERE BURNS WITH POSSIBLE EYE DAMAGE. Harmful or fatal if swallowed. **KEEP OUT OF REACH OF CHILDREN**

See back panel for additional cautions and first aid.



LIMITED WARRANTY

The manufacturer and distributors liability under any expressed or implied warranty is limited solely to replacement of product that is defective or refund of the purchase price. The manufacturer and distributors shall not be liable for injury, labor or any consequential damages.

QUESTIONS/COMMENTS?

Call 800-225-4161

(9:00 AM - 5:00 PM E.S.T.)

or visit us at

www.chemique.com

Manufactured
in the USA by:



Chemique, Inc.
315 N. Washington Ave.
Moorestown, NJ 08057

Product #99911



POSITION ONLY

