

 View MSDS
 1
 2
 3
 4
 5
 6
 7
 8
 9
 10
 11
 12
 13
 14
 15
 16

## SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: MSDS Manufacturer Number: Manufacturer Name: Address:	Premium Plus Porch & Floor Paint Low-Lustre Deep Base No. 6300 6300 BEHR Process Corporation 3400 W. Segerstrom Avenue Santa Ana, CA 92704 (714) 545 - 7101	NFPA 1 1 0	, a
General Phone Number:	(714) 545-7101		
General Fax Number:	(714) 241-1002	HMIS	
Customer Service Phone Number:	(800) 854-0133 ext. 2	Health Hazard	1
CHEMTREC:	For emergencies in the US, call CHEMTREC: 800-424-9300	Fire Hazard	1
Canutec:	In Canada, call CANUTEC: (613) 996-6666 (call collect)	Reactivity	ο
MSDS Creation Date:	January 30, 2007	-	-
MSDS Revision Date:	January 31, 2010	Personal Protection	
MSDS Format:	According to ANSI Z400.1-2004	* Chronic Health I	Effects

#### SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

CAS#	Ingredient Percent
No data	5 - 10 by weight
5444-75-7	1 - 5 by weight
37244-96-5	10 - 30 by weight
Proprietary	10 - 30 by weight
Not applicable	30 - 60 by weight
	No data 5444-75-7 37244-96-5 Proprietary

# SECTION 3 - HAZARDS IDENTIFICATION

Emergency Overview:	Irritant.
Potential Health Effects:	
Eye:	May cause irritation.
Skin:	May cause irritation.
Inhalation:	Prolonged or excessive inhalation may cause respiratory tract irritation.
Ingestion:	May be harmful if swallowed. May cause vomiting.
Chronic Health Effects:	Prolonged or repeated contact may cause skin irritation.
Signs/Symptoms:	Overexposure may cause headaches and dizziness.
Target Organs:	Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions:	None generally recognized.

### SECTION 4 - FIRST AID MEASURES

Eye Contact:	Immediately flush eyes with plenty of water for 15 to 20 minutes. Get medical attention, if irritation or symptoms of overexposure persists.
Skin Contact:	Immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.
Other First Aid:	Due to possible aspiration into the lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have the person lean forward to reduce the risk of aspiration.

# SECTION 5 - FIRE FIGHTING MEASURES

Flash Point:

No Data

t applicable. e alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray en fighting fires involving this material. in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH proved or equivalent) and full protective gear.
en fighting fires involving this material. in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH
E MEASURES
e proper personal protective equipment as listed in section 8.
pid runoff into storm sewers, ditches, and waterways.
sorb spill with inert material (e.g., dry sand or earth), then place in a chemical ste container. Provide ventilation. Clean up spills immediately observing cautions in the protective equipment section.
AGE
e with adequate ventilation. A void breathing vapor and contact with eyes, skin I clothing.
re in a cool, dry, well ventilated area away from sources of heat, combustible terials, and incompatible substances. Keep container tightly closed when not in e.
sh thoroughly after handling. A void contact with eyes and skin. A void inhaling oor or mist.
5, PERSONAL PROTECTION - EXPOSURE GUIDELINES
e appropriate engineering control such as process enclosures, local exhaust itilation, or other engineering controls to control airborne levels below
ommended exposure limits. Good general ventilation should be sufficient to trol airborne levels. Where such systems are not effective wear suitable sonal protective equipment, which performs satisfactorily and meets OSHA or er recognized standards. Consult with local procedures for selection, training, pection and maintenance of the personal protective equipment.
trol airborne levels. Where such systems are not effective wear suitable sonal protective equipment, which performs satisfactorily and meets OSHA or er recognized standards. Consult with local procedures for selection, training, pection and maintenance of the personal protective equipment. ar appropriate protective glasses or splash goggles as described by 29 CFR
trol airborne levels. Where such systems are not effective wear suitable sonal protective equipment, which performs satisfactorily and meets OSHA or er recognized standards. Consult with local procedures for selection, training, pection and maintenance of the personal protective equipment. ar appropriate protective glasses or splash goggles as described by 29 CFR 10.133, OSHA eye and face protection regulation, or the European standard EM 5.
trol airborne levels. Where such systems are not effective wear suitable sonal protective equipment, which performs satisfactorily and meets OSHA or er recognized standards. Consult with local procedures for selection, training, pection and maintenance of the personal protective equipment. ar appropriate protective glasses or splash goggles as described by 29 CFR 10.133, OSHA eye and face protection regulation, or the European standard EN 5. emical-resistant gloves and chemical goggles, face-shield and synthetic apron coveralls should be used to prevent contact with eyes, skin or clothing. ar appropriate protective gloves. Consult glove manufacturer's data for

Physical State Appearance:	Liquid.
Boiling Point:	No Data
Melting Point:	No Data
Density:	8 - 10 Lbs./gal.
Vapor Density:	Greater than 1 (Air = 1).
Vapor Pressure:	Greater than 1 (Air = 1).
pH:	No Data
Molecular Formula:	Mixture
Molecular Weight:	Mixture
Flash Point:	No Data
VOC Content:	Material VOC: 17 gm/l (Includes Water) Coating VOC.: 48 gm/l (Excludes Water)

# SECTION 10 - STABILITY and REACTIVITY

Chemical Stability:	Stable under normal temperatures and pressures.
Hazardous Polymerization:	Not reported.
Conditions to Avoid:	Heat, flames, incompatible materials, and freezing or temperatures below 32 deg.

	F.
Incompatible Materials:	Oxidizing agents. Strong acids and alkalis.
Special Decomposition Produc	cts: Incomplete combustion may produce carbon monoxide and other toxic gases.
SECTION 11 - TOXICOLOG	ICAL INFORMATION
SECTION 12 - ECOLOGICA	L INFORMATION
Ecotoxicity:	No ecotoxicity data was found for the product.
Environmental Fate:	No environmental information found for this product.
Waste Disposal:	Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with yo state and local waste requirements or guidelines, if applicable, to ensure compliance. A rrange disposal in accordance to the EPA and/or state and local guidelines.
SECTION 14 - TRANSPORT	INFORMATION
DOT UN Number:	No Data
DOT Hazard Class:	No Data
SECTION 15 - REGULATOR	Y INFORMATION
California PROP 65:	WARNING: This product contains a chemical known to the state of California to

cause cancer and birth defects or other reproductive harm.

This Health and Safety Information is correct to the best of our knowledge and belief at the date of its publication but we cannot accept liability for any loss, injury or damage which may result from its use. We shall ensure, so far as is reasonably practicable, that any revision of this Data Sheet is sent to all customers to whom we have directly supplied this substance, but must point out that it is the responsibility of any intermediate supplier to ensure that such revision is passed to the ultimate user. The information given in the Data Sheet is designed only as a guidance for safe handling, storage and the use of the substance. It is not a specification nor does it guarantee any specific properties. All chemicals should be handled only by competent personnel, within a controlled environment. Should further information be required, this can be obtained through

the sales office whose address is at the top of this data sheet.

Copyright© 1996-2010 Actio Software Corporation. All Rights Reserved.

The trademarks, service marks, graphics and logos used on this MSDS are registered or unregistered trademarks of BEHR Process Corporation. All Rights

Listed

Listed

Listed

1

1

0

х

January 30, 2007 January 31, 2010

Actio Corporation

Reserved.

Quarterly formula update

Not listed

Premium Plus Porch & Floor Paint Low-Lustre Deep Base No. 6300 Revison: 1/31/2010, Version:

2-ethylhexyl benzoate : TSCA Inventory Status:

SECTION 16 - ADDITIONAL INFORMATION

Canada DSL:

Canada DSL:

Nepheline Syenite : TSCA Inventory Status:

HMIS Health Hazard:

MSDS Creation Date:

MSDS Revision Date: MSDS Revision Notes:

HMIS Fire Hazard:

HMIS Reactivity:

HMIS Other:

MSDS Author:

Disclaimer:

Trademark: