



ALL-IN-ONE WOOD CLEANER

NO. 63



PRODUCT INFORMATION

BEHR PREMIUM® All-In-One Wood Cleaner is specifically formulated to clean, brighten and condition exterior wood surfaces prior to applying natural finishes, paints or stains. It's tough enough for stains caused by mold mildew, ketchup and wine, but gentle enough that it won't damage your wood surface.

RECOMMENDED USES:

For use on exterior surfaces such as:

- Wood & Composites
- Concrete
- Vinyl Siding

PRODUCT SPECIFICATIONS:

Tint Bases/Max Tint Load:

No. 63 128 oz

Active Type: Oxalic Acid

Weight per Gallon: 8.5 lbs

% Solids by Weight: 6.6%

VOC: <1 wt %

Flash Point: N/A

Viscosity: N/A

Coverage: One gallon of full strength will cover 200 Sq. Ft. / Gal. and diluted solution will clean and degrease up to 400 Sq. Ft. / Gal. and one gallon of depend on method of application, texture and surface porosity.

APPLICATION:

Brush: Nylon/polyester

Roller:

Smooth Surface: 3/8"-1/2" nap

Rough Surface: 1/2"-3/4" nap

Pump Sprayer: At packaged consistency

Apply solution liberally with a pump sprayer, brush, mop or roller. Keep the surface completely wet with solution for 10-15 minutes. Scrub surface using a stiff bristle broom or brush. The solution will foam. After scrubbing, rinse thoroughly with water at normal pressure, or use a pressure washer at low setting (500-1200 PSI). Do not use high pressure.

SURFACE PREPARATION:

Be sure to have a source for water, hose with nozzle and stiff bristle broom or brush. Wear protective clothing, goggles, acid resistant gloves. Always use a product such as BEHR PREMIUM All-In-One Wood Cleaner No. 63 after application of a product such as BEHR PREMIUM Wood Stain & Finish Stripper No. 64. Prevent all rinse solution from entering storm drains.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC.** Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN UP:

Clean all tools and equipment with clean water. For proper disposal of empty containers and unused product, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

- Protect from freezing.
- For best results, apply at temperatures between 50°F - 90°F. Temperatures above 90°F may affect the application such as drying too fast. Avoid painting in direct sun. NOTE: If the surface is hot to the touch it should be considered too hot to apply this coating.
- Avoid heavy traffic for 24 hours.
- CAUTION: Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.
- Shelf life under normal conditions is two years unopened.

COMPLIES WITH THE BELOW AS OF 2/1/2016

SCAQMD	YES	LADCO	YES
CARB	YES	AIM	YES
OTC	YES		

GENERAL INFORMATION:



Danger! Causes severe skin burns and serious eye damage. May be corrosive to metals. Wear protective clothing, gloves, eye, and face protection. Do not breathe vapors or spray mist. Do not eat, drink, or smoke when using this product. Wash hands thoroughly after handling. Wash contaminated clothing before use. Keep only in original, corrosive resistant container and store locked up. Dispose of unused contents, container and other contaminated waste in accordance with local, state, federal and provincial regulations.

First aid: If in eyes: Rinse cautiously with water for several minutes. Remove contacts if present and easy to do. Continue rinsing and get medical attention immediately.

If on skin or hair: Immediately remove all contaminated clothing, rinse skin with water and get medical attention.

If inhaled: Leave the area if you experience difficulty breathing, headaches, or dizziness to obtain fresh air and keep at rest in a position comfortable for breathing.

If difficulty continues, get medical attention immediately.
If swallowed: Rinse mouth. Do not induce vomiting. Get medical attention immediately.