

Viagrow® Black Bucket DWC Instructions



1. Wash and rinse the ViaStone Clay Rocks and fill the 6" Net Pot Bucket lid.
2. Insert the ¼" Clear Tubing through the hole of the 6" Lid. Attach one end of the ¼" Clear Tubing to the 2" Air Stone by gently pushing the tubing over the blue plastic barb on the Air Stone nipple. Attach the other end of the ¼" Clear Tubing to the Air pump nipple. It is recommended that the Air Pump be elevated above the height of the system. If the pump is placed lower than the height of the system you must use the Check Valve to prevent water from flowing back in to the air pump. ****Please check that air moves through the valve from the Pump to the Air Stone****. Now, place the 2" Air Stone at the bottom of the 5 Gallon Bucket. *Note - Check Valve has directional arrow and needs to point away from the Pump.*
3. Fill the 5 Gallon Bucket (reservoir) with a water-nutrient solution so that the lower ½" of the 6" Net Pot Lid will be submerged in water. As the roots grow, decrease the water level to keep the root mass from being submerged completely.
4. Place the Net Pot Lid on top of the 5 Gallon Bucket and snap it on securely.
5. Plug in the Air Pump and you are ready to Grow! Refill the 5 Gallon Bucket as needed.