70 - 198**SVS**[™] Silicone Vapor Shield[™]

SPECIFICATIONS

and engineered wood floors

ITEM NO.	70-198
COVERAGE	200 sq. ft.
DIMENSIONS	33.5 in. x 72 ft.

MOISTURE SHIELD

Reduces vapor flow without trapping moisture

> LESS MESS Helps reduce dust and noise levels, clean to use

EASY FLOORING INSTALLATIONS Recommended for staple and nail down installations of solid	

	SVS™	Red Rosin Paper	Asphalt Paper
Meets perm ratings recommended by the National Wood Flooring Association		-	Some brands
Clean to use, no rub-off on walls and hands		-	-
Ok to use with radiant heat systems - No asphalt odor			-
100% Recycled		-	-

Silicone Vapor Shield is a moisture barrier underlayment made of 6 mil. wet strength paper with a backed silicone coating that will not allow moisture to penetrate through to the wood flooring planks.

Since SVS is made with silicone, the smooth surface allows installers to slide wood planks easily during installation plus it does not contain any toxic tar or tar-based ingredients found in some underlayments. Silicone Vapor Shield is made from repurposed paper that is environmentally safe and made of 100% recycled contents. The SVS is a white paper that allows a more visible chalk line and doesn't leave a black residue on hands or walls and will not fall apart during installation like red rosin, Kraft paper or wax papers do.

SVS meets the recommended perm rating guidelines as set forth by the NWFA and is suitable for use on radiant heated floors.

Quality & Excellence Since 1938.

U.S. Headquarters 866 435 8665

Canada 800 840 9422 Europe/Middle East 0031 24 6485348

Australia 011 61 3 9797 1888

www.ROBERTSCONSOLIDATED.com

New Zealand 64 9 415 9700

A0414-8876