



**RESTORE™
SOLID ACRYLIC STAIN**

DESCRIPTION AND USES

Restore™ Solid Acrylic Stain is formulated to for bare concrete and wood surfaces. It is suitable for application to decks, railings, fences, siding, trim, retaining walls and more. Use it to match the color of surfaces coated with Restore™ Deck & Concrete. Do not apply Solid Acrylic Stain to any surface that has been coated with paint, stain or water repellent except surfaces coated with Restore Deck & Concrete.

PRODUCTS

SKU	Description
47021	1-Gallon Solid Acrylic Stain Cape Cod Gray
47026	1-Gallon Solid Acrylic Stain Timberline

PRODUCT APPLICATION

SURFACE PREPARATION

Proper surface preparation is critical to performance. Surface must be clean and free of dirt, grease, mildew and organic growth to ensure product bonding and adhesion. Sand or scrape any loose paint. Smooth or glossy surfaces should be sanded or roughed-up prior to application of Solid Acrylic Stain. Clean the surface using a brush and Restore Deck & Concrete Cleaner or suitable non-bleach cleaner.

PRODUCT APPLICATION (cont.)

APPLICATION

Apply when ambient air and surface temperatures are between 50-90°F (10-32°C) and the relative humidity is less than 85%. Do not apply if temperatures are expected to drop below 40°F or if rain or snow is expected within 24 hours.

Thoroughly power mix prior to application and stir occasionally during application. Box material if using more than one container to ensure color consistency. Restore Solid Acrylic Stain is ready to use. Do not thin or mix with any other stains or paints. Brushing out a sample is recommended to ensure color satisfaction. Apply by brush, roller or spray. When applying to wood, thoroughly coat all cut ends and joints. For best results, apply in the shade.

Two coats are recommended for maximum durability.

DRY TIMES

Dries to the touch in 1 hour and can be recoated in 2 hours. Full cure can be expected in 24 hours. Longer dry time is required in cooler temperatures and at higher humidity

CLEAN-UP

When finished, wash tools and equipment with mild soap and warm water. Properly dispose of all soiled rags and protect unused product from freezing.



TECHNICAL DATA

RESTORE™ SOLID ACRYLIC STAIN

PHYSICAL PROPERTIES

		SOLID ACRYLIC STAIN
Resin Type		Water-based Acrylic
Pigment Type		A Blend of Inorganic and Organic Pigments
Solvents		Glycol Ethers, Water
Weight	Per Gallon	10.5 lbs.
	Per Liter	1.27 kg
Solids	By Weight	49%
	By Volume	35%
Volatile Organic Compounds		<45 g/l (0.37 lbs./gal.)
Recommended Dry Film Thickness (DFT) Per Coat		1.5-2.0 mils
Wet Film Thickness to Achieve DFT		4.5-6.0 mils per coat
Practical Coverage at Recommended DFT		200-400 sq.ft./gal.
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Touch	1 hour
	Recoat	2 hours
	Full Cure	24 hours
Shelf Life		3-4 years
Flash Point		>200°F (93°C)
Safety Information		For additional information, see the SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.