Inspiring Great Spaces®



AMERICAN PERSONALITY[™] LVT FLOORING GLUE DOWN FLOOR CARE INSTRUCTIONS

FINISHING THE INSTALLATION

Replace molding or wall base, allowing slight clearance between the molding and the planks. Nail the molding to the wall surface, not through the flooring. At doorways and at other areas where American Personality flooring may meet other flooring surfaces, it is preferable to use a "T" molding or similar to cover the exposed edge but not pinch the planks. Leave a small gap between the planks and the adjoining surface.

PROACTIVE PROTECTION FOR YOUR FLOOR

- When moving appliances or heavy furniture it is always wise to lay a plywood panel on your floor and "walk" the item across it. This protects your floor from scuffing and tears.
- Use floor protectors under furniture to reduce indentation. As a general rule of thumb, the heavier the item, the wider the floor protector needed.
- Place a walk-off mat at outside entrances to reduce the amount of dirt brought into your home. We strongly recommend mats without a latex or rubber backing since these backings can cause permanent discoloration.
- All Armstrong floor care products have been specifically developed to care for Armstrong floors.

Caring for Your Floor

 Sweep or vacuum regularly, to remove loose dirt which can scratch your floor.

NOTE: We do not recommend vacuums that have a beater bar since it can visibly damage your flooring surface. Additionally, we do not recommend electric brooms with hard plastic bottoms with no padding as use may result in discoloration and deglossing.

- Wipe up spills as soon as possible. Never use highly abrasive scrubbing tools on any resilient floor.
- Wash your floor regularly with a vinyl floor cleaner such as Armstrong Once 'n Done[®] Floor Cleaner.
- Do NOT use detergents, abrasive cleaners, or "mop and shine" products. These products may leave a dull film on your floor.
- Do NOT use paste wax or solvent based polishes.
- Vinyl flooring, like other types of smooth floors, can become slippery when wet. Allow time for floor to dry after washing. Immediately wipe up wet areas from spills, foreign substance, or wet feet.

Repair Procedure

• For detailed repairs, please log on to Armstrong's floorexpert.com.