



SAFETY DATA SHEET

1. Identification

Product identifier BEHR Chalk Decorative Paint – Tin White

Other means of identification

Product code 70844

Recommended use Coating

Recommended restrictions None known

Manufacturer/Importer/Supplier/Distributor information

Supplier Behr Process Corp
1801 E. St. Andrew Place
Santa Ana, CA 92705 USA

Telephone 714-545-7101

Emergency telephone number (800)424-9300 CHEMTREC®

2. Hazard(s) identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Compressed gas
Health hazards	Serious eye damage/eye irritation	Category 2
	Carcinogenicity (inhalation)	Category 2
	Reproductive toxicity (the unborn child)	Category 2
	Specific target organ toxicity, single exposure	Category 3 narcotic effects
	Specific target organ toxicity, repeated exposure	Category 2 (central nervous system)
OSHA defined hazards	Not classified	

Label elements



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes serious eye irritation. Suspected of causing cancer by inhalation. Suspected of damaging the unborn child. May cause drowsiness or dizziness. May cause damage to organs (central nervous system) through prolonged or repeated exposure.

Precautionary statement

Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.
Response	If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention.
Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise Classified (HNOC)	None known
Supplemental information	None

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Acetone	67-64-1	20 – 40
n-Butyl acetate	123-86-4	10 – 20
Propane	74-98-6	10 – 20
Calcium carbonate	1317-65-3	2.5 - 10
Isobutane	75-28-5	2.5 – 10
Isobutyl acetate	110-19-0	2.5 – 10
2-Methoxy-1-methylethyl acetate	108-65-6	2.5 – 10
Titanium dioxide	13463-67-7	2.5 - 10
Toluene	108-88-3	1 – 2.5
Aluminum hydroxide	21645-51-2	0.1 - 1
Ethylbenzene	100-41-4	0.1 - 1
Xylene	1330-20-7	0.1 - 1

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison center or doctor/physician if you feel unwell.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion	Not likely, due to the form of the product. In the unlikely event of swallowing, contact a physician or poison control center. Rinse mouth.
Most important symptoms/ effects, acute and delayed	May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Alcohol resistant foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Fire fighting equipment/ instructions	Cool containers exposed to heat with water spray and remove container, if no risk is involved.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Avoid contact with eyes. Avoid prolonged exposure. Pregnant or
--------------------------------------	--

breastfeeding women must not handle this product. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Keep away from heat, sparks and open flame. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

U.S. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Acetone (CAS 67-64-1)	PEL	2400 mg/m3 1000 ppm	
Calcium carbonate (CAS 1317-65-3)	PEL	5 mg/m3 15 mg/m3	Respirable fraction Total dust
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3 100 ppm	
Isobutyl acetate (CAS 110-19-0)	PEL	700 mg/m3 150 ppm	
n-Butyl acetate (CAS 123-86-4)	PEL	710 mg/m3 150 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3 1000 ppm	
Titanium dioxide (CAS 13463-67-7)	PEL	15 mg/m3	Total dust
Xylene (CAS 1330-20-7)	PEL	435 mg/m3 100 ppm	

U.S. OSHA Table Z-2 (29 CFR 1910.1000)

Components	Type	Value
Toluene (CAS 108-88-3)	Ceiling	300 ppm
	TWA	200 ppm

U.S. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Titanium Dioxide (CAS 13463-67-7)	TWA	5 mg/m3	Respirable fraction
		15 mg/m3	Total dust
		50 mppcf	Total dust
		15 mppcf	Respirable fraction

U.S. ACGIH Threshold Limit Values

Components	Type	Value	Form
Acetone (CAS 67-64-1)	STEL	500 ppm	
	TWA	250 ppm	
Aluminum hydroxide (CAS 21645-51-2)	TWA	1 mg/m ³	Respirable fraction
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Isobutane (CAS 75-28-5)	STEL	1000 ppm	
Isobutyl acetate (CAS 110-19-0)	TWA	150 ppm	
n-Butyl acetate (CAS 123-86-4)	STEL	150 ppm	
	TWA	50 ppm	
Titanium dioxide (CAS 13463-67-7)	TWA	10 mg/m ³	
Toluene (CAS 108-88-3)	TWA	20 ppm	
Xylene (CAS 1330-20-7)	STEL	150 ppm	
	TWA	100 ppm	

U.S. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Acetone (CAS 67-64-1)	TWA	590 mg/m ³	
		250 ppm	
Calcium carbonate (CAS 1317-65-3)	TWA	5 mg/m ³	Respirable
		10 mg/m ³	Total
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m ³	
		125 ppm	
	TWA	435 mg/m ³	
Isobutane (CAS 75-28-5)	TWA	100 ppm	
		1900 mg/m ³	
Isobutyl acetate (CAS 110-19-0)	TWA	800 ppm	
		700 mg/m ³	
n-Butyl acetate (CAS 123-86-4)	STEL	150 ppm	
		950 mg/m ³	
	TWA	200 ppm	
Propane (CAS 74-98-6)	TWA	710 mg/m ³	
		150 ppm	
	TWA	1800 mg/m ³	
Toluene (CAS 108-88-3)	STEL	1000 ppm	
		560 mg/m ³	
	TWA	150 ppm	
		375 mg/m ³	

100 ppm

U.S. Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)	TWA	50 ppm

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
Acetone (CAS 67-64-1)	25 mg/l	Acetone	Urine	*
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*
Toluene (CAS 108-88-3)	0.3 mg/g	o-Cresol, with hydrolysis	Creatinine in urine	*
	0.03 mg/l	Toluene	Urine	*
	0.02 mg/l	Toluene	Blood	*
Xylene (CAS 1330-20-7)	1.5 g/g	Methylhippuric acids	Creatinine in urine	*

* - For sampling details, please see the source document.

Exposure guidelines

US – California OELs: Skin designation

2-Methoxy-1-methylethyl acetate (CAS 108-65-6)

Can be absorbed through the skin.

Toluene (CAS 108-88-3)

Can be absorbed through the skin.

US – Minnesota HAZ Subs: Skin designation applies

Toluene (CAS 108-88-3)

Skin designation applies.

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear approved safety goggles.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If airborne concentrations are above the applicable exposure limits, use NIOSH approved respiratory protection. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and

before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state	Liquid
Form	Aerosol
Color	Not available

Odor Not available

Odor threshold Not available

pH Not available

Melting point/freezing point Not available

Initial boiling point and range 835.8°F (446.6°C) estimated

Flash point -156.0°F (-104.4°C) Propellant. Estimated

Evaporation rate Not available

Flammability (solid, gas) Not applicable

Upper/lower flammability or explosive limits

Flammability limit – lower (%) 1.8% estimated

Flammability limit – upper (%) 9.5% estimated

Vapor pressure 60 – 70 psig at 20°C estimated / 110 – 130 psig at 54°C estimated

Vapor density Not available

Relative density 0.81 estimated

Solubility(ies)

Solubility (water) Not available

Partition coefficient Not available

(n-octanol/water)

Auto-ignition temperature 843.81°F (451.01°C) estimated

Decomposition temperature Not available

Viscosity Not available

Other information

Explosive properties Not explosive

Oxidizing properties Not oxidizing

VOC 51.95% w/w estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Avoid temperatures exceeding the flash point. Contact with incompatible materials.
Incompatible materials	Strong acids. Strong oxidizing agents. Chlorine. Fluorine. Halogens. Nitrates.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause drowsiness and dizziness. Headache. Nausea, vomiting. Suspected of causing cancer by inhalation. Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Causes serious eye irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Narcosis. Headache. Nausea, vomiting. Behavioral changes. Decrease in motor functions. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling and blurred vision. Coughing. Discomfort in the chest. Shortness of breath.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
2-Methoxy-1-methylethyl acetate (CAS 108-65-6)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	>5000 mg/kg
Oral		
LD50	Rat	>8532 mg/kg
Acetone (CAS 67-64-1)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	>15700 mg/kg, 24 Hours
Inhalation		
<i>Vapor</i>		
LC50	Rat	76 mg/l, 4 Hours

Components	Species	Test Results
Oral		
LD50	Rat	5800 mg/kg
Aluminum hydroxide (CAS 21645-51-2)		
<u>Acute</u>		
Oral		
LD50	Rat	>5000 mg/kg
Ethylbenzene (CAS 100-41-4)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	15400 mg/kg
Inhalation		
LC50	Rat	17.4 mg/l, 4 Hours
Oral		
LD50	Rat	3500 - 4700 mg/kg
Isobutane (CAS 75-28-5)		
<u>Acute</u>		
Inhalation		
LC50	Mouse	52 mg/l, 1 Hours
Isobutyl acetate (CAS 110-19-0)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	>5000 mg/kg
Oral		
LD50	Rat	13400 mg/kg
n-Butyl acetate (CAS 123-86-4)		
<u>Acute</u>		
Inhalation		
LC50	Rat	2000 ppm, 4 Hours

Components	Species	Test Results
Oral		
LD50	Rat	10768 mg/kg
Propane (CAS 74-98-6)		
<u>Acute</u>		
Inhalation		
Gas		
LC50	Rat	>80000 ppm, 15 minutes
Titanium dioxide (CAS 13463-67-7)		
<u>Acute</u>		
Inhalation		
LC50	Rat	3.43 mg/l, 4 Hours
Oral		
LD50	Rat	>5000 mg/kg
Toluene (CAS 108-88-3)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	12200 mg/kg
Inhalation		
Vapor		
LC50	Rat	28.1 mg/l, 4 Hours
Xylene (CAS 1330-20-7)		
<u>Acute</u>		
Oral		
LD50	Rat	3523 mg/kg

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylbenzene (CAS 100-41-4)	2B Possibly carcinogenic to humans.
Titanium dioxide (CAS 13463-67-7)	2B Possibly carcinogenic to humans.
Toluene (CAS 108-88-3)	3 Not classifiable as to carcinogenicity to humans.
Xylene (CAS 1330-20-7)	3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens

Not listed

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not regulated.

Reproductive toxicity Possible reproductive hazard. Components in this product have been shown to cause birth defects and reproductive disorders in laboratory animals. Suspected of damaging the unborn child.

Specific target organ toxicity - single exposure May cause drowsiness and dizziness.

Specific target organ toxicity - repeated exposure May cause damage to organs (central nervous system) through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life.

Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Mobility in soil No data available.

Other adverse effects The product contains volatile organic compounds which have a photochemical ozone creation potential.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues/unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers

14. Transport information

DOT

UN number UN1950

UN proper shipping Aerosols, flammable

name

Transport hazard class(es)

Class 2.1

Subsidiary risk -

Label(s) 2.1

Packing group -

Environmental hazards

Marine pollutant No

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Special provisions N82

Packaging exceptions 306

Packaging non bulk None

Packaging bulk None

IATA

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1

Subsidiary risk -

Packing group -

Environmental hazards No

ERG Code 10L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

Class 2.1

Subsidiary risk -

Packing group -

Environmental hazards

Marine pollutant No

EmS F-D, S-U

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
All components are listed on or exempt from the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)
Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Acetone (CAS 67-64-1)	Listed.
Ethylbenzene (CAS 100-41-4)	Listed.
Isobutane (CAS 75-28-5)	Listed.
Isobutyl acetate (CAS 110-19-0)	Listed.
n-Butyl acetate (CAS 123-86-4)	Listed.
Propane (CAS 74-98-6)	Listed.
Toluene (CAS 108-88-3)	Listed.
Xylene (CAS 1330-20-7)	Listed.

SARA 304 Emergency release notification
Not regulated.

OSHA Specifically Regulated Substances (296 CFR 1910.1001-1053)
Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance
Not listed.

SARA 311-312 Hazardous chemical Yes

Classified hazard categories Flammable (gases, aerosols, liquids, or solids)
Gas under pressure
Serious eye damage or eye irritation
Carcinogenicity
Reproductive toxicity
Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Ethylbenzene	100-41-4	0.1 - 1
Toluene	108-88-3	1 – 2.5

Other federal regulations**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Ethylbenzene (CAS 100-41-4)
 Toluene (CAS 108-88-3)
 Xylene (CAS 1330-20-7)

Clean Air Act (CAA Section 112®) Accidental Release Prevention (40 CFR 68.130)

Isobutane (CAS 75-28-5)
 Propane (CAS 74-98-6)

Safe Drinking Water Act (SDWA) Not regulated.

Drug Enforcement Administration (DEA). List 2 Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Acetone (CAS 67-64-1)	6532
Toluene (CAS 108-88-3)	6594

Drug Enforcement Administration (DEA). List1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12©)

Acetone (CAS 67-64-1)	35 %WV
Toluene (CAS 108-88-3)	35 %WV

DEA Exempt Chemical Mixtures Code Number

Acetone (CAS 67-64-1)	6532
Toluene (CAS 108-88-3)	6594

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

Acetone (CAS 67-64-1)	Low priority
Isobutyl acetate (CAS 110-19-0)	Low priority
n/Butyl acetate (CAS 123-86-4)	Low priority

U.S. state regulations**U.S. Massachusetts RTK – Substance List**

Acetone (CAS 67-64-1)
 Calcium carbonate (CAS 1317-65-3)
 Ethylbenzene (CAS 100-41-4)
 Isobutane (CAS 75-28-5)
 Isobutyl acetate (CAS 110-19-0)
 n-Butyl acetate (CAS 123-86-4)
 Propane (CAS 74-98-6)
 Titanium dioxide (CAS 13463-67-7)
 Toluene (CAS 108-88-3)
 Xylene (CAS 1330-20-7)

U.S. New Jersey Worker and Community Right-to-Know Act

Acetone (CAS 67-64-1)
 Calcium carbonate (CAS 1317-65-3)
 Ethylbenzene (CAS 100-41-4)
 Isobutane (CAS 75-28-5)
 Isobutyl acetate (CAS 110-19-0)
 n-Butyl acetate (CAS 123-86-4)
 Propane (CAS 74-98-6)
 Titanium dioxide (CAS 13463-67-7)
 Toluene (CAS 108-88-3)
 Xylene (CAS 1330-20-7)

U.S. Pennsylvania Worker and Community Right-to-Know Law

Acetone (CAS 67-64-1)
Calcium carbonate (CAS 1317-65-3)
Ethylbenzene (CAS 100-41-4)
Isobutane (CAS 75-28-5)
Isobutyl acetate (CAS 110-19-0)
n-Butyl acetate (CAS 123-86-4)
Propane (CAS 74-98-6)
Titanium dioxide (CAS 13463-67-7)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

U.S. Rhode Island RTK

Acetone (CAS 67-64-1)
Calcium carbonate (CAS 1317-65-3)
Ethylbenzene (CAS 100-41-4)
Isobutyl acetate (CAS 110-19-0)
n-Butyl acetate (CAS 123-86-4)
Propane (CAS 74-98-6)
Titanium dioxide (CAS 13463-67-7)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

U.S. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22,69502.3, subd. (a))

Acetone (CAS 67-64-1)
Ethylbenzene (CAS 100-41-4)
Isobutane (CAS 75-28-5)
Titanium dioxide (CAS 13463-67-7)
Toluene (CAS 108-88-3)
Xylene (CAS 1330-20-7)

16. Other information, including date of preparation or last revision

Issue date Draft version.

Revision date Draft version.

Version # Draft version.

HMSI® ratings Health: 2*
Flammability: 4
Physical hazard: 3

Disclaimer Behr Process Corp cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.