



BEHR PREMIUM Extra Textured DECKOVER®

No. 5015 Deep Base

- Conceals Splinters & Cracks up to 1/4"
- Creates a Heavily Textured, Slip-Resistant Finish
- Covers up to 75 Sq. Ft. in 2 Coats
- Resists Cracking & Peeling
- Durable, Mildew Resistant Finish
- Solid Color Coating
- Revives Wood & Composite Decks, Railings, Porches & Boat Docks
- Great for Concrete Pool Decks, Patios & Sidewalks
- 100% Acrylic



Must Prep Before Use



2 Coats Required



Horizontal Spread Rate:
1st Coat 75 Sq. Ft.
2nd Coat 75 Sq. Ft.



Soap & Water Clean-Up

WHERE TO USE

Recommended for properly prepared exterior weathered or cracked horizontal and vertical wood and composite surfaces such as Decks, Railings, Porches and Boat Docks. Also great for concrete surfaces such as Pool Decks, Patios and Sidewalks. **Do not use on drivable surfaces such as garage floors and driveways.**

PREPARATION

(Proper surface preparation is required.) All surfaces must be clean, sound, dry and free of any dirt, oil, and grease before application.

Wood Surfaces: Replace rotting or unstable boards and remove loose splinters. Remove mildew stains, dirt, oil and grease with a product such as BEHR PREMIUM® No. 63 All-In-One Wood Cleaner prior to application. Use a product such as BEHR PREMIUM No. 64 Wood Stain & Finish Stripper (must be followed by No. 63) to remove all loose wood fibers, peeling paint/stain or deteriorated coatings prior to application of Extra Textured DECKOVER coating. On new wood, use No. 63 to remove mill glaze and open the pores of the wood. Rinse thoroughly and allow to dry before coating. **Concrete Surfaces:** Avoid areas that are structurally weak or subject to hydrostatic pressure above 8 psi. Allow new surfaces to cure for 30 days. Use a product such as BEHR PREMIUM No. 992 Concrete & Masonry Paint Stripper to strip peeling coating. Use a product such as BEHR PREMIUM No. 991 Concrete & Masonry Cleaner & Etcher to clean and etch uncoated concrete or No. 990 Concrete & Masonry Degreaser & Cleaner on sound, coated surfaces prior to coating.

APPLICATION

Use product when air and surface temperatures are between 50-90° F (10-32° C). During application, avoid exposure of container to direct sunlight. Do not use if rain is expected within 24 hours. Avoid painting if humidity is expected to be greater than 80%. Intermit multiple containers to ensure color uniformity. Stir product occasionally throughout application. May thin with up to 8 oz. of clean water per gallon. **For nail holes and cracks up to 1/4", completely fill in with Extra Textured DECKOVER coating using**

a nylon/polyester brush and allow to dry prior to rolling. Deep nail holes and cracks may require additional filling. For edges, corners and in between wood boards, apply using a nylon/polyester brush. Use pressure while rolling and apply a generous, even coat using the DECKOVER Extra Textured Roller Cover. For vertical surfaces such as railings, use a nylon/polyester brush or roller and apply two thin coats at a spread rate of 400 sq. ft. per gallon. Do not use with airless sprayer. For optimum performance, film uniformity, leveling and to cover cracks, **a second coat MUST be applied.** Maintain a wet edge when applying.

DRY TIME

4-6 hours before recoat. Dries to touch in 4 hours. Wait 24-48 hours before light foot traffic. 72 hours to full cure. Additional dry time may be needed in cooler temperatures and higher humidity. Premature heavy traffic will cause coating failure.

DISPOSAL

For disposal of empty containers and unused product contact your household refuse collection service.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARNING! Sanding or scraping pressure treated lumber may be hazardous; wear appropriate protection.

A quality product that contains a mildewcide will assist in providing a finish that is resistant to mildew, provided that all existing mildew is removed prior to application. While this product does contain a mildewcide, it will not prevent mildew growth.

LIMITED WARRANTY

Behr Process Corporation warrants that this product meets Behr's manufacturing specifications. If this product is found not to meet our manufacturing specifications upon inspection by our representative, Behr Process Corporation will, at its option and upon presentation of proof-of-purchase (the original receipt), either furnish an equivalent amount of new product or refund the original purchase price of this product to you. **This warranty excludes (1) labor and costs of labor for the application or removal of any product, and (2) any incidental or consequential damages, whether based on breach of express or implied warranty, negligence, strict liability or any other legal theory.** Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights, which vary from state to state.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2017 Behr Process Corporation
Santa Ana, CA 92704 U.S.A. • behr.com
V.O.C. <50 g/L • REV. 01/17

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15-20 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.