

Safety Data Sheet

29 CFR 1910.1200

Effective Date : 26/05-2015

Trade Name : Alkaline Manganese Dry Battery

1 Identification

• Product identifier

• Trade name : Alkaline Manganese Dry Battery

• Item No.:

AM1/LR20、AM2/LR14、AM3/LR6、AM4/LR03、LR50、LR61、AM9VF

• Recommended use of the chemical and restrictions on use :

• Application of the substance / the preparation : Electronic products

• Details of the supplier of the safety data sheet

• Manufacturer/Supplier :

CHUNG PAK BATTERY WORKS LIMITED

CHUNG PAK (GUANG DONG) BATTERY INDUSTRIAL CO., LTD

• Full address :

7/F., CHUNG PAK COMMERCIAL BUILDING, 2 CHO YUEN STREET, YAU TONG BAY, KOWLOON, HONGKONG

GANCUN SECTION FOCHEN ROAD CHEN CUN COUNTY SHUNDE DISTRICT

FOSHAN CITY GUANGDONG PROVINCE CHINA

Phone number :

852-27171338

Fax : 852 2772 7727

• Email : dylan.cai@chungpak.com

• Other US contact point : No available

• Further information obtainable from :

CHUNG PAK BATTERY WORKS LIMITED

CHUNG PAK (GUANG DONG) BATTERY INDUSTRIAL CO., LTD

• Emergency telephone number :

USA Poison Center Tel: +1 800 222 1222

+86-757-23312338 Dylan

• Remark :

*This sample is likely to be classified as article and is out of scope of a SDS as set out in 29 CFR Part 1910.1200. This SDS is generated for client's reference only.

2 Hazard(s) identification

• Classification of the substance or mixture

Classification according to OSHA Hazard Communication Standard (29 CFR 1910.1200)



GHS05 Corrosion

Skin Corr. 1A

H314 Causes severe skin burns and eye damage.

Eye Dam. 1

H318 Causes serious eye damage.



GHS07

Acute Tox. 4

H302 Harmful if swallowed.

Acute Tox. 4

H332 Harmful if inhaled.

• Information concerning particular hazards for human and environment :

The product has to be labeled due to the calculation procedure of OSHA Hazard Communication Standard (29 CFR 1910.1200).

• Classification system :

The classification is according to the latest edition of OSHA Hazard Communication Standard (29 CFR 1910.1200), and extended by company and literature data.

(Contd. on page 2)

Safety Data Sheet

29 CFR 1910.1200

Effective Date : 26/05-2015

Trade Name : Alkaline Manganese Dry Battery

(Contd. on page 1)

- Label elements
- Labeling according to OSHA Hazard Communication Standard (29 CFR 1910.1200)
- Hazard pictograms



GHS05 GHS07

- Signal word : Danger
- Hazard-determining components of labeling :

manganese dioxide
potassium hydroxide

- Hazard statements

H302+H332 Harmful if swallowed or if inhaled.
H314 Causes severe skin burns and eye damage.

- Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read label before use.
P260 Do not breathe dusts or mists.
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310 Immediately call a poison center/doctor.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local / regional / national / international regulations.

- Hazards not otherwise classified (HNOC) No further relevant information available.

3 Composition / information on ingredients

- Chemical characterization: Mixtures

- Description:

Mixture of the substances listed below with nonhazardous additions.
For the wording of listed risk phrases refer to section 16.

• Composition:		
1313-13-9	manganese dioxide Acute Tox.4, H302; Acute Tox. 4, H332	42.0-45.0%
7439-89-6	iron	15.0-20.0%
7440-66-6	zinc	15.0-18.0%
7732-18-5	water	7.0-9.0%
1310-58-3	potassium hydroxide Skin Corr. 1A, H314; Acute Tox. 4, H302	6.0-7.0%
7440-50-8	copper	1.0-3.5%
7782-42-5	Graphite	2.0-3.0%
32131-17-2	Nylon-66	0.6-1.5%
25038-59-9	Polyethylene terephthalate	1.0-1.5%
9004-34-6	Cellulose	0.5-1.0%

(Contd. on page 3)

Safety Data Sheet

29 CFR 1910.1200

Effective Date : 26/05-2015

Trade Name : Alkaline Manganese Dry Battery

(Contd. on page 2)

• Remark :

zinc (CAS: 7440-66-6)

Note: Zn

manganese dioxide (CAS: 1313-13-9)

Note: MnO₂

potassium hydroxide (CAS: 1310-58-3)

Note: KOH

Graphite (CAS: 7782-42-5)

Note: Carbon(C)

copper(CAS: 7440-50-8)

Note: Cu

Nylon-66 (CAS: 32131-17-2)

Note: C36H66N6O6X2

iron (CAS: 7439-89-6)

Note: Fe

water (CAS: 7732-18-5)

Note: H₂O

Cellulose (CAS: 9004-34-6)

Note: Paper

Polyethylene terephthalate (CAS: 25038-59-9)

Note: PET((C10H8O4)n)

4 First-aid measures

• Description of first aid measures

• General description:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly. Then consult a doctor.

• After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

• After swallowing:

Do not induce vomiting; immediately call for medical help.

Drink copious amounts of water and provide fresh air. Immediately call a doctor.

• Most important symptoms and effects, both acute and delayed No further relevant information available.

• Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

• Suitable extinguishing agents:

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• Special hazards arising from the substance or mixture: No further relevant information available.

• Special protective equipment and precautions for firefighters

• Protective equipment: Mouth respiratory protective device.

(Contd. on page 4)

Safety Data Sheet

29 CFR 1910.1200

Effective Date : 26/05-2015

Trade Name : Alkaline Manganese Dry Battery

(Contd. on page 3)

6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures:

Wear protective equipment. Keep unprotected persons away.

• Environmental precautions: Do not allow to enter sewers/surface or ground water.

• Methods and material for containment and cleaning up:

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

7 Handling and storage

• Precautions for safe handling:

Thorough dedusting.

Ensure good ventilation/exhaustion at the workplace.

• Information about protection against explosions and fires: No special measures required.

• Storage:

• Conditions for safe storage, including any incompatibilities

• Requirements to be met by storerooms and receptacles: No special requirements.

• Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Keep receptacle tightly sealed.

• Specific end use(s): No further relevant information available.

8 Exposure controls / personal protection

• Components with limit values that require monitoring at the workplace:

1313-13-9 manganese dioxide (42.0-45.0%)

PEL (USA)	Ceiling limit value: 5mg/m ³ as Mn
REL (USA)	Short-term value: 3mg/m ³ Long-term value: 1mg/m ³ as Mn
TLV (USA)	Long-term value: 0.02*0.1* mg/m ³ as Mn; * respirable **inhalable fraction

1310-58-3 potassium hydroxide (6.0-7.0%)

REL (USA)	Ceiling limit value: 2mg/m ³
TLV(USA)	Ceiling limit value: 2mg/m ³

7440-50-8 copper (1.0-3.5%)

PEL (USA)	Long-term value: 1*0.1**mg/m ³ as Cu *dusts and mists **fume
REL (USA)	Long-term value: 1*0.1**mg/m ³ as Cu *dusts and mists **fume
TLV(USA)	Long-term value: 1*0.2**mg/m ³ *dusts and mists **fume; as Cu

7782-42-5 Graphite (2.0-3.0%)

PEL (USA)	Long-term value: 15mppcf*mg/m ³
-----------	--

(Contd. on page 5)

Safety Data Sheet

29 CFR 1910.1200

Effective Date : 26/05-2015

Trade Name : Alkaline Manganese Dry Battery

(Contd. on page 4)

	*impinge samples counted by light field techn.
REL (USA)	Long-term value: 2.5mg/m ³ *respirable dust
TLV(USA)	Long-term value:2*mg/m ³ all forms except graphite fibers; *resp. fraction
9004-34-6 Cellulose (0.5-1.0%)	
PEL (USA)	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV(USA)	Long-term value: 10mg/m ³

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Based on the composition shown in Section 3, the following measures are suggested for occupational safety measure.**
- **Appropriate engineering controls:**
 - Wash clothing and shoes before reuse.
 - Keep away from foodstuffs, beverages and feed.
 - Immediately remove all soiled and contaminated clothing.
 - Wash hands before breaks and at the end of work.
 - Avoid contact with the eyes and skin.
 - See Section 7 for information about design of technical facilities.

- **Personal protective equipment:**

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands :**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material:**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

(Contd. on page 6)

Safety Data Sheet

29 CFR 1910.1200

Effective Date : 26/05-2015

Trade Name : Alkaline Manganese Dry Battery

(Contd. on page 5)

9 Physical and chemical properties

. General Information	
. Appearance:	
Form:	Cylindrical
Color:	Blue, silvery
. Odor:	Odorless
. Odour threshold:	Not available
. pH-value:	Not available
. Change in condition	
Melting point/ Melting range:	Not available
Freezing point:	Not available
Boiling point/ Boiling range:	Not available
. Flash point:	Not available
. Flammability (solid, gaseous):	Not available
. Auto-Ignition temperature:	Not available
. Decomposition temperature:	Not available
. Explosion limits:	
Lower:	Not available
Upper:	Not available
. Vapor pressure:	Not available
. Density:	Not available
. Relative density:	Not available
. Vapour density:	Not available
. Evaporation rate:	Not available
. Solubility in/ Miscibility with	
Water:	Not available
. Partition coefficient (n-octanol/water)	Not available
. Viscosity:	
Dynamic:	Not available
Kinematic:	Not available
. Other information	Voltage 1.5V

10 Stability and reactivity

- . Reactivity:** Data not available
- . Chemical stability:** Stable under normal operating and storage conditions.
- . Possibility of hazardous reactions:** No dangerous reactions known.
- . Conditions to avoid:** No further relevant information available.
- . Incompatible materials:** No further relevant information available.
- . Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

. Acute toxicity:

. LD/LC50 values that are relevant for classification:		
1310-58-3 potassium hydroxide		
Oral	LD50	273 mg/kg (rat)

(Contd. on page 7)

Safety Data Sheet

29 CFR 1910.1200

Effective Date : 26/05-2015

Trade Name : Alkaline Manganese Dry Battery

(Contd. on page 6)

7439-89-6 iron

Oral	LD50	30000 mg/kg (rat)
------	------	-------------------

9004-34-6 Cellulose

Oral	LD50	>5000 mg/kg (rat)
------	------	-------------------

• Primary irritant effect:

• **on the skin:** Strong caustic effect on skin and mucous membranes.

• **on the eye:** Strong caustic effect.

• **Sensitization:** No sensitizing effects known.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

• Carcinogenic categories

• IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

• NTP (National Toxicology Program)

None of the ingredients is listed.

• OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

• Toxicity

• **Aquatic toxicity:** No further relevant information available.

• **Persistence and degradability:** No further relevant information available.

• **Bioaccumulative potential:** No further relevant information available.

• **Mobility in soil:** No further relevant information available.

• **Other adverse effects:** No further relevant information available.

13 Disposal considerations

• Waste treatment methods

• Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

• Uncleaned packagings:

• **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

• Alkaline Manganese Dry Battery is exempt from dangerous goods. It is considered non-dangerous goods by the international Civil Aviation Organization (ICAO), the International Air Transport Association (IATA), International Maritime Dangerous Goods regulations (IMDG), the «Recommendations on the Transport of Dangerous Goods Model Regulations» and also is not classified as dangerous goods under the 56th Edition of the IATA Dangerous Goods Regulation 2015 Special Provision A123.

(Contd. on page 8)

Safety Data Sheet

29 CFR 1910.1200

Effective Date : 26/05-2015

Trade Name : Alkaline Manganese Dry Battery

(Contd. on page 7)

Separate batteries when shipping to prevent short-circuiting. They should be packed in strong packaging for support during transport.

Transport Fashion: By air, by sea, by road.

15 Regulatory information

. Safety, health and environmental regulations/legislation specific for the substance or mixture

. Sara

. Section 335 (extremely hazardous substances):

None of the ingredients is listed.

. Section 313 (specific toxic chemical listings):

1313-13-9	manganese dioxide
-----------	-------------------

7440-50-8	copper
-----------	--------

. TSCA (Toxic Substances Control Act):

1313-13-9	manganese dioxide
-----------	-------------------

7439-89-6	iron
-----------	------

7732-18-5	water
-----------	-------

1310-58-3	potassium hydroxide
-----------	---------------------

7440-50-8	copper
-----------	--------

7782-42-5	Graphite
-----------	----------

32131-17-2	Nylon-66
------------	----------

25038-59-9	Polyethylene terephthalate
------------	----------------------------

9004-34-6	Cellulose
-----------	-----------

. Proposition 65

. Chemical known to cause cancer:

None of the ingredients is listed.

. Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

. Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

. Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

. Carcinogenicity categories

. EPA (Environmental Protection Agency)

1313-13-9	manganese dioxide	D
-----------	-------------------	---

7440-66-6	zinc	II
-----------	------	----

7440-50-8	copper	D
-----------	--------	---

. TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

. NIOSH-Ca (National Institution for Occupational Safety & Health)

None of the ingredients is listed.

(Contd. on page 9)

Safety Data Sheet

29 CFR 1910.1200

Effective Date : 26/05-2015

Trade Name : Alkaline Manganese Dry Battery

(Contd. on page 8)

16 Other information

NFPA ratings (scale 0-4)



Health = 3
Fire = 0
Reactivity = 0

• HMIS ratings (scale 0-4)



Health = 4
Fire = 0
Reactivity = 0

• Relevant phrases

- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H332 Harmful if inhaled.

The contents and format of this SDS are in accordance with 29 CFR 1910.1200 (g)

DISCLAIMER OF LIABILITY

The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in anyway connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable.

Remark:

*This sample is likely to be classified as article and is out of scope of a SDS as set out in 29 CFR Part 1910.1200. This SDS is generated for client's reference only.

Date of preparation/last revision 2015.05.26/-

Abbreviations and acronyms:

- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Acute Tox. 4: Acute toxicity, Hazard Category 4
- Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A
- Eye Dam . 1: Serious eye damage/eye irritation, Hazard Category 1

End of document