



0336 Rust Stopper Rusty Metal Spray Primer

- Fast Dry
- Corrosion Protection
- Ideal to Treat Rust Spots on Metal Roofs

Suggested Uses:

- Rusted metal Refinish machinery
- Restore equipment Protect metal structures

APPLICATION

1. Surface must be clean, dry and free of rust before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50 °F and 90 °F (10 °C and 32 °C.).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Spray surface with steady even strokes at a distance of 8 to 10 inches (20 to 25cm). Several light coats give a better finish than one heavy coat.
4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. Do not stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
5. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

PRECAUTIONS: For exterior use only. Do not use in drinking water or food systems. Product will dry to touch in 10 minutes. Full cure or before recoating may take up to 4 hours. For longest life, store in controlled environment, 50 °F to 85 °F.

STORAGE: Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50 °C / 122 °F.

DISPOSAL: Dispose of product in accordance with local/regional/national/international regulations.

ADDITIONAL PRECAUTION STATEMENTS: Vapors may ignite explosively and cause a flash fire. Prevent buildup of vapors by opening windows and doors to achieve cross ventilation. Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately inhaling the contents may be harmful or fatal. In cases where short and/or long term overexposure conditions exist, a charcoal filter respirator should be worn. Follow respirator manufacturer's directions for use.

Properties:

Coverage	Up to 18 square feet
Cleanup	Paint or lacquer thinner
Flammability	Extremely Flammable
Flash point	-4 °F
Specific Gravity	0.81
Solids Content	24%
MIR value	0.69, cannot exceed 0.70
HAPs content	11%
Storage Temperature	40-100 °F
Application Temperature	50-90 °F
Heat Resistance	250 °F
Resin System	Phenolic
Shelf life	Guaranteed for 2 years
Food contact rating	No

Dry Time*:

To touch	10 minutes
To recoat	1 - 4 hours

*At 72 °F, 50% humidity, 1.5 mil thickness. Curing/Recoat time is extended with multiple coats and excessively thick coats.

Gloss**: Flat, <15

**As measured on a 60 degree gloss meter.

AVAILABLE SIZES

PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
0336-GA	20 fl. oz.	2.69" x 2.69" x 9.38"	17 oz.	1.4 lbs.	6/crtn	025056033604

www.gardner-gibson.com

Gardner-Gibson • P.O. Box 5449 • Tampa, Florida 33675-5449

Phone: (813) 248-2101