



# SAFETY DATA SHEET

Name of Material Crack-Stix	
1	HEALTH
1	FLAMMABILITY
0	REACTIVITY
X	PROTECTIVE EQUIPMENT

## Section I – PRODUCT AND COMPANY IDENTIFICATION

**Product Name:** Latexite® Crack-Stix Crack & Joint Filler

**Manufacturer Name:** Dalton Enterprises, Inc.

Product	Package Size	Item #	UPC
Small (1/4" Diameter)	Pli-Stix Clamshell (60 ft.)	36099	0 90932 36099 0
	2 Gallon Pail (250 ft.)	2060	0 90932 02060 3
	Full Spool (1000 ft.)	20600	0 90932 20600 7
Medium (1/2" Diameter)	Pli-Stix Clamshell (30 ft.)	35099	0 90932 35099 1
	2 Gallon Pail (125 ft.)	2050	0 90932 50150 8
	Full Spool (500 ft.)	20500	0 90932 20500 0

**Address:** 131 Willow Street Cheshire, CT 06410

**Telephone Number:** (203) 272-3221

**24 Hour Emergency Number:** (203) 272-3221

**U.S. And Canada:** (203) 272-3221

**Recommended Use and Restrictions:** Joint sealant/Crack filler

## Section II – HAZARDS IDENTIFICATION

### Classification

Carcinogenicity	1A
-----------------	----

### Label Elements



### GHS Pictogram:

**Signal Word:** DANGER

**Hazard Statements:** May cause cancer

### Precautionary Statements – Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Do not eat, drink or smoke when using this product

Use only outdoors in a well-ventilated area

**Precautionary Statements - Storage**

Store locked up

**Precautionary Statements - Disposal**

Dispose of contents/container in accordance with local regulations.

**Hazards not otherwise classified (HNOC)**

Not applicable

**Unknown Toxicity**

0% of the mixture consists of ingredient(s) of unknown toxicity

**Other information**

Contact with heated product will result in burns.

**Interactions with Other Chemicals**

No information available.

**Section III - COMPOSITION**

<u>CAS#</u>	<u>Component</u>	<u>% Composition</u>
8052-42-4	Asphalt Cement	30 – 95
64742-04-7	Extracts, petroleum, heavy paraffinic distillate solvent	0.1 – 20

**Section IV - FIRST-AID MEASURES**

**Emergency and First Aid Procedures**

**General Advice:** Present this safety data sheet to the physician in attendance.

**Eye Contact:** Flush thoroughly with water. If irritation persists, see a physician.

**Skin Contact:** Clean exposed area thoroughly with soap and water. If irritation persists, see a physician.

**Ingestion:** If swallowed do NOT induce vomiting. Seek medical attention if symptoms develop.

**Inhalation:** Move to fresh air if symptoms develop. If irritation persists, see a physician.

**Most Important Symptoms:** Heated product causes burns, vapors may cause respiratory irritation.

**Indication of Immediate Medical Attention and Special Treatment Needed:** Treat Symptomatically

**Section V - FIRE-FIGHTING MEASURES**

**Suitable Extinguishing Media:** Water Spray, CO2, dry chemical, foam, sand.

**Unsuitable Extinguishing Media:** Do not use heavy water stream

**Specific Hazards arising from the Chemical:** Combustion may yield toxic fumes, smoke, carbon monoxide and carbon dioxide.

**Special Protective Equipment and Precautions for Firefighters:** Wear full protective clothing, including self-contained breathing apparatus (Positive Pressure/Pressure Demand), helmet, and face mask.

**Section VI - ACCIDENTAL RELEASE MEASURES**

**Personal Precautions, Protective Equipment and Emergency Procedures:** Avoid skin and eye contact, use proper protective equipment recommended in section 8.

**Methods and Materials for Containment and Cleanup:** Contain spill and dike with inert material (sand, sawdust, dirt, etc.). Allow hot material to cool and place in closed container for proper disposal. Avoid runoff to waterways and sewers. Dispose of in accordance with local regulations.

## Section VII - HANDLING AND STORAGE

**Precautions for Safe Handling:** Store in a dry area, avoid eye contact and wash thoroughly after handling  
**Conditions for Safe Storage, Including Incompatibilities:** Keep container closed and upright to prevent leakage. Store in a cool, dry, ventilated area. Avoid heat sources and strong oxidizers.

## Section VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

### Exposure Guidelines

<u>Component</u>	<u>ACGIH TWA (mg/m<sup>3</sup>)</u>	<u>OSHA PEL (TWA) (mg/m<sup>3</sup>)</u>	<u>NIOSH (STEL)/(TWA)</u>
Petroleum Asphalt	0.5 mg/m <sup>3</sup>	N/A	N/A
Extracts, Petroleum, Heavy Paraffinic Solvent	5 mg/m <sup>3</sup> (Inhalable Fraction)	5 mg/m <sup>3</sup> (Mist)	STEL 10 mg/m <sup>3</sup> (mist) TWA 5 mg/m <sup>3</sup> (mist)

**Engineering Controls:** Use outdoors only. Ensure adequate ventilation.

### Individual Protection Measures

**Eyes/Face:** Safety goggles

**Skin:** Gloves, long sleeves, protective clothing and footwear

**Respiratory:** None required if good ventilation is maintained.

**Hygienic controls:** Wash thoroughly with soap and water before eating or drinking. Wash contaminated clothing.

## Section IX - PHYSICAL AND CHEMICAL PROPERTIES

**Appearance:** Black Solid

**Physical State:** Solid below softening point

**Odor:** Asphaltic odor

**Odor Threshold:** N/A

**pH:** N/A

**Melting Point:** 150-250° F/65.5-121.1°C

**Boiling Point:** >600° F/315.6°C

**Flash Point:** > 400 °F/204.4 °C

**Evaporation Rate:** N/A

**Upper Explosive Limit:** N/A

**Lower Explosive Limit:** N/A

**Vapor Pressure:** N/A

**Vapor Density:** N/A

**Specific Gravity:** 1.05-1.9

**Solubility In Water:** Negligible

**Partition Coefficient (n-octanol/water):** N/A

**Auto Ignition Temperature:** >700° F/371.1°C

**Decomposition Temperature:** N/A

**Flammability:** N/A

**Max Voc:** 0 g/L

**Section X – STABILITY AND REACTIVITY**

**Reactivity:** None known under normal conditions

**Stability:** Stable

**Hazardous Reactions:** None known under normal conditions

**Conditions to avoid:** Keep from freezing and extreme heat

**Incompatibility:** Strong oxidizers

**Hazardous Decomposition Products:** Combustion may yield fumes, smoke, carbon monoxide and carbon dioxide.

**Section XI – TOXICOLOGICAL INFORMATION**

**Health Effects**

**Likely Routes of Exposure:** Skin/eye contact, Inhalation

**Eye Contact:** Heated product causes burns

**Skin Contact:** Heated product causes burns

**Ingestion:** Minor irritation may result

**Inhalation:** Vapors may cause respiratory irritation

**Toxicological Effects**

<u>Component</u>	<u>CAS #</u>	<u>Acute oral toxicity LD50</u>	<u>Acute dermal toxicity LD50</u>	<u>Acute Inhalation Toxicity LD50</u>
Asphalt Cement	8052-42-4	5,001 mg/kg (rat)	2,001 mg/kg (rat)	-

**Delayed and immediate effects as well as chronic effects from short and long-term exposure**

**Sensitization:** Product not known to cause sensitization

**Mutagenic Effects:** None known

**Carcinogenicity:** May cause cancer

<u>Component</u>	<u>CAS #</u>	<u>IARC</u>	<u>NTP</u>	<u>OSHA</u>
Asphalt Cement	8052-42-4	2B	Suspected	-

**Reproductive Toxicity:** No toxicity known

**STOT – Single Exposure:** None Known

**STOT – Repeated Exposure:** None Known

**Chronic Toxicity:** No Known Effect

**Target Organ Effects:** Eyes, Skin.

**Aspiration Hazard:** Based on available data, the classification criteria are not met.

### Numerical Measures of Toxicity

No data available

## Section XII – ECOLOGICAL INFORMATION

**Ecological Fate:** No data available  
**Persistence/Degradability:** No data available  
**Bioaccumulation Potential:** No data available  
**Mobility in Soil:** No data available  
**Other Adverse Effects:** No data available

Analysis for ecological effects has not been conducted.

## Section XIII – DISPOSAL CONSIDERATIONS

**Waste Disposal Information:** Dispose of in accordance with federal, state, and local regulations.

## Section XIV – TRANSPORT INFORMATION

**DOT – U.S. Department of Transportation**  
**Proper Shipping Name:** Not regulated

**IATA – International Air Transport Association**  
**Proper Shipping Name:** Not regulated

**IMDG – International Maritime Dangerous Goods**  
**Proper Shipping Name:** Not regulated

## Section XV – REGULATORY INFORMATION

### International Inventories

**TSCA:** Complies  
**DSL/NDSL:** Complies

### US Federal Regulations

**SARA 313:** This product contains no chemicals subject to Annual Release Reporting Requirements under SARA Title III, Section 313 (40 CFR 372)

**SARA Hazard Category (311/312):** Non Hazardous

**CWA (Clean Water Act):** This product contains no chemicals regulated by the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

**CERCLA:** This product contains no substances regulated by the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

### US State Regulations

Component Name	CAS	State Right to Know		
		MA	NJ	PA
Asphalt Cement	8052-42-4	yes	yes	yes

### California Proposition 65

WARNING: This product can expose you to chemicals including Asphalt, which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### International Regulations

WHMIS: Non Hazardous

## Section XVI – OTHER INFORMATION

### Other precautions:

- Keep out of reach of children.
- Always read label plus precautions and follow directions carefully.
- Do not breathe vapor or spray mist.
- Use only with adequate ventilation.
- Do not take internally.
- Avoid contact with eyes and skin.
- Wash thoroughly after using.

**NFPA Rating:** Health 1; Fire 1; Reactivity 0

**Revision Date:** 01/22/18

### Disclaimer/Statement of Liability:

THE INFORMATION AND RECOMMENDATIONS PROVIDED HEREIN ARE BELIEVED TO BE ACCURATE AS OF THE DATE HEREOF. HOWEVER, SUCH INFORMATION AND RECOMMENDATIONS ARE PROVIDED WITHOUT WARRANTY OF ANY KIND AND THIS CORPORATION DISCLAIMS ANY AND ALL LIABILITY OR LEGAL RESPONSIBILITY FOR USE OR RELIANCE UPON SAME.