Undercounter **Basins**



INSTALLATION INSTRUCTIONS

Tools Needed

• Pencil • Tape Measure • Jigsaw • Wrench • Hammer • Screwdriver • Drill •

Materials Needed

• Sink • Faucet • Drain Assembly • Supply Pipe & Fittings • Drain Pipe, Trap & Fittings • Silicone Sealant • • Sink Clips (NOT Provided) •





- If possible, attach the drain to the lavatory before installation.
- Install the water supplies and drain piping according to the manufacturer.
- Verify cabinet clearance beneath the countertop to accommodate lavatory basin, faucet valving, and drain piping.
- Cut out the template where indicated for the countertop opening.
- Cut along the inside of the cutting line.
- Position the template on the countertop to ensure clearance between the lavatory, faucet, and backsplash.
- Trace around the template on the countertop with a pencil.
- Mark the faucet hole centerline on the countertop.
- Cut out the countertop opening by carefully following the pencil line traced from the template.
- Position the lavatory in the cut-out and verify the fit.

For Wood Countertops:

Be sure to waterproof any exposed areas of wood.

- 1. If the countertop has not been installed, install it at this time.
- 2. Drill the faucet holes according to the faucet installation instructions.
- 3. Install the faucet and drain according to the manufacturer's instructions.
- 4. Apply a continuous bead of quality sealant to the top surface of the lavatory rim where it will contact the countertop.
- 5. Install the lavatory to the countertop with sink clips (not provided).
- 6. Position the lavatory squarely under the cut-out before tightening the clamps.
- 7. Draw the lavatory rim up against the countertop until it is snug. Do not overtighten.
- 8. Immediately wipe away any excess sealant and fill any voids as needed.
- 9. Allow the sealant to set for 30 minutes before proceeding.
- 10. Connect and tighten the trap to the drain, and complete the water supply connections to the faucet according to the faucet instructions.
- 11. Run water into the lavatory and check for leaks.

NOTE:

DO NOT tighten too much or you may damage bowl.