

ROMAN™

THE NO.1 CONTRACTOR BRAND

Technical Data: PRO-935, R-35®

Updated: 2/8/16



PRO-935

R-35®, Adhesion Promoting Wallpaper Primer

Clear Wallcovering Primer for Non-Porous Surfaces

Product Number(s): 12105, 12101, 12114

Base: Proprietary specialty polymer

Product Information

General Properties: An adhesion-promoting primer/sizer for non-porous surfaces.

- Dries clear with a permanent tack
- Water resistant
- Low odor, no spatter
- LEED compliant

Recommended Uses: Application over non-porous or sealed surfaces

NOT Recommended For: Porous surfaces. Not recommended for direct application over oil-based primers.

Compatible Coatings: All ROMAN® adhesives

Substrates: Non-porous surfaces such as ceramic tile, sealed wood paneling and glass/mirrors

Mildew-Resistant: All Roman products contain biocides for in-can preservation

Specification Data

Coverage: Up to approx. 400 square feet per gallon

VOC (regulatory): 0 g/L as calculated per EPA Method 24

Drying Time: Minimum drying time is three hours. Optimum drying time is 12 hours. Low temperature, high humidity and poor ventilation will slow down the drying process.

Roman Decorating Products – Calumet City, Illinois

For Technical Help: Call 1-800-488-6117 or Email: technicalhelp@romandec.com

www.romandecoratingproducts.com

Application Instructions

Surface Preparation: Surface must be free from grease and all residues, dry, smooth and structurally sound. Repair all unsound surfaces. Clean ceramic tile, paneling, glass and sealed surfaces with isopropyl alcohol. For best results, lightly sand or abrade all glossy or sealed surfaces prior to applying. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

After completion of the required surface preparation, it is critical to test the surface to ensure compatibility. Select a small, inconspicuous area of the surface for testing and apply the primer or adhesive as specified. Inspect test area after 24 hours before proceeding with installation of wallcovering.

Dilution: Do not dilute.

Application Method: Use only when the room temperature is above 60°F. Apply at recommended spread rate using roller or spraying system. Do not overspread.

Airless Spray:	PSI Capable:	minimum 3000 PSI
	Hose:	3/8" I.D.
	Tip Size:	.015 and larger
	Gun PSI:	1500-1700

Clean-Up: Before the primer dries, remove any excess with clean water. Brushes and rollers should be cleaned immediately after use with a mild soap and clean, warm water.

Warning

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Roman Decorating Products, LLC does not endorse the use of any product in an installation that does not meet a Class A fire rating or any applicable code. Testing by a certified laboratory should be conducted to verify that the installation meets a Class A fire rating and to guarantee compliance with all applicable codes. Specifically, if a Roman product is used to hang wallpaper over existing wallpaper, it is unlikely to meet these standards.

Limited Warranty

Roman Decorating Products, LLC warrants that it will replace this product free of charge, if, within 12 months of manufacture, it is found to be defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential, punitive, and special damages. Conditions of use are beyond our control.

Caution

Store in a cool, dry place. DO NOT FREEZE! Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well-ventilated work area. Close container after each use. Keep out of reach of children.