side 1





- Peak Watts: 11,050W Rated Watts: 9000W
- Engine Type: Single Cylinder, 4 Stroke, OHV, Air Cooled
- Displacement: 457cc
- Noise Level (@7m) ≤ 78dBA
- Low Oil Sensor
- Electric & Recoil Start Two Duplex 120V 20A GFCI
- One 120/240V AC 50A Twist-Lock
- (NEMA L14-50)
- Hour Meter
- Rubber Outlet Dust Covers
- Powder Coated Heavy Duty Ø1-1/4" (32mm) Steel Tube Frame
- Fold Down / Cushion Grip Handles
- 10" No Flat Foam Tires With

- - 6.6 Gallon Fuel Tank 9.5 Hour Run time @ 50% Load
 - Fuel Gauge
 - Maintenance Free Battery (Sealed) 12V 14Ah

(1.1L) Engine Oil & Funnel

Battery, Quick Start Guide User Manual, Engine Manual, Spark Plug T Wrench, Combination Wrench Phillips Screw Driver, 10W30 38oz.







www.fordpower.cc

side 2



FORD POWER EQUIPMENT



11,050WATT GENERATOR







FG11050PE

Item No. Assembled Dim. Net Weight **Gross Weight** Carton Type Outside Dim. 40'HQ Qty. Warranty

F2E900E991 819699014096 30" x 29.25" x 25" 218lbs. (99kg) 233lbs. (106kg) Color Box 30.6" x 23.6" x 23.6" 206 Labor 1 Year Limited Parts 2 Years Limited







Ford Motor Company Trademarks and Trade Dress used under license. Manufactured and distributed by Pulsar Products Inc.