

INSTANT HOT WATER

BUILT-IN RECIRCULATION BENEFITS:

Instant Hot Water at the Tap¹
Perfect for Replacement
Programmable timer based activation
Save Time on Install with Built-in Pump
Reduces Water Waste

TANKLESS FEATURES:

- .94 UEF
- Dual Stainless Steel Heat Exchangers
- 1/2" Gas Line Compatible
- Vents with PVC up to 100' (3") and 50' (2")
- Ultra Low NOx Burner
- Includes Crossover Valve for easy installation using existing plumbing

Key Features

- **Water and Gas Leak Detection for Added Protection**
- **Compatible with Room Air Intake**
More install options and faster to install
(single units only, not common vented)
- **Max GPM of 11** (on 199K BTU models)
- **Warranty**
 - **12-Year** heat exchanger – Residential
 - **5-Year** heat exchanger – Commercial
 - **5-Year** parts including **Built-in Recirculation Pump**
 - **1-Year** labor

¹ Individual results may vary.



RHEEM® PERFORMANCE PLATINUM™
CONDENSING TANKLESS GAS WATER
HEATERS WITH BUILT-IN RECIRCULATION

ECO200DVRHLN

18,000-199,000 BTU/h

ECO180DVRHLN

18,000-180,000 BTU/h

Natural Gas Models

Indoor Models only (outdoor

conversion covers coming soon)

\$125 VALUE

Crossover valve
and service valves
included.

Recirculation Pump Specifications:

- Timer-based recirculation pump with option for on-demand accessory wall switch
- Max. Pipe Lengths:
 - **3/4" copper pipe – 500 ft. total**
 - **1/2" copper pipe – 200 ft. total**

Performance Platinum™ Series
exclusively sold at



The new degree of comfort.®



PERFORMANCE PLATINUM™

DESCRIPTION				FEATURES					ROUGHING IN DIMENSIONS (SHOWN IN INCHES)						ENERGY INFO.	
MODEL NUMBER	GAS INPUT BTU/H	TYPE	NUMBER OF BATHROOMS*	TEMP. RANGE	MIN. FLOW/ACTIVATION GPM	GPM @ 77° RISE MAX.	GPM @ 45° RISE MAX.	MAX. GPM	CONNECTION		HEIGHT	WIDTH	DEPTH	VENT DIAM.	SHIP WEIGHT (LBS.)	UNIFORM ENERGY FACTOR (UEF)
									WATER	GAS						
ECO200DVRHLN	18,000-199,000	Indoor DV w/ Recirc Pump	4	100° to 140° F	0.50/0.50	5.0	8.5	11.0	3/4	3/4	28.7	17.3	14.8	2" or 3" PVC 2-Pipe	85	0.94
ECO180DVRHLN	18,000-180,000	Indoor DV w/ Recirc Pump	3-4	100° to 140° F	0.50/0.50	4.5	7.7	9.9	3/4	3/4	28.7	17.3	14.8	2" or 3" PVC 2-Pipe	85	0.94

*Based on simultaneous showers using 2.5 gallons per minute. Flow rates vary depending on temperature of cold water supply.

INCLUDED IN THE BOX:

- ✓ Tankless water heater with built-in recirculation pump
- ✓ Brass service valves
- ✓ Crossover valve
- ✓ Pressure relief valve
- ✓ 5' 120V 3-prong power cord
- ✓ Mounting & spare parts kit
- ✓ Vent screens
- ✓ Use & care manual

ALSO NEEDED FOR INSTALLATION:

- ✓ Schedule 40 PVC venting in 2" or 3" (sold separately)
- ✓ 120V outlet near installation location*
- ✓ Water and gas lines near installation location*
- ✓ Condensate Wastewater Neutralizer (sold separately)*


*Check local code requirements

OPTIONAL ACCESSORIES:


- ✓ On-Demand Recirculation kit & Manual Wall Switch
- ✓ Venting kits

Accessories available at homedepot.com

DIMENSIONS



HOW IT WORKS



In keeping with its policy of continuous progress and product improvement, Rheem reserves the right to make changes without notice.

Rheem Water Heating • 1115 Northmeadow Parkway, Suite 100
Roswell, Georgia 30076 • www.rheem.com

Rheem.com

PRINTED IN U.S.A. 11/17 WP FORM NO. THD-TK-RH110DV-FEATURE-NAT