

JEFF LEWIS® PAINT

JEFF LEWIS PAINTS are high-quality, ultra-low VOC, paints designed for use on trim, walls, ceilings, and other properly prepared and primed surfaces. The products offer excellent washability, superior scrub, and very good non-blocking properties. The paint cannot cause, prevent, or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.

SURFACE COVERAGE

This paint has a spread rate of 350-400 square feet per gallon, depending on surface conditions and application techniques.

SURFACE PREPARATION

All surfaces must be cured, clean, dry, and free from oil, dirt, dust, rust, stains, grease, mildew, wax, efflorescence, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and surface imperfections with a suitable patching material. Repaired surfaces should be sanded smooth and dusted clean. Glossy surfaces should be dulled for adhesion.

APPLICATION

Stir well before using. This paint is designed to be applied at package consistency. If thinning is necessary for good flow and workability, add up to 1/4 pint (4 fl. oz.) of water per gallon. The paint may be brushed, rolled, or sprayed. Do not apply when air or surface temperature is below 50° F.

AVERAGE DRY TIME

Dry to touch in 1 hour. Recoat after 4 hours.

STORAGE

Store in dry area and protect from freezing. Extreme temperatures may cause paint to become unusable. Freezing and thawing will cause paint to gel and high heat may cause a solid skin to form.

CLEAN UP

Wash all equipment with warm, soapy water.

MANUFACTURING INFORMATION

JEFF LEWIS Paint is manufactured in the U.S.A. by VISTA PAINT CORPORATION, FULLERTON, CA 92831.

ADDITIONAL INFORMATION

Product Information Sheets, Material Safety Data Sheets, local disposal options of unwanted leftover paint and other information for this product are available on www.JeffLewisPaint.com.

HEALTH & SAFETY

Keep out of reach of children. Avoid breathing spray mist. Do not ingest. Avoid prolonged contact with skin. Close container after each use. Use with adequate ventilation. FIRST AID: If swallowed, immediately give 1 or 2 glasses of water to drink. For EMERGENCY INFORMATION, call 1-800-222-1222. For eye contact, immediately flush with water for 15-minutes. For skin contact, wash with soap and water.

CAUTION

CLOSE CONTAINER AFTER EACH USE.
DO NOT TAKE INTERNALLY.
USE ONLY WITH ADEQUATE VENTILATION.

LEAD: WARNING! If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Hotline at 1-800-424-LEAD or log on to epa.gov/lead.



JEFFLEWISPAINT.com

 **WARNING! Cancer and Reproductive Harm**
www.P65Warnings.ca.gov