



Build to Withstand
the Elements

Deck-Drive™
DWP WOOD SS Screw

**Now Available in Additional
Sizes and Lengths!**

(800) 999-5099
www.strongtie.com

Deck-Drive™ DWP WOOD SS Screw for Severe-Exposure Wood Decking Applications



The Deck-Drive™ DWP Wood SS screw product line has been expanded to include both trim- and flat-head fasteners in a variety of sizes and lengths, making it ideally suited for almost any exterior wood-to-wood fastening application. The DWP was designed to provide fast, easy installations in high-exposure environments so you can truly build to withstand the elements. Available in corrosion-resistant Type 305 and Type 316 stainless steel, the DWP is great for decks, docks, boardwalks and general exterior wood construction where extra weather resistance and long-lasting quality are critical. The specially designed sharp point and unique box threads also greatly reduce driving torque, allowing for easier installations and higher productivity on the jobsite.



DWP Trim-Head
Unpainted without nibs
1" – 4" lengths



DWP Flat-Head
Unpainted with nibs
1¼" – 5" lengths



Unique "box" thread design provides up to 35% increase in screw driving productivity*

**Great for Decking,
Docks and Boardwalks;
Finishing, Millwork and Trim**



Type 316 Stainless Steel
for elevated corrosion resistance (also available in Type 305 stainless steel)

6-Lobe Drive
helps prevent driver-bit cam-out for easier driving and extended bit life

Specially Designed Sharp Point penetrates even hard wood products with ease

* Based on test results indicating the DWP screw requires up to 35% less measured torque in comparison to other wood screws.

Also Available:

Trim-Head, Painted

Type 316 Stainless Steel
1½" – 3" lengths



Type 305 Stainless Steel
2½" length




Tan 03 (Ipè)

The trim-head version is available in Types 305 and 316 stainless steel with a tan painted head for a better color match

Deck-Drive™ DWP WOOD SS Screw


for High-Exposure Wood Decking Applications



DWP Trim-Head, Unpainted

Type 316 Stainless Steel											
Size	Length (in.)	Head Diameter (in.)	Bit Size	Approx. Count Per lb.	1 lb. Model No.	5 lb. Model No.	Clam Shell		350-Count Model No.	Bulk Bucket	
							Count	Model No.		Count	Model No.
#7	1½	0.23	T15	195	T07162WP1	T07162WP5	100	T07162FWP	T07162WPP	4,000	T07162WPB
#7	2¼	0.23	T15	138	T07225WP1	T07225WP5	86	T07225FWP	T07225WPP	1,750	T07225WPB
#7	3	0.23	T15	98	T07300WP1	—	60	T07300FWP	T07300WPP	1,750	T07300WPB
Type 305 Stainless Steel											
#7	1	0.23	T15	303	S07100WP1	S07100WP5	—	—	—	5,000	S07100WPB
#7	1¼	0.23	T15	264	S07125WP1	S07125WP5	—	—	S07125WPP	5,000	S07125WPB
#7	1½	0.23	T15	195	S07162WP1	S07162WP5	135	S07162FWP	S07162WPP	4,000	S07162WPB
#7	2	0.23	T15	156	S07200WP1	S07200WP5	—	—	S07200WPP	4,000	S07200WPB
#7	2¼	0.23	T15	138	S07225WP1	S07225WP5	100	S07225FWP	S07225WPP	1,750	S07225WPB
#7	2½	0.23	T15	121	S07250WP1	S07250WP5	—	—	S07250WPP	1,750	S07250WPB
#7	3	0.23	T15	98	S07300WP1	S07300WP5	60	S07300FWP	S07300WPP	1,750	S07300WPB
#8	2½	0.25	T20	109	—	—	70	S08250FWP	S08250WPP	1,750	S08250WPB
#8	3	0.25	T20	91	—	—	70	S08300FWP	S08300WPP	1,750	S08300WPB
#9	3½	0.25	T20	70	S09350WP1	S09350WP5	35	S09350FWP	—	1,500	S09350WPB
#9	4	0.25	T20	61	S09400WP1	S09400WP5	—	—	—	1,000	S09400WPB

6-lobe bit replacements: T15 uses BIT15T-2; T20 uses BIT20T-2.



DWP Trim-Head, Painted


Type 316 Stainless Steel					
Size	Length (in.)	Head Diameter (in.)	Bit Size	350-Count Model No.	1,750-Count Model No.
#7	1½	0.23	T15	T07162WJI	T07162WCI
#7	2¼	0.23	T15	T07225WJI	T07225WCI
#7	3	0.23	T15	T07300WJI	T07300WCI
Type 305 Stainless Steel					
#8	2½	0.25	T20	S08250WJI	S08250WCI



6-lobe bit replacements: T15 uses BIT15T-2; T20 uses BIT20T-2.

Deck-Drive™ DWP WOOD SS Screw

DWP Flat-Head




Type 316 Stainless Steel										
Size	Length (in.)	Head Diameter (in.)	Bit Size	Approx. Count Per lb.	1 lb. Model No.	5 lb. Model No.	Deck Pack		Bulk Bucket	
							Count	Model No.	Count	Model No.
#8	1 1/4	0.34	T20	176	T08125WP1	T08125WP5	—	—	5,000	T08125WPB
#8	1 5/8	0.34	T20	150	T08162WP1	—	350	T08162WPP	4,000	T08162WPB
#8	2	0.34	T20	128	T08200WP1	T08200WP5	350	T08200WPP	3,000	T08200WPB
#8	2 1/2	0.34	T20	102	T08250WPF1	T08250WPF5	—	—	1,750	T08250WPFB
#8	3	0.34	T20	82	T08300WPF1	T08300WPF5	—	—	1,750	T08300WPFB
#10	2	0.34	T25	96	T10200WP1	T10200WP5	—	—	2,500	T10200WPB
#10	2 1/2	0.34	T25	82	T10250WP1	T10250WP5	350	T10250WPP	1,750	T10250WPB
#10	3	0.34	T25	68	T10300WP1	T10300WP5	350	T10300WPP	1,750	T10300WPB
#10	3 1/2	0.34	T25	56	T10350WP1	—	250	T10350WPP	1,000	T10350WPB
#10	4 1/2	0.34	T25	43	—	—	—	—	1,000	T10450WPCM
#12	2 1/2	0.44	T27	56	T12250WP1	T12250WP5	—	—	1,750	T12250WPB
#12	3	0.44	T27	48	T12300WP1	T12300WP5	—	—	1,500	T12300WPB
#12	3 1/2	0.44	T27	42	T12350WP1	T12350WP5	—	—	1,000	T12350WPB
#12	4	0.44	T27	36	T12400WP1	T12400WP5	100	T12400WPP	750	T12400WPB
#12	4 1/2	0.44	T27	32	T12450WP1	T12450WP5	—	—	750	T12450WPB
#12	5	0.44	T27	29	T12500WP1	T12500WP5	—	—	500	T12500WPB
#14	4	0.46	T27	26	—	T14400WP5	100	T14400WPP	700	T14400WPB

Type 305 Stainless Steel										
Size	Length (in.)	Head Diameter (in.)	Bit Size	Approx. Count Per lb.	1 lb. Model No.	5 lb. Model No.	Deck Pack		Bulk Bucket	
							Count	Model No.	Count	Model No.
#8	1 1/4	0.34	T20	176	S08125WP1	S08125WP5	—	—	5,000	S08125WPB
#8	1 5/8	0.34	T20	150	S08162WP1	S08162WP5	350	S08162WPP	4,000	S08162WPB
#8	2	0.34	T20	128	S08200WP1	S08200WP5	350	S08200WPP	3,000	S08200WPB
#8	2 1/2	0.34	T20	102	S08250WPF1	S08250WPF5	—	—	1,750	S08250WPFB
#8	3	0.34	T20	82	S08300WPF1	S08300WPF5	—	—	1,750	S08300WPFB
#10	1	0.34	T25	172	S10100WP1	S10100WP5	—	—	4,500	S10100WPB
#10	1 1/2	0.34	T25	134	S10150WP1	S10150WP5	—	—	3,500	S10150WPB
#10	2	0.34	T25	96	S10200WP1	S10200WP5	—	—	2,500	S10200WPB
#10	2 1/2	0.34	T25	82	S10250WP1	S10250WP5	350	S10250WPP	1,750	S10250WPB
#10	3	0.34	T25	68	S10300WP1	S10300WP5	350	S10300WPP	1,750	S10300WPB
#10	3 1/2	0.34	T25	56	S10350WP1	S10350WP5	—	—	1,000	S10350WPB
#12	2 1/2	0.44	T27	56	S12250WP1	S12250WP5	—	—	1,750	S12250WPB
#12	3	0.44	T27	48	S12300WP1	S12300WP5	—	—	1,500	S12300WPB
#12	3 1/2	0.44	T27	42	S12350WP1	S12350WP5	—	—	1,000	S12350WPB
#12	4	0.44	T27	36	S12400WP1	S12400WP5	100	S12400WPP	800	S12400WPB
#12	4 1/2	0.44	T27	32	S12450WP1	S12450WP5	—	—	750	S12450WPB
#12	5	0.44	T27	29	S12500WP1	S12500WP5	—	—	500	S12500WPB
#14	4	0.46	T27	26	—	S14400WP5	100	S14400WPP	700	S14400WPB

6-lobe bit replacements: T20 uses BIT20T-2; T25 uses BIT25T-2; T27 uses BIT27T-2.

DWP Flat-Head, Collated



Type 316 Stainless Steel					
Size	Length (in.)	Material	1,000 ct. Model No.	1,500 ct. Model No.	PRO 300S
#10	2 1/2	316SS	—	SSDWP212S316	✓
#10	3	316SS	SSDWP3S316	—	✓
Type 305 Stainless Steel					
#10	2 1/2	305SS	—	SSDWP212S305	✓
#10	3	305SS	SSDWP3S305	—	✓

Uses BITTX25 replacement bit.



Available collated for the Quik Drive® auto-feed screw driving system. See strongtie.com for details.

This flier is effective until June 30, 2018, and reflects information available as of April 1, 2016. This information is updated periodically and should not be relied upon after June 30, 2018; contact Simpson Strong-Tie for current information and limited warranty or see www.strongtie.com.