

• TRUSTED QUALITY SINCE 1921 •

**RUST-OLEUM®****UNIVERSAL®**  
ADVANCED FORMULA**HAMMERED  
ALL SURFACE  
PAINT + PRIMER****MAXIMUM DURABILITY  
& ADHESION****WOOD  
METAL  
PLASTIC  
MASONRY****SILVER****INDOOR & OUTDOOR • SPRAY ANY ANGLE  
FAST DRYING • RUST PREVENTIVE****DANGER!** EXTREMELY FLAMMABLE LIQUID  
AND VAPOR. VAPOR HARMFUL. VAPOR MAY  
CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE.  
See other cautions on back panel.**PELIGRO!** LÍQUIDO Y VAPORES EXTREMADAMENTE  
INFLAMABLES. VAPORES NOCIVOS. PUEDEN CAUSAR UN  
INCENDIO REPENTINO. NO SOMETER A PRESIÓN.  
Observar otras precauciones al dorso.

NET WT. 12 OZ. 340g

**UNIVERSAL IS A PREMIUM ALL-SURFACE PAINT + PRIMER** that provides the ultimate long-lasting protection and durability. This breakthrough, rust preventive formula adheres to plastic, wood, metal, concrete, wicker, aluminum, and masonry surfaces. A comfort grip trigger eliminates finger fatigue caused by continuous spraying. Any angle spray allows you to spray even upside down. Fast Drying. TIP: Some plastics made of polyethylene such as plastic storage containers are manufactured in a way that may hinder maximum paint adhesion. Test paint in a hidden area first.

**Painting Conditions:** Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50°F and 90°F (10°-32°C) and humidity is below 65% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200°F (93°C) or galvanized metal. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

**Preparation:** Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. Clean with soap and water, rinse and let dry. **WARNING:** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**Painting:** Shake vigorously for one minute after mixing ball begins to rattle. If mixing ball fails to rattle **DO NOT STRIKE CAN!** Contact Rust-Oleum. Prior to use, slide off the safety clip from the trigger. Shake often during use. Hold can upright 8-12" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more medium coats applied at moderate speed.

**Dry & Recoat Times:** based on 70°F-50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 30 minutes, to handle in 1 hour and fully dry in 24 hours. Apply a second coat within 1 hour or after 48 hours.

**Clean-up:** When finished spraying, wipe off tip before storing. Clean up wet paint with Xylol or mineral spirits. Dispose of empty can in recycle pickup. Do not burn or place in trash compactor.

**CONTAINS:** ACETONE, LIQUEFIED PETROLEUM GAS, XYLENE, ETHYL ACETATE, GLYCOL ETHERS AND DIMETHYL CARBONATE. Vapor harmful. May affect the brain or nervous system causing dizziness, headache, or nausea. Causes eye, skin, nose and throat irritation. Do not puncture, strike, or incinerate (burn) container. Exposure to heat or prolonged exposure to sun may cause bursting. Do not expose to heat or store at temperatures above 120°F (49°C). **NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the content may be harmful or fatal. **Vapors may ignite explosively.** Keep away from heat, sparks and flame. Do not smoke. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Use only with adequate ventilation. Do not breathe vapors or spray mist. Ensure fresh air during application and drying. If you experience eye watering, headache or dizziness, wear an appropriate, properly fitted respirator (NIOSH approved) or leave the area to obtain fresh air. Avoid contact with eyes, skin and clothing. **First Aid:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. **WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). **KEEP OUT OF REACH OF CHILDREN.** For emergency call your physician, local poison control center or local emergency room. For product health information, call: (800) 461-4785.

**SATISFACTION GUARANTEED:** If you are dissatisfied with this product, contact **Rust-Oleum**. Product Support at 800-461-4785 for product replacement or a full refund of the purchase price. Refer to product number and batch code.

**UNIVERSAL ES UNA PINTURA Y PRIMERA PARA TODAS LAS SUPERFICIES** que brinda la máxima protección y durabilidad de larga duración. Esta innovadora fórmula antioxidante se adhiere a las superficies de plástico, madera, metal, hormigón, madera, aluminio y mampostería. Un gatillo de agarre cómodo elimina la fatiga del dedo causada por la pulverización continua. Cualquier spray de agua le permite rociar incluso al revés. Secado rápido. **CONSEJO:** Algunos plásticos hechos de polietileno como los recipientes de almacenamiento de plástico están fabricados de manera tal que pueden dificultar la máxima adhesión de la pintura. Pruebe la pintura en un área oculta primero.

**Condiciones para Pintar:** Use en el aire libre o en un área bien ventilada como en un garaje abierto. Use cuando la temperatura se encuentra entre 50°F y 90°F (10°-32°C) y la humedad relativa se encuentra bajo un 65%, para asegurar un secado apropiado. No aplique a las superficies que exceden una temperatura de 93°C (200°F). Fijar tapones sobre metal galvanizado. Evite el rociado durante condiciones verticales y con polvo. Proteja las superficies que se encuentren alrededor contra la niebla de rociado. **Preparación:** Quite toda la pintura suelta y la oxidación con un cepillo de carbón de aluminio o con papel lijado. Lije ligeramente las superficies lustrosas. Limpie con jabón y agua, enjuague y déjelo seco. **ADVERTENCIA:** Si usted raspa, lija o remueve la pintura vieja, usted puede soltar polvo de plomo. El PLOMO ES TOXICO. Póngase en contacto con la Línea Alérgica Nacional para la información sobre el Plomo (llamada al 1-800-424-LEAD (5323)) o visite a [www.epa.gov/lead](http://www.epa.gov/lead). **Printado:** Agite la lata vigorosamente por un minuto después de que le diera tiempo de reposo. Pruebe la pintura en un área oculta primero.

**Pintando:** Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 50°F and 90°F (10°-32°C) and humidity is below 65% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200°F (93°C) or galvanized metal. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

**Preparación:** Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. Clean with soap and water, rinse and let dry. **WARNING:** If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

**Pintando:** Shake vigorously for one minute after mixing ball begins to rattle. If mixing ball fails to rattle **DO NOT STRIKE CAN!** Contact Rust-Oleum. Prior to use, slide off the safety clip from the trigger. Shake often during use. Hold can upright 8-12" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more medium coats applied at moderate speed.

**Dry & Recoat Times:** based on 70°F-50% relative humidity. Allow more time at cooler temperatures. Dries to touch in 30 minutes, to handle in 1 hour and fully dry in 24 hours. Apply a second coat within 1 hour or after 48 hours.

**Clean-up:** When finished spraying, wipe off tip before storing. Clean up wet paint with Xylol or mineral spirits. Dispose of empty can in recycle pickup. Do not burn or place in trash compactor.

**CONTIENE:** ACETONA, GAS LICUADO DE PETRÓLEO, XILENO, ACETATO DE ETILo, ETER DE GLICOLo Y CARBONATO DE DIMEtILO. Vapores dañinos. Pueden afectar al cerebro o al sistema nervioso y causar mareo, dolor de cabeza o náuseas. Causan irritaciones en los ojos, piel, nariz y garganta. No perfor, golpee o incinere (queme) el contenedor. Una exposición al calor o una prolongada exposición al Sol puede causar una explosión. No expone al calor ni tampoco almacene en temperaturas sobre 40°C (104°F). **AVISO:** Los reportes han asociado repetidas y prolongadas exposiciones ocupacionales a los solventes con daños permanentes al cerebro y al sistema nervioso. El uso intencional al concentrar e inhalar el contenido deliberadamente puede ser peligroso o fatal. Los vapores pueden encenderse explosivamente. Mantenga las llamas del calor, cigarras y las llamas de fuego. No fume. Durante la aplicación del producto, apague las llamas y llamas piloto, las estufas, calentadores, motores eléctricos y todas las otras fuentes de ignición hasta que todos los vapores hayan desaparecido. Prevenga la acumulación de vapores abriendo todas las ventanas y puertas para lograr una ventilación cruzada. **Use solamente cuando existe una ventilación adecuada.** No respire los vapores o niebla del rociado. Asegure la entrada de aire fresco durante la aplicación y el tiempo de secado. Si experimenta lagrimeo, dolor de cabeza o mareo, coloque adecuadamente un respirador apropiado (aprobadlo por el NIOSH) o abandone el área y respire aire fresco. Evite contacto con los ojos, la piel y la ropa. **Primeros Auxilios:** Si experimenta dificultad al respirar, salga del área para obtener aire fresco. Si la dificultad continúa, obtenga atención médica inmediatamente. En caso de contacto con los ojos, enjuaguelos inmediatamente con bastante agua por lo menos durante 15 minutos y obtenga atención médica. En caso de contacto con la piel, lávela completamente con jabón y agua.

**ADVERTENCIA:** Cancer y daños reproductivos – [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov). **MANTENGA FUERA DEL alcance DE LOS NIÑOS.** En caso de emergencia, llame a su médico, el centro local para el control de los venenos, o sala de emergencias. Para obtener información sobre la sanidad del producto, llame a: (800) 461-4785. PROHIBIDA SU VENTA A MENORES DE EDAD. PRODUCTO ORIGINARIO DE E.U.A.

**342492 SILVER HAMMERED**

219123

**RUST-OLEUM**  
CORPORATION

11 Hawthorn Pkwy., Vernon Hills, IL 60061

800-481-4785 [rustoleum.com](http://rustoleum.com)

Made in USA | Hecho en E.U.A.

©2018 Rust-Oleum Corporation 342383 0818

U.S. PATENT NO. 7,204,393

343283 342492 UNV HD HMRD SILVER.indd 1

SCRN WHITE WHITE UNV GOLD SILVER PMS 199 YEL BLACK

10/21/18 8:52 AM



Flexible Packaging & Label Specialists  
22790 Meets Rd.  
Novi, Michigan 48375  
800/748-0209 • 248/335-7440  
[www.anchorprinting.com](http://www.anchorprinting.com)

Specs:

Size: 16 oz 21 x 604  
8.625" x 5.917"

Coating: Lamination

Please read the proof and specifications carefully. Any errors that are not acknowledged by the customer are NOT the responsibility of Anchor Printing. Customer approval is required for print production.

APPROVED  
OK TO PROCEED

NOT APPROVED  
SEND NEW PROOF

CUSTOMER INITIALS

