IN41321 INSTALLATION INSTRUCTIONS

1500 Cherokee Parkway, Suite 100, Acworth, GA 30102 Phone: (866) 845-5451 • Fax: (866) 816-6165

E: service@acclaim-lighting.com • www.acclaim-lighting.com



Please read carefully and save these instructions, as you may need them at a later date.

CAUTION

WARNING: Risk of Fire. Consult a qualified electrician to ensure correct branch circuit conductor.

Turn off the main power at the circuit breaker before installing the fixture in order to prevent possible shock.

GENERAL

All electrical connections must be in accordance with local and National Electrical Code (N.E.C.) standards. If you are unfamiliar with proper electrical wiring connections obtain the services of a qualified electrician.

Remove the fixture and the mounting package from the box and make sure that no parts are missing by referencing the illustration.

ASSEMBLY AND INSTALLATION

- 1. Insert plastic anchor (9) into wall.
- 2 Secure the back plate (6) to the outlet box (1) with machine screws (8). Secure the back plate (6) to the plastic anchors (9) with two anchors screws (10).
- 3. Pull out the outlet wire and ground wire from the outlet box (1). Make wire connections.
- --Ribbed wire (w/o marking) or white wire from light to White wire (2) from power source.
- --Smooth wire (w/o marking) or black wire from light to Black wire (3) from power source.
- --Attach the ground wire (4) to back plate (6) with a ground screw (7).
- 4. Secure front plate (11) to back plate (6) with mounting screws (12).
- 5. Remove socket ring (16) from socket (13) and place the glass (15) and spacer (15) over the socket (13). Use socket wrench (17) to secure socket ring (16) back onto socket (13).
- 6. Install bulbs: (bulbs not included)
- (Don't exceed the maximum capacity recommended on the sockets).

INSTALLATION IS NOW COMPLETED

