

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this MSDS are further described in Section 16.

# 1. Identification

This Material Safety Data Sheet is available in American Spanish upon request. Los Datos de Serguridad del Producto pueden obtenerse en Espanol si lo riquiere.

Product Name:	SIDE Winder Advanced Polymer Sealant - All Colors	Revision Date:	5/8/2015
Product UPC Number:	00801, 00801, 00804, 00807, 00810, 00813, 00823, 00835	Supercedes Date:	4/28/2015
Product Use/Class:	Caulking Compound	SDS No:	00010029001
Manufacturer:	DAP Products Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723 888-327-8477 (non-emergency matters)		
Preparer:	Regulatory Department		

# 2. Hazards Identification

**EMERGENCY OVERVIEW:** Under normal use conditions, this product is not expected to cause adverse health effects. High concentration of vapors may cause irritation to eyes and respiratory system.

### **GHS Classification**

Not a hazardous substance or mixture.

### Symbol(s) of Product

Not a hazardous substance or mixture.

### Signal Word

Not a hazardous substance or mixture.

# 3. Composition/Information on Ingredients

<u>Chemical Name</u>	CAS-No.	Wt. % GHS Symbols	GHS Statements
Calcium Carbonate	471-34-1	25-50 GHS07	H332
Limestone	1317-65-3	25-50 GHS07	H332
Proprietary Phthalate Esters	Proprietary	10-25 GHS07	H332
Titanium dioxide	13463-67-7	2.5-10 No Information	No Information
Sodium Potassium alumino silicate	37244-96-5	1.0-2.5 No Information	No Information
Diisononyl phthalate	28553-12-0	1.0-2.5 GHS06	H331
Trimethoxyvinylsilane	2768-02-7	1.0-2.5 GHS02-GHS07	H225-332
Quartz	14808-60-7	0.1-1.0 GHS07	H302

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

## 4. First-aid Measures

**FIRST AID - INHALATION:** Material is not likely to present an inhalation hazard at ambient conditions. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

### 5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: No special protective measures against fire required.

**SPECIAL FIREFIGHTING PROCEDURES:** Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

**EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

## 6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Scrape up dried material and place into containers. Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

## 7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN!DO NOT TAKE INTERNALLY. Avoid breathing vapor and contact with eyes, skin and clothing. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Wash thoroughly after handling. Remove contact lenses before using. Do not handle contact lenses until all sealant has been cleaned from fingertips, nails and cuticles. Residual sealant may transfer to contact lenses and cause severe eye irritation.

**STORAGE:** Avoid excessive heat and freezing. Do not store at temperatures above 120 degrees F. Store away from caustics and oxidizers.

## 8. Exposure Controls/Personal Protection

Ingredients with Occupational Expo	sure Limits			
Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	<u>OSHA PEL-TWA</u>	OSHA PEL-CEILING
Calcium Carbonate	N.E.	N.E.	N.E.	N.E.
Limestone	N.E.	N.E.	15 mg/m3 TWA	N.E.
			total dust, 5 mg/m	3
			TWA respirable	

fraction

#### SDS Number: 00010029001

Proprietary Phthalate Esters	N.E.	N.E.	N.E.	N.E.
Titanium dioxide	10 mg/m3 TWA	N.E.	15 mg/m3 TWA total dust	N.E.
Sodium Potassium alumino silicate	N.E.	N.E.	N.E.	N.E.
Diisononyl phthalate	N.E.	N.E.	N.E.	N.E.
Trimethoxyvinylsilane	N.E.	N.E.	N.E.	N.E.
Quartz	0.025 mg/m3 TWA respirable fraction	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

## **Personal Protection**



**RESPIRATORY PROTECTION:** No personal respiratory protective equipment normally required. National Institute for Occupational Safety and Health (NIOSH) has recommended that the permissible exposure limit be changed to 50 micrograms respirable free silica per cubic meter of air (0.05 mg/m3) as determined by a full shift sample up to 10-hour work shift.



SKIN PROTECTION: Wear nitrile or neoprene gloves.



**EYE PROTECTION:** Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Not required under normal use.



**HYGIENIC PRACTICES:** Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

# 9. Physical and Chemical Properties

Colored	Physical State:	Paste
Slight	Odor Threshold:	Not Established
1.48 - 1.54	pH:	Not Established
Not Established	Viscosity (mPa.s):	Not Established
Not Established	Partition Coeff., n-octanol/water:	Not Established
Not Established	Explosive Limits, %:	N.I N.I.
N.I N.I.	Auto-Ignition Temperature, °C	Not Established
93.3	Vapor Pressure, mmHg:	No Information
Slower Than n-Butyl Acetate	Flash Method:	Seta Closed Cup
Heavier Than Air		
Does not Support Combustion		
	Slight 1.48 - 1.54 Not Established Not Established Not Established N.I N.I. 93.3 Slower Than n-Butyl Acetate Heavier Than Air	SlightOdor Threshold:1.48 - 1.54pH:Not EstablishedViscosity (mPa.s):Not EstablishedPartition Coeff., n-octanol/water:Not EstablishedExplosive Limits, %:N.I N.I.Auto-Ignition Temperature, °C93.3Vapor Pressure, mmHg:Slower Than n-Butyl AcetateFlash Method:

(See "Other information" Section for abbreviation legend) (If product is an aerosol, the flash point stated above is that of the propellant.)

# 10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Excessive heat and freezing.

**INCOMPATIBILITY:** Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., COx, NOx.

## 11. Toxicological Information

**EFFECT OF OVEREXPOSURE - INHALATION:** Under normal use conditions, this product is not expected to cause adverse health effects. During application and cure, this product releases methanol. Methanol may affect the brain or nervous system causing dizziness, headache or nausea. Inhalation of vapors in high concentration may cause mild irritation of respiratory system (nose, mouth, mucous membranes).

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Under normal use conditions, this product is not expected to cause adverse health effects. Prolonged or repeated contact with skin may cause mild irritation.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Under normal use conditions, this product is not expected to cause adverse health effects. Direct eye contact may cause irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** Under normal use conditions, this product is not expected to cause adverse health effects. Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury. Ingestion may result in obstruction when material hardens.

CARCINOGENICITY: No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Inhalation, Skin Contact

#### **Acute Toxicity Values**

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u> 471-34-1	<u>Chemical Name</u> Calcium Carbonate	<u>Oral LD50</u> 6450 mg/kg Rat	<mark>Dermal LD50</mark> >2000 mg/kg Rat	<u>Vapor LC50</u> >20 mg/L
1317-65-3	Limestone	6450 mg/kg Rat	>2000 mg/kg	>20 mg/L
68515-49-1	Proprietary Phthalate Esters	>60000 mg/kg Rat	16000 mg/kg Rabbit	>12.54 mg/L Rat
13463-67-7	Titanium dioxide	>10000 mg/kg Rat	>5000 mg/kg Rabbit	>20 mg/L
37244-96-5	Sodium Potassium alumino silicate	N.I.	N.I.	N.I.
28553-12-0	Diisononyl phthalate	>9750 mg/kg Rat	3160 mg/kg Rabbit	>4.4 mg/L Rat
2768-02-7	Trimethoxyvinylsilane	11000 mg/kg Rat	3259.2 mg/kg Rabbit	>20 mg/L
14808-60-7	Quartz	500 mg/kg Rat	>2000 mg/kg	>20 mg/L

N.I. = No Information

# 12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

## 13. Disposal Information

**DISPOSAL METHOD:** This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Scrape up dried material and place into containers. Use personal protective equipment as necessary. In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations.

## 14. Transport Information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT Proper Shipping Na	me:	Not Regulated.		
DOT Technical Name:	N.A.		Hazard SubClass:	N.A.
DOT Hazard Class:	N.A.		DOT UN/NA Number:	N.A.
Packing Group:	N.A.			

# 15. Regulatory Information

## **U.S. Federal Regulations:**

### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard, Chronic Health Hazard

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt. This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA12(b) components exist in this product in concentrations at or above their thresholds.

#### **CALIFORNIA PROPOSITION 65 CARCINOGENS**

WARNING: This product contains chemicals known to the State of California to cause cancer.

#### **CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

WARNING: This product contains chemicals known to the State of California to cause birth defects or other reproductive harm.

## International Regulations: As follows -

## CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

WHMIS Class Consumer Commodity.

Revision D	ate:	5/8/2015			S	upersedes Date:	4/28/20	)15
Reason fo	r revision:	HazCom201	2/GHS Con	version				
Datasheet	produced by:	Regulatory D	epartment					
HMIS Rat	ings:							

VOC, Material, g/L:4


VOC as Defined by California Consumer Product Regulation, Wt/Wt%:0.2

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.

H331 Toxic if inhaled. H332 Harmful if inhaled.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since thisdocument is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.