



Eucatex of North America  
11475 Great oaks way  
Alpharetta, Georgia 30022  
(678)-624-0160  
Fax (678)-624-0621  
www.eucatex.com.br

---

## SAFETY DATA SHEET

Last Revision March 20, 2017

### SECTION 1. IDENTIFICATION

**PRODUCT NAME:** Pre Finished HardBoard

**TRADE NAME:** EUCAPLAC / EUCATILE

**DESCRIPTION:** Eucaboard is manufactured from wet, mat formed, hot pressed eucalyptus fiber hardboard. Under heat and pressure the natural wood resins flow and bond into a material with uniform physical properties.

**Recommended use:** Building Materials , Decorative , Furniture and General Construction

**Restriction Use:** HardBoard is intended for dry interior use Only and requires care in Handling

#### Manufacturer and Distributor:

Eucatex of North America  
11475 Great Oaks Way  
Alpharetta , GA 30022  
[www.eucatex.com](http://www.eucatex.com)  
**Contact Telephone – General :** 678-624-0160

### SECTION 2. HAZARDOUS IDENTIFICATION

#### Classification of the substance or mixture

OSHA HCS 2012 . This product is generally an article but is regulated under OSHA for the release of wood dust during mechanical operations releasing dust. The product is not considered Hazardous under the U.S OSHA 29 CFR 1910.1200 Hazard Communication Standard .The free hazardous under the U.S OSHA 29CFR 1910.1200 Hazard communication Standard

The classifications below are based upon wood dust.

Skin Irritation 2  
Skin Sensitization 1  
Eye Mild Irritation 2B  
Respiratory Sensitization 1  
Specific Target Organ Toxicity Single Exposure  
Combustible Dust

**INHALATION:** Gaseous formaldehyde may cause temporary irritation to the nose and throat. Wood dust may cause nasal dryness, irritation, coughing and sinusitis. Repeated exposures (even below 5 mg/m<sup>3</sup>) to certain wood dusts such as Western Red Cedar can produce allergic responses in some sensitive individuals.

**EYE CONTACT:** Gaseous formaldehyde may cause temporary irritation to the eyes. Wood dust can cause mechanical irritation.

**SKIN CONTACT:** Both formaldehyde and various species of wood dust may evoke allergic contact dermatitis in sensitized individuals. If an allergy pre-exists or develops, it may be necessary to remove the sensitized worker from further exposure to formaldehyde bonded wood products



Eucatex of North America  
11475 Great oaks way  
Alpharetta, Georgia 30022  
(678)-624-0160  
Fax (678)-624-0621  
www.eucatex.com.br

---

**Prevention:**

Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Do not breathe dust.  
Contaminated work clothing should not be allowed out of the workplace.  
In case of inadequate ventilation wear respiratory protection.  
Wash thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/protective clothing/eye protection.

**Response:**

**INHALATION:** Remove to fresh air. If persistent irritation, severe coughing or breathing difficulty occurs, get medical attention.

**EYE CONTACT:** Remove contact lenses. Flush eyes, including under eyelids, with large amounts of water. If irritation persists, get medical attention.

**SKIN CONTACT:** Wash affected areas with soap and water. If rash or persistent irritation or dermatitis occurs, get medical attention.

**INGESTION:** Not applicable under normal conditions of use. Get medical attention.

**Other information:**

NFPA + Health = 1, Flammability = 1, Reactivity = 0, Special Information = None

HMS + Health = \*1, Flammability = 1, Reactivity = 0, PPE = E \* Chronic Health Hazard

E = Safety glasses, gloves, and a dust respirator

**SECTION 3 COMPOSITION INFORMATION**

**MIXTURES:**

These wood products are composed of wood and resins.

Components shown below may appear in some or in various combinations in a particular product.

\* Wood contains trace amounts of various chemicals present in the environment which are absorbed by trees through natural growth.

Hardboard is free of Formaldehyde.

The Acrylic cured TopCoat does contain Formaldehyde.

Cured Acrylic top coat does not contain significant residual amounts of volatile solvents.

All products produced at EUCATEX mills are certified TO COMPLY TO THE C.A.R.B phase 2 emissions standards of the California Air Resource Board 17 CCR 93120.2(a)



Eucatex of North America  
11475 Great oaks way  
Alpharetta, Georgia 30022  
(678)-624-0160  
Fax (678)-624-0621  
www.eucatex.com.br

Only hazardous components above the appropriate cut-off-limit are shown

Chemical Name	Identifiers CAS	Cancer Designation
Wood Fibers	CAS : Not Available	Group 1/ IARC
Cobalt neodecanoate	27253-31-2	Group 2 / IARC
Hexanoic acid, 2-ethyl-, cobalt(+2) salt	136-52-7	Group 2/ IARC
Filler	14808-60-7/13463-67-7/7631-86-9	IARC-1/NIOSH-CA/NTP-K/TLV-A2/MAK-1
TopaCoat / Acrylic Resin(cured)	50-00-0	EPA-B1/IARC-2A/NIOSH-CA/NTP-R

Acrylic Top Coat Cured – (PNOS) PEL -TWA = 15mg/m3; PEL-TWA 5mg/m3, respiratory fraction; PEL-TWA 0.75ppm

#### SECTION 4. FIRST AID MEASURES

**INHALATION:** Remove to fresh air. If persistent irritation, severe coughing or breathing difficulty occurs, get medical attention.

**EYE CONTACT:** Remove contact lenses. Flush eyes, including under eyelids, with large amounts of water. If irritation persists, get medical attention.

**SKIN CONTACT:** Wash affected areas with soap and water. If rash or persistent irritation or dermatitis occurs, get medical attention. **INGESTION:** Not applicable under normal conditions of use **Most important symptoms and effects, both acute and delayed**

\* Refer to Section 11 - Toxicological Information.

#### Section 5. FIRE RATE AND FIRE FIGHTING MEASURES.

**RATE CLASSIFICATION:** Flame spread rate classifications are established by the model building codes for various types of construction.

The classifications commonly used are listed below:

Model Code	Flame Spread Rate
(1) Boca Class I	0-25
Boca Class II	26-75
Boca Class III	76-200
Boca Class IV	over 200

(2) SBCCI (Classifications are not listed. Flame spread rate values are specified for specific areas of buildings.)

(3) ICBO Class I	0-25
ICBO Class II	26-75
ICBO Class III	76-225

**FLAME SPREAD – Class III – under 200 – in accordance with ASTM E-84-91A and ANSI / AHA A 135.5**

**FLASH POINT:** Not applicable.

**EXPLOSIVE LIMITS:** Sawing, sanding or machining wood products can produce wood dust as a by-product. Wood dust is a strong to severe explosion hazard if a dust "cloud" contacts an ignition source. 212°F (100°C) has been suggested as the upper temperature limit for continuous exposure for wood without risk of ignition (wood dust may require a still lower

temperature). An airborne concentration of 40 grams of dust per cubic meter of air is often used as the lowest explosion limit (LEL) for wood dust.

Eucatex of North America  
11475 Great oaks way  
Alpharetta, Georgia 30022  
(678)-624-0160  
Fax (678)-624-0621  
www.eucatex.com.br



---

**HAZARDOUS COMBUSTION PRODUCTS:** Thermal-oxidative degradation, or burning, of wood can produce irritating and potentially toxic fumes and gases including carbon monoxide, aldehydes and organic acids.

**AUTOIGNITION TEMPERATURE:** 400°-500° F (204°-260°C)

**FIRE EXTINGUISHING MEDIA:** Water. Partially burned dust is especially hazardous if dispersed into the air. Remove burned or wet dust to open area after fire is extinguished.

## SECTION 6. ACCIDENTAL RELEASE MEASURES

Not applicable for product in purchased form. Sweep or vacuum dust for recovery or disposal. Wood dust clean-up and disposal activities should be accomplished in a manner to minimize creation of airborne dust.

## SECTION 7. HANDLING AND STORAGE

Wood products are combustible and, therefore, should not be subjected to temperatures exceeding the autoignition temperature. Water spray may be used to wet down wood dust generated by sawing, sanding or machining to reduce the likelihood of ignition or dispersion of dust into the air. See other sections of this MSDS for information on handling.

## SECTION 8. EXPOSURE CONTROLS/ PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Due to the explosive potential of wood dust when suspended in air, precautions should be taken during sanding, sawing or machining of wood products to prevent sparks or other ignition sources in ventilation equipment. Use of totally enclosed motors is recommended. Provide local exhaust as necessary to meet OSHA requirement.

**RESPIRATORY PROTECTION:** Wear NIOSH/OSHA approved respirator when the permissible OSHA exposure limits to wood dust may be exceeded. **EYE PROTECTION:** Recommend goggles or safety glasses as conditions indicate when sawing, sanding or machining wood products.

**SKIN PROTECTION:** Protective equipment such as gloves and outer garments may be needed to reduce skin contact. The following are wood dust exposure limits which are in accord with those recommended by OSHA in the 1989 revision of PELs.

The exposure limits were vacated in 1992; the present exposure limits governing wood dust are 15 mg/m<sup>3</sup> total dust and 5 mg/m<sup>3</sup> for the respirable fraction.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Solid. **BOILING POINT:** Not Applicable.  
**PH:** Not Applicable. **MELTING POINT:** Not Applicable.  
Applicable. **VAPOR PRESSURE:** Not Applicable. **SOLUBILITY IN WATER:**  
Insoluble. **VAPOR DENSITY:** Not Applicable. **SPECIFIC GRAVITY:** < 1.0

## SECTION 10. STABILITY AND REACTIVITY

**Stability:** stable

**CONDITIONS TO AVOID:** Wood dust generated from sawing, sanding or machining the product is extremely combustible. Keep in cool dry place away from ignition sources.

**INCOMPATIBILITY (MATERIALS TO AVOID):** Oxidizing agents and drying oils.

**HAZARDOUS COMBUSTION PRODUCTS:** Thermal-oxidative degradation, or burning, of wood can produce irritating and



Eucatex of North America  
11475 Great oaks way  
Alpharetta, Georgia 30022  
(678)-624-0160  
Fax (678)-624-0621  
www.eucatex.com.br

potentially toxic fumes and gases including carbon monoxide, aldehydes and organic acids.

**HAZARDOUS POLYMERIZATION:** Will not occur.

## SECTION 11. TOXICOLOGICAL INFORMATION

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	Identifiers CAS	Cancer Designation
Wood Fibers	CAS : Not Available	Group 1/ IARC
Cobalt neodecanoate	27253-31-2	Group 2 / IARC
Hexanoic acid, 2-ethyl-, cobalt(+2) salt	136-52-7	Group 2/ IARC
Filler	14808-60-7/13463-67-7/7631-86-9	IARC-1/NIOSH-CA/NTP-K/TLV-A2/MAK-1
Top Coat / Acrylic Resin(cured)	50-00-0 Formaldehyde	EPA-B1/IARC-2A/NIOSH-CA/NTP-R

**Formaldehyde:** Exposure to gaseous formaldehyde may cause temporary irritation to the nose and throat as well as lead to respiratory disorders. However, in a thorough review of sensory/respiratory irritation studies of formaldehyde from the standpoint of occupational exposure, an expert panel has observed exposure up to concentrations of 0.3 ppm failed to produce irritation. With regard to respiratory disorders, studies have concluded the threshold for long-term chronic pulmonary effects is between 0.4 and 3 ppm and for chronic obstructive pulmonary disease is 2 ppm. Pre-existing respiratory disorders may be aggravated by exposure.

*Acrylic Top Coat Cured – (PNOS) PEL -TWA = 15mg/m<sup>3</sup>; PEL-TWA 5mg/m<sup>3</sup>, respiratory fraction; PEL-TWA 0.75ppm*

**WOOD DUST:** Wood dust generated from sawing, sanding or machining this product may cause nasal dryness, irritation, coughing and sinusitis. The International Agency for Research on Cancer (IARC) and the National Toxicology Program (NTP) classify wood dust as a human carcinogen (Group I). This classification is based primarily on increased risk in the occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with exposure to wood dust. The evaluation did not find sufficient evidence to associate cancers of the oropharynx, hypopharynx, lung, lymphatic and hematopoietic systems, stomach, colon or rectum with exposure to wood dust.

## SECTION 12. DISPOSAL CONSIDERATIONS

This product is not considered hazardous waste under Federal Hazardous Waste Regulations 40 CFR 261. Please be advised, however, state and local requirements for waste disposal may be different from federal regulations.

Incinerate or landfill in accordance with local, state and federal regulations.

## SECTION 13. TRANSPORT INFORMATION

This product is not a DOT hazardous material

**OSHA:** Wood products are not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200. However, formaldehyde emissions from this product and wood dust generated by sawing, sanding or machining this product may be hazardous.



Eucatex of North America  
11475 Great oaks way  
Alpharetta, Georgia 30022  
(678)-624-0160  
Fax (678)-624-0621  
www.eucatex.com.br

---

**TSCA:** This product complies with TSCA inventory requirements.

**SARA 313:** None.

**ANSI A135.4 – 1995 - HARDBOARD:** This industry consensus standard offers manufacturers, consumers and the general public concerned with the product an effective guide developed under the consensus procedures of the American National Standards Institute.

**CANADIAN WHMIS:** This product(s) is not considered a controlled product.

## SECTION 15. REGULATORY INFORMATION

**OSHA:** Wood products are not hazardous under the criteria of the Federal OSHA Hazard Communication Standard 29 CFR 1910.1200. However, formaldehyde emissions from this product and wood dust generated by sawing, sanding or machining this product may be hazardous.

**TSCA:** This product complies with TSCA inventory requirements.

**SARA 313:** None.

**CALIFORNIA:** Proposition 65 provides for labeling and disclosure of the presence of chemical(s) known to the state to cause cancer or reproductive toxicity if ordinary use of the product will result in exposures above a no significant risk level. The products covered by this SDS contain formaldehyde and may, depending on conditions such as temperature and relative humidity, emit formaldehyde gas. Formaldehyde gas is listed under Proposition 65 as a chemical known to the State to cause cancer

### U.S. - California - Proposition 65 - Carcinogens List

- Fiberboard and ingredients (unless listed below) N/A Not Listed
  - Formaldehyde gas is listed under Proposition 65 as a chemical known to the State to cause cancer

•Wood dust as Wood Dust, all soft and hard woods N/A Carcinogens.

---

## SECTION 16. OTHER INFORMATION

### LABEL TEXT:

-----  
-----

Wood Products  
**CAUTION!**

**SAWING, SANDING OR MACHINING WOOD PRODUCTS CAN PRODUCE WOOD DUST WHICH CAN CAUSE A FLAMMABLE OR EXPLOSIVE HAZARD. WOOD DUST MAY CAUSE LUNG, UPPER RESPIRATORY TRACT, EYE AND SKIN IRRITATION. SOME WOOD SPECIES MAY CAUSE DERMATITIS AND/OR RESPIRATORY ALLERGIC EFFECTS. THE INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) HAS CLASSIFIED WOOD DUST AS A NASAL CARCINOGEN IN HUMANS.**

Avoid dust contact with ignition source.

Wood dust clean-up and disposal activities should be accomplished in a manner to minimize creation of airborne dust. Avoid breathing dust.

Avoid dust contact with eyes and skin.

**FIRST AID:** If inhaled, remove to fresh air. In case of contact, flush eyes and skin with water. If irritation persists, call a physician.

**IMPORTANT:** The information and data herein are believed to be accurate and have been compiled from sources believed to be reliable. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product in compliance with applicable federal, state and local laws and regulations. Eucatex make no warranty of any kind, express or implied, concerning the accuracy or completeness of the information and data herein. The implied warranties of merchantability and fitness for a particular purpose are specifically excluded. Eucatex will not be liable for claims relating to any party's use of or reliance on information and data contained herein regardless of whether it is claimed that the information and data are inaccurate, incomplete or otherwise misleading.

This Material Safety Data Sheet is being furnished for similar wood products produced by different manufacturers. Consult labels, stamps and markings on the product or packaging for the exact identity of the manufacturer.