



Steves and Sons Corporation

Veranda Steel Entry Door CRT-M-2

ENERGY PERFORMANCE RATINGS

Product Description* Default Frame** Wood	U-Factor ¹ / Solar Heat Gain Coefficient (SHGC)			
	Individual Option Number			
	1/4 Lite ≤410†	1/2 Lite ≤900†	3/4 Lite ≤1100†	Full Lite >1100†
Triple Pane Decorative IG	0.20 0.10	0.23 0.17	0.26 0.24	0.30 0.30
	00752-00001	00753-00001	00754-00001	00758-00001
1 Inch Decorative IG	0.23 0.11	0.28 0.19	0.32 0.26	0.36 0.33
	00458-00002	00459-00002	00460-00002	00461-00002
1 Inch IG Low E	0.21 0.10	0.24 0.17	0.27 0.24	0.30 0.30
	00478-00001	00479-00001	00480-00001	00481-00001
1 Inch IG Low E With Blinds	- -	0.27 0.11	- -	0.30 0.19
	-	00809-00001	-	00810-00001
1 Inch IG Low E With Grilles	0.21 0.09	0.24 0.16	0.27 0.22	0.30 0.27
	00582-00001	00583-00001	00584-00001	00585-00001
½ Inch IG Low E With Grilles	0.22 0.09	0.26 0.16	0.29 0.22	0.33 0.28
	00566-00001	00567-00001	00568-00001	00569-00001
Vent Lite IG	- -	0.43 0.16	- -	- -
	-	00830-00001	-	-

Flush / Embossed
00441-00001 U-Factor¹ 0.16 SHGC 0.01

Air Leakage - cfm.ft²

Manufacturer stipulates that these ratings conform to applicable NFRC procedures for determining whole product performance. NFRC ratings are determined for a fixed set of environmental conditions and a specific product size. NFRC does not recommend any product and does not warrant the suitability of any product for any specific use. Consult manufacturer's literature for other product performance information.
* #glazing layers / spacer type / low-e emissivity (surface) / gap fill / gap width (na=not applicable)

** per NFRC 100 † square inches ¹ btu/hr*ft²*F

*** Numbers below the performance ratings are referenced in the NFRC Certified Products Directory (e.g., ABC-X-1-00001-00001 or 123-X-1-00001-00001)

www.nfrc.org

ENERGY STAR® Certified in All 50 States

