ASSEMBLY INSTRUCTIONS 1 LIGHT SEMI FLUSH

Item: CH1868

- 1. Carefully unpack and identify each part to make sure you have everything ready for installation. Lay out each part on a clean flat area such as a table or the floor.
- 2. Shut down the main electrical supply from the fuse box or circuit breaker in your house or building.
- 3. Tighten the support screws (long) into the side of the mounting bracket (do not completely tighten the screws, they will be fully tightened later), secure by using the hex nut. The support screws (long) should extend long enough to protrude through the canopy when it is mounted. (Adjust as needed.)
- 4. Fasten the mounting bracket onto the outlet box using the 2 outlet box screws (short).
- 5. Connect the wires from the fixture to the power supply wires from the outlet box and cover with the wire connector.
 - A. Twist together the black wire from the fixture with the black wire from the outlet box. Cover with the wire connector.
 - B. Twist together the white wire from the fixture with the white wire from the outlet box. Cover with the wire connector.
 - C. Loop the bare copper ground wire from the fixture body under the head of the green screw on the mounting bracket, then connect it to the ground conductor from the supply circuit and cover with the wire connector.
- 6. Place the canopy assembly over the outlet box, allow the heads of the support screws (long) go through the holes of the canopy, then secure by tightening the cap nuts.
- 7. Remove the plastic bags from the crystal strands.
- 8. Unscew the socket ring from the socket located on the canopy assembly. Place the shade onto the socket and secure with the socket ring.
- 9. Install the bulb (not included) to the socket. Use one Max 60W medium base type A bulb or Max 9W medium base self-ballasted LED bulb.
- 10. Turn on the electrical power in your house or building to test the pendant lamp. Save these instructions for future use.

Cleaning

- Use only a soft cloth to dust and clean your new lamp.
- Do not use any chemicals, polishes or abrasives.

Warning: Do not immerse your lamp in water; doing so will damage the wiring.

ASSEMBLY INSTRUCTIONS 1 LIGHT SEMI FLUSH

Item: CH1868

Fixture Installation Drawing

