

# ASSEMBLY INSTRUCTIONS

## 3 LIGHT FLUSH MOUNT

Item: CH1870

1. Carefully unpack and identify each part to make sure you have everything ready for installation. Lay out each part on a clean flat area such as a table or the floor.
2. Shut down the main electrical supply from the fuse box or circuit breaker in your house or building.
3. Unscrew the four support screws from the canopy located on top of the fixture body, and remove the mounting bracket from the canopy.
4. Fasten the mounting bracket onto the outlet box using the 2 outlet box screws.
5. Connect the wires from the fixture to the power supply wires from the outlet box and cover with the wire connector.
  - A. Twist together the black wire from the fixture with the black wire from the outlet box. Cover with the wire connector.
  - B. Twist together the white wire from the fixture with the white wire from the outlet box. Cover with the wire connector.
  - C. Loop the bare copper ground wire from the fixture body under the head of the green screw on the mounting bracket, then connect it to the ground conductor from the supply circuit and cover with the wire connector.
6. Place the canopy of the fixture body over the outlet box, align the four holes of the canopy and the holes of the side of the mounting bracket, then tighten with the four support screws.
7. Remove the plastic bags from the crystal strands.
8. Install the bulbs (bulbs are not included) to each socket on the fixture body. Use three **Max 40W candelabra base type B** bulbs or **Max 9W candelabra base self-ballasted LED** bulbs.
9. Turn on the electrical power in your house or building to test the pendant lamp. Save these instructions for future use.

### Cleaning

- Use only a soft cloth to dust and clean your new lamp.
- Do not use any chemicals, polishes or abrasives.

**Warning:** Do not immerse your lamp in water; doing so will damage the wiring.

### Fixture Installation Drawing

