



**OLYMPIC ELITE Solid Color Advanced Stain + Sealant In One**

**GENERAL DESCRIPTION**

*Olympic ELITE* Advanced Stain + Sealant in One is a super-premium stain formulated to protect and enhance wood's natural beauty with exceptional richness and depth of color. *Olympic ELITE* solid color stain delivers a rich, durable, low-luster, opaque finish that covers the grain but accentuates wood texture. Nature-inspired hues complement wood, brick and stone.

Recommended for use on any properly prepared exterior wood, including decks, fences, siding, railings, outdoor furniture and other wood surfaces. Apply to new, dry, pressure-treated wood, uncoated new or weathered wood, or previously coated wood with a weathered, clear sealant, or semi-transparent stain.

**RECOMMENDED SUBSTRATES**

Wood

**APPLICATION INFORMATION**

**FOR EXTERIOR USE ONLY.** Stir thoroughly before and often during use. When using more than one can of the same color, intermix to ensure color uniformity.

Apply to new, dry, pressure-treated wood, uncoated new or weathered wood, or previously coated wood with a weathered, clear sealant or semi-transparent stain. Apply when air and surface temperatures are 35°F (2°C) to 90°F (32°C) and will remain above 35°F (2°C) for the next 24 hours.

**Application Method:** Apply two thin coats with a high quality brush, paint /stain pad, or by spray equipment. When applying by roller or spray, always back brush for best results. To help avoid lapmarks, apply to only a few boards at a time and maintain a wet edge.

**Thinning:** DO NOT THIN.

**Permissible temperatures during application:**

Material:	50 to 90°F	10 to 32°C
Ambient:	35 to 90°	2 to 32°C
Substrate:	35 to 90°	2 to 32°C

**PRODUCT INFORMATION**

80301	Base 1*
80302	Base 2*

\*Must be tinted.

Refer to the appropriate color formula book, automatic tinting equipment, and or computer color matching system for color formulas and tinting instructions.

**PRODUCT DATA**

<b>VOLUME SOLIDS*:</b>	34% +/- 2%
<b>WEIGHT SOLIDS*:</b>	43% +/- 2%
<b>VOC*:</b>	<100 g/L (0.8 lbs./gal.)

**WEIGHT/GALLON\*:** 9.7 lbs. (4.4 kg) +/- 0.2 lbs. (91 g)

\*Product data calculated on 80301.

**COVERAGE:** Approximately 350 to 500 sq. ft. (32.2 to 46.5 sq. meters) per gallon (3.78 L) depending upon wood texture and porosity. Coverage figures do not include loss due to surface irregularities and porosity or material loss due to application method or mixing.

**DRYING TIME:** Normally dries to touch in 30 minutes when applied in optimal temperatures of 50°F (10°C) to 85°F (29°C). Allow 2 to 4 hours between coats or before recoating. Application in high humidity or in temperatures below 50°F (10°C) may prolong drying and recoating times. Allow 24 to 48 hours of drying time before light foot traffic or replacing furniture. Allow new stain to cure 30 days before washing.

It is not recommended to apply product if rain is expected within 24 hours.

Drying times listed may vary depending on temperature, humidity, film build, color and air movement.

**CLEANUP:** Clean brushes and tools with warm, soapy water.

**DISPOSAL:** Contact your local environmental regulatory agency for guidance on disposal of unused product. Do not pour down a drain or storm sewer.

**FLASH POINT:** >200°F (93°C)

**FEATURES / BENEFITS**

**Features**

Advanced Stain + Sealant In One  
Color Rich™ Technology

4-Season™ Protection Package

Curated Palette

Low-luster Finish  
Self-Priming

**Benefits**

Protect & Beautify in one step

Tint bases & color formulas maximize durability. Color palette of rich wood- and nature-inspired hues excludes non- durable pigments. Formulas deliver color continuity with wood-inspired hues in semi-transparent and semi-solid opacities

Urethane-fortified resin combines strength & flexibility for toughness and resilience. Enhanced water proofing protection protects wood from water damage. Exceptional UV resistance to slow color fade Provides our best mildew and algae resistant coating

Colors selected for natural beauty and durability. Palette offers the most attractive hues for use on exteriors to increase the likelihood of a successful project and a satisfied customer.

Provides a more dirt and mildew resistant coating than the standard flat sheens  
No primer needed on most bare or previously coated surfaces

**OLYMPIC ELITE Solid Color Advanced Stain + Sealant In One****GENERAL SURFACE PREPARATION**

Surface must be dry and clean. Remove all dust, dirt, mildew, oil, loose wood fibers, and other contaminants. Previous coatings must be completely removed. To ensure proper penetration, weathered, dirty or mildewed surfaces should be cleaned with *OLYMPIC Deck Cleaner* prior to applying stain. After rinsing, allow wood to dry.

**WARNING!** If you scrape, sand, or remove old paint, you may release lead dust or fumes. **LEAD IS TOXIC. EXPOSURE TO LEAD DUST OR FUMES CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear a properly fitted NIOSH-approved respirator and prevent skin contact to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the USEPA National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead). Follow these instructions to control exposure to other hazardous substances that may be released during surface preparation.

**DECKS:** Clean weathered, dirty or mildewed surfaces with *OLYMPIC Deck Cleaner* prior to applying product.

**FENCES OR SIDING:** Remove and inhibit mildew with *OLYMPIC Deck Cleaner*. Before use, be sure to read and follow the instructions and warnings on the label.

**PRIME:** This product is self-priming over most substrates.

**EXTRACTIVE BLEEDING:** Some woods, such as redwood and cedar contain natural water-soluble colorings or extractives that tend to "bleed" or migrate to the surface. If extractive bleeding occurs, allow the coating to dry completely, then wash with a mild detergent solution and rinse with clear water.

**LIMITATIONS OF USE**

While this product provides a mildew resistant coating, growth may still occur if the substrate is not properly prepared prior to painting and/or if the substrate is consistently exposed to conditions conducive to mold, mildew, and algae. Examples of these conditions include, but are not limited to, under eaves, behind shrubbery and trees, and in areas that are consistently damp with little to no direct sunlight.

Do not apply when air, coating or surface temperatures are below 35°F (2°C). Avoid painting in direct sunlight or on hot surfaces. It is not recommended to apply product if rain is expected within 24 hours.

Not recommended for recently painted or sealed surfaces. Do not use on plastic, rubber, asphalt, tile, vinyl, concrete or any non-porous surface. **FOR EXTERIOR USE ONLY.**

**SAFETY PRECAUTIONS**

Before using the products listed in this publication, carefully read each product label and follow directions for its use. Please read and observe all the warnings and precautionary information on the product labels. Material Safety Data Sheets are available through our Sales Representative, Retailer or by calling (412) 492-5555.

Spray equipment must be handled with due care and in accordance with manufacturer's recommendation. High-pressure injection of coatings into the skin by airless equipment may cause serious injury.

**USE WITH ADEQUATE VENTILATION. KEEP OUT OF REACH OF CHILDREN.**

**PACKAGING**

Quart (946 mL)  
1-Gallon (3.78 L)  
3-Gallon (11.3 L)

The PPG logo is a registered trademark of PPG Industries Ohio, Inc. *Olympic and Olympic and Design* are registered trademarks and *ELITE, Color Rich Technology, 4-Season Protection Package* are trademarks of PPG Architectural Finishes, Inc.

PPG Architectural Finishes, Inc. believes the technical data presented is currently accurate; however, no guarantee of accuracy, comprehensiveness, or performance is given or implied. Improvements in coatings technology may cause future technical data to vary from what is in this bulletin. For complete, up-to-date technical information, call 1-800-426-6306.



PPG Industries, Inc.  
Architectural Coatings  
One PPG Place  
Pittsburgh, PA 15272  
[www.olympic.com](http://www.olympic.com)

Technical Services  
1-800-426-6306

Architect/Specifier  
1-888-PPG-IDEA

PPG Architectural Coatings Canada Inc.  
4 Kenview Boulevard  
Brampton, ON L6T 5E4

T.D. 80301 2/2014

Made in the  
**USA**