



BEHR® CHALK SPRAY PAINT

PRODUCT INFORMATION

BEHR® Chalk Spray Paint is designed to deliver a smooth, matte finish that can be applied over most existing surfaces with very little surface preparation. It has excellent adhesion and coverage. It is ideal for refreshing old and new wooden furniture, cast stone, concrete, and even metal surfaces to create one-of-a-kind accent pieces. It also features an ergonomic can shape that allows for more comfortable application.

RECOMMENDED USES:

Use on properly prepared surfaces such as:

- Wood
- Metal
- Plastic
- Cast Stone
- Wicker

COLOR AND SHEEN ON THE CAP IS REPRESENTATIVE OF THE PRODUCT. Not for touch-up on surfaces previously painted with BEHR CHALK DECORATIVE PAINT.

PRODUCT SPECIFICATIONS:

Colors:

70244	BEHR Chalk Spray Paint Miniature Rose
70844	BEHR Chalk Spray Paint Tin White
71044	BEHR Chalk Spray Paint Pale Moon
72844	BEHR Chalk Spray Paint Surf
73544	BEHR Chalk Spray Paint Gingham
74544	BEHR Chalk Spray Paint Classic Noir
†714044	BEHR Chalk Spray Paint Clear

Sheen: < 5 @ 85° F

Resin Type: Modified Alkyd

Net Weight: 12 oz / 340 g

***% Solids by Volume:** 17% ± 2%

***% Solids by Weight:** 21% ± 2%

Max VOC (by weight): 60%

Max Product Weighted MIR: 0.80

Coverage: 12 sq ft per can, depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

APPLICATION:

- Cover adjacent areas to avoid overspray.
- Shake can vigorously for one minute after mixing ball begins to rattle and often during use.
- Hold can upright, moving from side-to-side while spraying lightly and evenly about 12" from area being painted.
- Always start and finish spraying off the object. Each spray pass should overlap the previous pass by half.
- Test your spray application technique on a scrap surface or inconspicuous area before starting the project.
- Apply multiple thin coats to prevent dripping and sagging. Two to three thin coats produce best results. Allow to dry between each coat.

†NOTE: Use BEHR Chalk Spray Paint Clear No. 714044 over glossy surfaces to create a matte finish. For high-use surfaces, such as coffee tables, dining tables or vanities, spray over surfaces previously painted with BEHR Chalk Style Paint for a permanent seal.

Dry Time: @ 77°F (25° C) and 50% RH:

Allow to dry between each coat.

To Touch: 15 minutes

To Recoat: before 1 hour or after 24 hours

SURFACE PREPARATION:

- The surface must be clean, free of dust, grease, wax, peeling paint, mold and mildew. If washing is necessary, use a nonsoapy detergent or a TSP substitute. Rinse well and allow to dry.
- Scrape off loose paint and sand to a smooth surface.
- For maximum adhesion, sand glossy surfaces thoroughly before coating. For optimal adhesion to difficult surfaces apply a coat of primer such as BEHR® Interior/Exterior Bonding Primer, BEHR® Multi-Surface Interior/Exterior Primer & Sealer No. 436 or KILZ® Original Aerosol (for smaller areas).

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

CLEAN-UP/DISPOSAL:

- Clear spray valve immediately after use by turning can upside down and spraying until only clear gas is released. If spray nozzle becomes clogged, remove and clean with VOC-compliant paint thinner or mineral spirits where allowed. Otherwise use acetone.
- Clean fresh overspray with VOC-compliant paint thinner or mineral spirits. Otherwise use acetone. Remove dried paint with paint remover, but test small area first to ensure paint remover does not damage substrate.
- Please consider donating any unused product. For recycling or disposal information contact your local household refuse collection service.

CAUTIONS/LIMITATIONS:

- Do not stick pins or wire into can opening.
- Ensure adequate ventilation when spraying indoors.
- For best results, apply when air, material and surface temperatures are between 50°F and 90°F. Avoid painting in direct sunlight. Temperature and humidity extremes can affect dry time and final appearance.
- Shelf life under normal conditions is two years unopened.

GENERAL INFORMATION:

VENTILATION REQUIRED: To avoid inhalation and combustion hazards (see below), DO NOT use this product unless you can achieve cross ventilation by opening windows and doors during application and drying.

CONTAINS ACETONE, N-BUTYL ACETATE, PROPANE, ISOBUTANE, ISOBUTYL ACETATE, PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE, TOLUENE AND XYLENE. VAPOR HARMFUL. May affect the brain or nervous system causing dizziness, headache or nausea. **CAUSES SERIOUS EYE DAMAGE. IRRITATES SKIN, NOSE AND THROAT.** Do not breathe vapors or spray mist. If you experience eye watering, headaches or dizziness, increase fresh air, wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. **VAPORS MAY IGNITE EXPLOSIVELY.** Do not spray near sparks, heat or open flame. Do not smoke. Vapors are heavier than air and can travel at floor level to distant ignition sources. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone. **WARNING-CONTENTS UNDER PRESSURE.** Do not puncture or incinerate container. Do not expose to heat or store at elevated temperatures above 120°F. Prolonged exposure to sun may cause bursting.

* Values given here are from BEHR® CHALK SPRAY PAINT White color.

This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a Behr Paint Company representative, call 1-800-854-0133 Ext. 2 (U.S.A. only). ©2020 Behr Process Corporation, Santa Ana, CA 92705 U.S.A.





BEHR® CHALK SPRAY PAINT

First Aid: If you experience difficulty breathing, leave the area to obtain fresh air. If difficulty continues, get medical attention immediately. If swallowed, call physician immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water.

KEEP OUT OF REACH OF CHILDREN.