

Customer: Beyond Paint	Job Name: All In One Pint Furniture & More	Part/rev#: RMC-789	Corner Radius: 0.125"
Shop Order: 4221	Across x Around Size: 2.5" x 11"	Die Tooth: 152 Die #: DC-397-40	Plate Tooth: -
Material Face Stock: 1095 Semi-Gloss	Adhesive: Permanent	Liner: 40#	Completed by: LN Checked by:
# of Colors: 4	Print Colors: 4 Color Process	PMS 1109 Gloss UV	DIELINE 4000

Colors shown on proofs are for illustration of the indicated PMS #s. Colors will be matched on press to the PMS standards. Please check all aspects of the proof and specifications before approving. **Upon receipt of the signed proof, we will proceed with your order.**

emailed to: _____ date: ____/____/____

Approved As Is Submit New Proof

Signature Date

11.0"

BEYOND PAINT®
For all your home projects

QUICK · EASY · DURABLE

- ALL-IN-ONE -
BONDS · PRIMES · SEALS

ONE-STEP PROCESS
Advanced NANO-TECHNOLOGY

NO STRIPPING
NO SANDING
NO PRIMING

FURNITURE, CABINETS, COUNTERTOPS & MORE

1 PINT
16 FL OZ
473 ML

PERFECT FOR

Wood Linoleum Glass Laminate Plastic Varnish Tile Masonry Metal Painted Surfaces

Surface must be CLEAN, DRY, GREASE, OIL and WAX FREE. Use an all-purpose degreaser. Avoid TSP & soaps when prepping.

BEYOND PAINT® is lightly textured matte/eggshell finish; which eliminates stroke marks, provides a finish that conceals imperfections and offers versatility in application.

RECOMMENDED TOOLS:
 ☉ Tray. ☉ Fabric or woven roller nap (3/8 inch nap) and handle. ☉ Brush for stippling creviced areas.
 ☉ If spraying use a wide nozzle HVLP sprayer.

Seal BEYOND PAINT® countertops and outdoor projects with BEYOND PAINT® Multi-Purpose SEALER.

EASY TO USE INDOOR DIRECTIONS:
 ☉ Using a soft bristle brush, simply "mush" or "stipple" into crevice areas.
 ☉ Roll all possible areas (an all-purpose fabric roller is preferred).
 ☉ Avoid traditional brush strokes.
 ☉ Two coats are recommended; allow 2-4 hours drying time between coats.
 ☉ Clean up with soap and water.

EASY TO USE COUNTERTOP AND OUTDOOR DIRECTIONS:
 ☉ Follow above directions.
 ☉ Allow to dry for at least 24 hours. ☉ Apply two LIGHT coats of Multi-Purpose Sealer (leaves a light satin sheen). ☉ For granite-like finish apply countertop flecks before applying sealer (sold separately).

EASY CARE DIRECTIONS:
 Allow 7 days for paint to fully bond. Maintain thereafter, with mild soap and water. Surfaces may take up to 30 days to fully cure. Keep your BP project away from extreme heat or standing water.

Warning: Causes serious eye irritation. Wear protective gloves. Wear eye or face protection. Wash hands thoroughly after handling. **If in eyes:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **Hazardous ingredients:** Alcohols, C12-14 secondary, ethoxylated ammonia.

Proper Use and Ingredients- Recommended shelf life of up to 18 months. Use and application of this product are beyond the control of the manufacturer, distributor and dealer. Liability, if any, is limited to replacement of only product proven to be defective in manufacturing. Store in climate controlled area. Paint can freeze.

2655 Ulmerton Rd. #162
Clearwater, FL 33762
866.266.0650 • Made in the USA
VISIT US AT WWW.BEYONDPAIN.COM

