



PAINT + PRIMER AEROSOL ENAMEL



PRODUCT INFORMATION

BEHR® Paint + Primer Aerosol Enamel delivers a premium finish with excellent adhesion to multiple surfaces. Ideal for small indoor and outdoor projects and highly detailed surfaces. BEHR Paint + Primer Aerosol Enamel can be used on wood, metal, plastic, cast stone and wicker. The comfort tip reduces finger fatigue and delivers a great application experience.

RECOMMENDED USES:

Use on properly prepared surfaces such as:

- Wood
- Metal
- Plastic
- Cast Stone
- Wicker

CONTAINER CAP PROVIDES CLOSE APPROXIMATION OF COLOR AND SHEEN OF THE PRODUCT. Not for touch-up on surfaces previously painted with non-aerosol BEHR paint.

PRODUCT SPECIFICATIONS:

Colors:

B000144 Black Gloss	B001344 Venom Gloss
B000244 Orion Gray Gloss	B001444 Tropics Gloss
B000344 Lunar Surface Gloss	B001544 Mayan Treasure Gloss
B000444 Hidden Sea Glass Gloss	B001644 Sugar Beet Gloss
B000544 Inked Gloss	B001744 Outdoor Café
B000644 Blazing Bonfire Gloss	B001844 Khaki Shade Gloss
B000744 Baronial Brown Gloss	B001944 White Gloss
B000844 No More Drama Gloss	B002044 White Flat
B000944 Flirt Alert Gloss	B002144 Black Flat
B001044 Unmellow Yellow Gloss	B002244 Lunar Surface Flat
B001144 Luck of the Irish Gloss	B002344 Clear Flat
B001244 Congo Gloss	B002444 Resort Sunrise Gloss

Finish:

Flat: <5 @ 60

Gloss: >80 @ 60

Sheen level depends on porosity of surface and various surface irregularities.

Resin Type: Modified Alkyd

Net Weight: 12 oz / 340 g

***% Solids by Weight:** 20% ± 2%

***% Solids by Volume:** 16% ± 2%

Max VOC (by weight): 60%

Max Product-Weighted MIR:

Flat: 0.80

Non-Flat: 0.95

Coverage: 12 sq ft per can, depending on the surface texture, porosity and application method. Does not include the loss of material from spraying.

SURFACE PREPARATION:

- The surface must be clean, free of dust, grease, wax, peeling paint, mold and mildew. If washing is necessary, use a non-soapy detergent or a TSP substitute. Rinse well and allow to dry.
- Scrape off loose paint and sand to a smooth surface.
- For maximum adhesion, sand glossy surfaces thoroughly before coating.

Stain-Blocking:

- If stain-blocking performance is required, apply a coat of primer such as KILZ® ORIGINAL Interior/Exterior Oil-Based Aerosol Primer No. 1008.

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Center at 1-800-424-LEAD or log on to www.epa.gov/lead.

APPLICATION:

- Shake can vigorously for 1 minute after mixing ball begins to rattle and often during use.
- Test your spray application technique on a scrap surface or inconspicuous area before starting the project.
- Hold can upright, moving from side-to-side while spraying lightly and evenly about 12" from area being painted. Always start and finish spraying off the object. Each spray pass should overlap the previous pass by half.
- Apply multiple thin coats to prevent dripping and sagging. Allow to dry between each coat.

Dry Time: @ 77°F (25°C), 50% RH:

Longer dry time required in cooler temperatures and in higher humidity.

To Touch: 15 minutes

Re-coat: Before 1 hour or after 24 hours

CLEAN-UP/DISPOSAL:

- Clear spray valve immediately after use by turning can upside down and spraying until only clear gas is released. If spray nozzle becomes clogged, remove and clean with paint thinner or mineral spirits where allowed.
- Do not stick pins or wire into spray nozzle opening.
- Clean fresh overspray with VOC-compliant paint thinner or mineral spirits. Otherwise use acetone. Remove dried paint with paint remover, but test small area first to ensure paint remover does not damage substrate.
- Wipe off tip before storing.
- Do not burn or place in home trash compactor.

- Do not stick pins or wire into spray nozzle opening.
- For recycling or disposal information, contact your household refuse collection service.

CAUTIONS/LIMITATIONS:

- Temperature and humidity extremes can affect dry time and final appearance.
- Apply if surface, air and product temperatures are between 50°-90°F.
- Avoid painting in direct sunlight.
- Avoid spraying in very windy and dusty conditions.
- Ensure adequate ventilation when spraying indoors.
- Cover adjacent areas to avoid overspray.
- Do not apply to galvanized steel.

GENERAL INFORMATION:

VENTILATION REQUIRED: To avoid inhalation and combustion hazards (see below), DO NOT use this product unless you can achieve cross ventilation by opening windows and doors during application and drying. **CONTAINS ACETONE, N-BUTYL ACETATE, PROPANE, ISOBUTANE, ISOBUTYL ACETATE, PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE, TOLUENE AND XYLENE. VAPOR HARMFUL.** May affect the brain or nervous system causing dizziness, headache or nausea. **CAUSES SERIOUS EYE DAMAGE. IRRITATES SKIN, NOSE AND THROAT.** Do not breathe vapors or spray mist. If you experience eye watering, headaches or dizziness, increase fresh air, wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. **VAPORS MAY IGNITE EXPLOSIVELY.** Do not spray near sparks, heat or open flame. Do not smoke. Vapors are heavier than air and can travel at floor level to distant ignition sources. Extinguish all flames and pilot lights and turn off stoves, heaters, electric motors, high intensity lights and other sources of ignition during use and until all vapors are gone. **WARNING-CONTENTS UNDER PRESSURE.** Do not puncture or incinerate container. Do not expose to heat or store at elevated temperatures above 120°F. Prolonged exposure to sun may cause bursting. **FIRST AID:** If you have difficulty breathing, leave area to obtain fresh air. If difficulty continues, get medical attention immediately. If swallowed, call physician immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. **KEEP OUT OF REACH OF CHILDREN.**

*Values given here are from BEHR® Paint + Primer Aerosol Enamel White color.

This information is provided "as is" and no representations or warranties, either express or implied, of merchantability, fitness for a particular purpose or of any other nature are made with respect to this information or to any product referred to in this information. For SDS or to consult with a technical service representative, call 1-800-854-0133, Ext.2 (U.S.) • www.behr.com ©2019 Behr Process Corporation, Santa Ana, CA 92705 U.S.A.

