TECHNICAL DATA



KRUD KUTTER[®] PARTS WASHER CLEANER & DEGREASER

DESCRIPTION AND USES

Krud Kutter[®] Parts Washer is formulated with Prevent-X[™] Corrosion Inhibitor to resist future corrosion, rust and oxidation caused by the elements. An industrial strength, aqueous solution it is a safe alternative to hazardous cleaning chemicals such as mineral spirits and other solvents.

This multi-purpose formula is designed to be used in immersion, ultrasonic, manual, and spray applications. Can be used on aluminum, copper, carbon steel, acrylic, vinyl, stainless steel, iron, tin, titanium, brass, bronze, plastic, rubber, powder coated surfaces and more. It safely and effectively removes grease, grime, oils, carbon, ink and other organic deposits.

PRODUCTS			
Description			
1-Gallon Bottle			
5-Gallons			
55-Gallon Drum			

PRODUCT APPLICATION

DIRECTIONS

IMMERSION PARTS CLEANER DIRECTIONS:

Pour cleaner into your container to the desired level, based on the amount of parts to be cleaned. Immerse parts to be cleaned in the solution. Cleaning time will depend on type and thickness of soils, and will vary from minutes to overnight. To determine if items have been cleaned, periodically lift parts out of container. It may be necessary to remove heavy soils with a wire brush or scrub pad, and this can be done over the dipping container or separate container. Once complete, the soils will separate from the parts and may float to the top of the container. An oil skimmer is suggested such as a floating absorber and should be changed periodically. Final cleanup can be completed by using compressed air or water wash.

KRK-21

SPRAY/MANUAL DIRECTIONS:

Can also be used to clean heavy equipment on site. For heavy soils apply full strength with a pump sprayer or manual application. For light to medium soils dilute the product 1 to 10 (12 oz. of concentrate to 1 gallon of water), or run full strength through a pressure washer chemical injector or reservoir tank. Allow cleaner to penetrate soils for 5-10 minutes and wash off. Contains anti-corrosive agents to safeguard pressure washer parts.

SAFETY INSTRUCTIONS: Rubber gloves and safety glasses are recommended

CAUTION: EYE AND SKIN IRRITANT. In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. **Do not induce vomiting.** Get medical attention.

KEEP OUT OF REACH OF CHILDREN.



TECHNICAL DATA

KRUD KUTTER[®] PARTS WASHER CLEANER & DEGREASER

PHYSICAL PROPERTIES

		PARTS WASHER CLEANER & DEGREASER
Composition		Proprietary Ingredients in a Water-based Solution
Weight	Per Gallon	8.7 lbs.
	Per Liter	1.04 kg
Solids by Weight		7.5%
Odor		Detergent
Color		Colorless
рН		12-13
VOC		0.5%
Practical Coverage		Spray/Manual Application Heavy Soils (Full Strength) 1-Gallon – 200-300 square feet
		Light/Medium Soils (10 to 1) 1-Gallon – 2,200-3,300 square feet Light/Medium Soils (10 to 1) 5-Gallon – 11,000-16,500 square feet
Shelf Life		NA
Flash Point		>200°F (93°C)
Caution!		CAUTION: EYE AND SKIN IRRITANT. In case of contact with eyes or skin, flush with water for at least 15 minutes. If irritation persists, seek medical attention. If swallowed, take large amounts of water. Do not induce vomiting. Get medical attention. KEEP OUT OF REACH OF CHILDREN.
Safety Informa	tion	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.



Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, Illinois 60061 An RPM Company

Phone: 877•385•8155 www.rustoleum.com